



593 SERIES **PRISM®** Surface Mount LED 3mm Round Lens

APPLICATIONS

Data center infrastructure
Telecommunication
Electronic test and
measurement instruments
Automation
Medical
Wireless infrastructure

CERTIFICATIONS & RATINGS


RoHS compliant

FEATURES & BENEFITS


- SMT LED Technology designed to survive 260°C peak reflow temperature
- Eliminates wave soldering process
- Black, low profile PPA housing enhances the contrast ratio for better clarity
- Compatible with automatic pick-and-place equipment for reduced installation costs
- Ideal for limited space applications and board edge mounting

DIMENSIONS inches [mm]


FRONT VIEW




SIDE VIEW




BOTTOM VIEW



Single-Color LED




Bi-Color LED & Tri-Color LED
Scale 6.000



RECOMMENDED PAD LAYOUT


Fig. 1



Pin 1 = Cathode; Pin 2 = Anode

RECOMMENDED PAD LAYOUT

Fig. 2



For multi-color LED pin references, see table

SINGLE-COLOR LED PIN REFERENCE

Code	LED Color	Pin 1	Pin 2
20	Red	Cathode	Anode
21	Red	Cathode	Anode
26	Blue	Cathode	Anode
27	Yellow	Cathode	Anode
28	White	Cathode	Anode
40	True Green	Cathode	Anode

MULTI-COLOR LED PIN REFERENCE

Code	LED Color	Pin 1	Pin 2	Pin 3	Pin 4
30	Red / Green	Red Cathode	Red Anode	Green Anode	Green Cathode
31	Yellow / Green	Yellow Cathode	Yellow Anode	Green Anode	Green Cathode
32	Red / Yellow	Red Cathode	Red Anode	Yellow Anode	Yellow Cathode
33	Yellow/Green InGaN	Green Cathode	Green Anode	Yellow Cathode	Yellow Anode
34	Red/Blue	Red Cathode	Red Anode	Blue Anode	Blue Cathode
37	Red / Green / Blue	Red Cathode	Common Anode	Green Cathode	Blue Cathode
42	Red / Green / Blue	Red Cathode	Common Anode	Green Cathode	Blue Cathode

OPERATING CHARACTERISTICS AT 25°C AMBIENT

13" Reel	LED Color	Luminous Intensity (mcd)	Forward Voltage (V)		Dominant Wavelength (nm)	Reverse Current (μA)	MSL Rating	LED Position	
		Typ.	Min.	Max.	Typ.	Max.			
		IF=2mA							
593-303030-313F	Red	5	1.7	2.2	630	10	2	1	
	Green	5			570				
	Red	5	1.7	2.2	630	10		2	
	Green	5			570				
	Red	5	1.7	2.2	630	10		3	
	Green	5			570				
		IF=2mA							
593-303126-413F	Red	5	1.7	2.2	630	10	3	1	
	Green	5			570				
	Yellow	6	1.7	2.2	587	10		2	
	Green	5			570				
		IF=10mA							
	Blue	95	2.8	3.5	470	10		3	
		IF=2mA							
593-313131-313F	Yellow	6	1.7	2.2	587	10	2	1	
	Green	5			570				
	Yellow	6	1.7	2.2	587	10		2	
	Green	5			570				
	Yellow	6	1.7	2.2	587	10		3	
	Green	5			570				
		IF=20mA							
593-323232-313F	Red	60	1.8	2.3	633	10	2	1	
	Yellow	50	1.9	2.4	587				
	Red	60	1.8	2.3	633	10		2	
	Yellow	50	1.9	2.4	587				
	Red	60	1.8	2.3	633	10		3	
	Yellow	50	1.9	2.4	587				
593-333321-313F	Yellow	300	1.8	2.4	590	10	3	1	
	InGan Green	500	2.8	3.4	520				
	Yellow	300	1.8	2.4	590	10		2	
	InGan Green	500	2.8	3.4	520				
	Red	60	1.8	2.5	630	10		3	
593-333333-313F	Yellow	300	1.8	2.4	590	10	3	1	
	InGan Green	500	2.8	3.4	520				
	Yellow	300	1.8	2.4	590	10		2	
	InGan Green	500	2.8	3.4	520				
	Yellow	300	1.8	2.4	590	10		3	
	InGan Green	500	2.8	3.4	520				



OPERATING CHARACTERISTICS AT 25°C AMBIENT

13" Reel	LED Color	Luminous Intensity (mcd)	Forward Voltage (V)		Dominant Wavelength (nm)	Reverse Current (μA)	MSL Rating	LED Position
		Typ.	Min.	Max.	Typ.	Max.		
		IF=20mA						
593-373321-313F	Red	150	1.8	2.4	620	10	5a	1
	Green	400	2.8	3.6	523			
	Blue	60	2.8	3.6	470			
	Yellow	300	1.8	2.4	590	10		2
	InGan Green	500	2.8	3.4	520			
	Red	60	1.8	2.5	630			
593-373737-413F	Red	150	1.8	2.4	620	10	5a	1
	Green	400	2.8	3.6	523			
	Blue	60	2.8	3.6	470			
	Red	150	1.8	2.4	620	10		2
	Green	400	2.8	3.6	523			
	Blue	60	2.8	3.6	470			
	Red	150	1.8	2.4	620	10		3
	Green	400	2.8	3.6	523			
	Blue	60	2.8	3.6	470			
593-402627-413F	True Green	400	2.8	3.5	525	10	3	1
	Blue	100	2.8	3.5	470	10		2
	AlInGaP Yellow	130	1.9	2.4	587	10		3
593-424242-413F	Red	50	1.5	2.4	620	10	3	1
	Green	300	2.8	3.6	523	50		
	Blue	50	2.8	3.6	470	50		
	Red	50	1.5	2.4	620	10		2
	Green	300	2.8	3.6	523	50		
	Blue	50	2.8	3.6	470	50		
	Red	50	1.5	2.4	620	10		3
	Green	300	2.8	3.6	523	50		
	Blue	50	2.8	3.6	470	50		

ABSOLUTE MAXIMUM RATINGS AT 25°C AMBIENT

	Codes																Units					
	20	21	26	27	28	30		31		32		33		34		37		40	42			
	Red	Red	Blue	Yellow	White	Red	Green	Yellow	Green	Red	Yellow	Yellow	Green	Red	Blue	Red		Green	Blue	True Green	Red	Green
Continuous Forward Current	30	30	30	30	30	15		15		30		20		20		30		30	50	30	30	mA
Reverse Voltage	12	5	5	12	5	12		12		12		5		5		5		5	5			V
Peak Forward Current	250	185	100	200	100	100		100		200		125		100		100		100	130	100	100	mA
Operating Temperature Range	-40°C to +85°C																				°C	
Storage Temperature Range	-40°C to +100°C																				°C	


TAPE AND REEL SPECIFICATIONS



* 13" Reel Per EIA standard 481-2 on 56mm wide carrier tape
 * Quantity = 150 Pcs/reel in vacuum sealed bag
 * Label and color dots on reel and on bag
 * Label to include P/N, qty. per bag, MFG date, LED lot no., LED color, LED bin Intensity for all LEDs
 corner of label on reel indicates moisture sensitivity level
 aluminum barrier bag includes MSL label

REFLOW SOLDERING PROFILE:

Note: Reflow soldering should not be done more than two times.



Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com

Warranty Statement: Except for the warranty expressly provided for at: www.dialight.com/resources/warranties/, Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.