



NOTES:

1. MATERIALS AND FINISHES:
 BODY, INNER BODY - BRASS, NICKEL PLATING
 CONTACT - BeCu, GOLD PLATING
 INSULATOR - PTFE, NATURAL
 FERRULE - COPPER, NICKEL PLATING
 HEAT SHRINK TUBING - CROSSLINKED POLYOLEFIN, BLACK
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
 B. FREQUENCY RANGE: DC - 6 GHz
 C. VSWR: 1.20 MAX. @ DC - 3 GHz
 1.30 MAX. @ 3 - 6 GHz
 D. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS. MIN.
3. MECHANICAL:
 A. DURABILITY: 500 CYCLES MIN.
 B. TEMPERATURE RANGE: -65°C TO +165°C
 C. CONNECTOR MEETS IP 67 REQUIREMENTS IN MATED CONDITION.


4. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: PACKING TO BE MARKED
 "AMPHENOL RF, 82-6809 AND DATE CODE"
 C. FERRULE AND HEAT SHRINK TUBE ARE PACKAGED LOOSE
5. CABLE ASSEMBLY INSTRUCTIONS:
 A. TRIM CABLE AS SHOWN
 B. SLIDE HEAT SHRINK TUBING, FERRULE ONTO CABLE.
 C. FLARE BRAID SLIGHTLY AND INSERT CABLE INTO BODY UNTIL BOTTOMED.
 D. CRIMP FERRULE OVER BRAID WITH 0.216" HEX DIE.
 E. APPLY HEAT SHRINK TUBING OVER FERRULE.
 F. HEAT SHRINK TUBING SHOULD FULLY (360 DEG) COVER THE BUMP ON BODY AND END WITHIN AREA "A"

6. SHOW CABLE ENTRY DIMENSIONS.

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	24-DEC-25	17703	LEO
B	ONE CRIMP WAS EZ CRIMP	05-FEB-26	17755	VK



RECOMMENDED CABLE STRIPPING DIMENSIONS



CUSTOMER OUTLINE DRAWING
 ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE: <0.5mm = ±0.05mm [-0.020 = ±0.002] 0.5 - 6mm = ±0.1mm [+0.020 - 0.236 = ±0.004] >6.00 - 30mm = ±0.2mm [+0.236 - 1.181 = ±0.008] >30.00 - 120mm = ±0.3mm [+1.181 - 4.725 = ±0.012]		MATERIAL SEE NOTES		TITLE N STR JACK ONE CRIMP FOR LMR 200 CABLE (SOLID CENTER CONDUCTOR)		Amphenol RF	
THIRD ANGLE PROJ.		REFERENCE		ENGR.1 THAMBI RAJ ENGR.2 JACK LIANG DATE 26-FEB-25		SHEET NO. 2 OF 2 SCALE: 4.0:1.0		DRAWING NO. 82-6809 ITEM NO. 82-6809 PART NO. 82-6809	
EAR# 12096		ANGLES = ±1°		DATE		SIZE B		REV B	