





NOTES:

1. MATERIALS AND FINISHES:
 BODY, OUTER CONTACT &
 COUPLING NUT - BRASS, NICKEL PLATING
 CONTACT - BeCu, GOLD PLATING
 INSULATOR - PTFE, NATURAL
 GASKET - SILICONE RUBBER, RED
 RETAINING RING - SUS 304, NATURAL
 FERRULE - COPPER, NICKEL PLATING
 HEAT SHRINK TUBING - CROSSLINKED POLYOLEFIN, BLACK
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
 B. FREQUENCY RANGE: DC - 6 GHz
 C. VSWR: 1.20 MAX. @ DC - 3 GHz
 1.30 MAX. @ 3 - 6 GHz
 C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS, MIN.
3. MECHANICAL:
 A. DURABILITY: 500 CYCLES MIN.
 B. TEMPERATURE RANGE: -65°C TO +165°C
 C. CONNECTOR MEETS IP 67 REQUIREMENTS IN MATED CONDITION.

4. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: PACKAGING TO BE MARKED
 "AMPHENOL RF, 82-6813 AND DATE CODE"
 C. FERRULE AND HEAT SHRINK TUBE ARE PACKAGED LOOSE
 5. RECOMMENDED CABLE ASSEMBLY INSTRUCTIONS:
 A. TRIM CABLE AS SHOWN
 B. SLIDE HEAT SHRINK TUBING AND FERRULE ONTO CABLE.
 C. FLAIR BRAID SLIGHTLY AND INSERT CABLE INTO BODY UNTIL BOTTOMED.
 D. CRIMP FERRULE OVER BRAID WITH 0.216" HEX DIE.
 E. APPLY HEAT SHRINK TUBING OVER FERRULE.
 F. HEAT SHRINK TUBING SHOULD FULLY (360 DEG) COVER THE
 BUMP ON BODY AND END WITHIN AREA "A"
 6. RECOMMENDED COUPLING TORQUE : 6-10 IN-LBS.
7. SHOW CABLE ENTRY DIMENSIONS.

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	24-DEC-25	17704	LEO
B	ONE CRIMP WAS EZ CRIMP	05-FEB-26	17755	VK



CUSTOMER OUTLINE DRAWING
 ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC (INCHES) AND TOLERANCES ARE: <0.5mm = ±0.05mm [-0.020 = ±0.002] 0.5 - 6mm = ±0.1mm [-0.020 - 0.236 = ±0.004] >6.00 - 30mm = ±0.2mm [-0.236 - 1.181 = ±0.008] >30.00 - 120mm = ±0.3mm [-1.181 - 4.725 = ±0.012]		MATERIAL SEE NOTES		TITLE N STR PLUG ONE CRIMP FOR LMR 200 CABLE (SOLID CENTER CONDUCTOR)		Amphenol RF	
THIRD ANGLE PROJ.		REFERENCE		ENGR.1 KARTHIK		ENGR.2 JACK LIANG		DATE 24-FEB-25	
EAR# 12096		ANGLES = ±1°		SHEET NO. 2 OF 2		SCALE: 3.6:1.0		DRAWING NO. 82-6813 ITEM NO. 82-6813 PART NO. 82-6813	