

526-2,139 USG | 1,993-8,096 L

FIREPRO

FIRE-PROTECTED FUEL STORAGE

With UL2085 certification, these tanks are built to exceed the toughest fire safety and environmental standards and feature a fire-rated, insulated, ballistic and impact resistant design. FirePro tanks provide unmatched protection and compliance for both permanent and temporary installations.



BENEFITS



SAVES SPACE* *excluding FPT2000

Easily stackable when empty (up to 2 high) to save space in your yard.



COMPLIANCE

UL2085 and CARB-approved for peace of mind in the most demanding jurisdictions.



READY TO MOVE

Four-way fork pockets for quick and easy maneuvering and mobility when empty.



TURNKEY

Built for your fueling needs with pre-installed accessories. Arrives onsite ready to go.



SECURE

Lockable equipment cabinet keeps fuel, ports and equipment safe.



GUARANTEED

Industry leading 8-year tank warranty. We've got you covered.

APPLICATION USES

- On-site fleet refueling
- Fuel Islands
- Remote & mega jobsites
- Highly regulated sites
- Extended runtime

FEATURES

- Venting fitted for Diesel, Gas, CARB
- Equipment Rails
- Four-Way Fork Pockets
- Stackable Corner Brackets **excluding FPT2000*
- Built-In Lockable Spill Box (UL2583 Compliant)
- Lockable Equipment Cabinet



MODELS & SPECIFICATIONS

	FPT500	FPT1000	FPT2000
BRIM FILL	526 USG / 1,993 L	1,074 USG / 4,064 L	2,139 USG / 8,096 L
95% SAFE FILL	500 USG / 1,893 L	1,020 USG / 3,861 L	1,941 USG / 7,346 L
WEIGHT* (EMPTY)	4,320 lbs / 1,960 kg	6,743 lbs / 3,059 kg	9,378 lbs / 4,254 kg
WEIGHT* (FULL)	7,867 lbs / 3,568 kg	13,979 lbs / 6,341 kg	23,789 lbs / 10,791 kg
DIMENSIONS* (L x W x H)	78 x 87 x 50 in 1,981 x 2,210 x 1,270 mm	131 x 87 x 50 in 3,327 x 2,210 x 1,270 mm	116 x 87 x 101 in 2,946 x 2,210 x 2,565 mm

**Weights are approximate. Individual tanks may vary from these values. Weights & Dimensions include Tank + Lockable Equipment Cabinet.*

TANK APPROVALS & STANDARDS



UL2085
CERTIFIED



UL Listing does not cover use while in transport or optional accessories.