

LUBE CONTAINER



The Lube Container from Western Global enables the customer by having the waste oil storage and filter swaps on site which greatly reduce the amount of time allotted to the maintenance of generators. The Lube Container eliminates the need for expensive lubricant trucks.

FEATURES



20 FT. ISO CONTAINER

Equipment and fluids are secure and spills are contained. Features lockable doors.

PUMP BAY

Easily accessible ceiling-mounted hose reel with 50ft of 1/2" air hose rated at 300 PSI.

RETRACTABLE EXTENSION CORD

Quick and easy ceiling-mounted reel with a 40ft extension cord and grounded triple tap adapter.

USED OIL STORAGE

Safely store up to 1000 gallons of used oil within the double-walled, 110% contained waste oil spec FuelCube.

ONBOARD POWER

Ready to use two-stage air compressor and 4000kW generator, powered by Honda engine.



FRESH OIL DISPENSING

Effortlessly pump fresh oil into equipment during routine maintenance with 50ft. hose and digital metering gun.

USED OIL REMOVAL

Suction used oil into the on-board storage, or flip the evacuation valve to dispense used oil for disposal.

STINGER TUBE

Quick connect the pump to remove used oil.

FRESH OIL TANK

Ideal for routine equipment maintenance, store up to 500 gallons of fresh oil.

FILTER DRAINING CABINET

Quickly drain used filters to simplify equipment maintenance.



IDEAL USES AND APPLICATIONS

ON-SITE YARD

Easily maintenance machinery from an on-site rental yard when needed and cut back on lubricant truck expenses.

EQUIPMENT MAINTENANCE

The Lube Container allows a single person to perform quick and easy maintenance on a fleet or paralleled generators

SPECIFICATIONS

Standard accessories: Filter draining cabinet, 4000W Generator / Air Compressor w/ Honda engine, Interior LED lighting, 40ft triple tap Electric cord reel, 1" x 50ft fresh oil dispensing reel w/ digital meter, 1" x 50ft used oil suction / dispensing reel (can be used for both via evacuation valve), 50ft air hose reel w/ quick connect for air tools, Stinger tube for oil pickup from drain pans / filter drain cabinet, RAASM 7:1 Pneumatic Pump for Fresh Oil dispensing, and RAASM dual diaphragm 1:1 Pump for used oil transfers.

Container length:	20 feet	Fresh Oil Tank Capacity: (brim fill)	500 US Gallons
Container width:	8 feet	Fresh Oil Tank Capacity: (safe fill)	490 US Gallons
Container height:	8 feet 6 inches	Weight empty:	14,820 lbs
Used Oil Tank Capacity (brim fill):	1,016 US Gallons	Weight full:	18,020 lbs
Used Oil Tank Capacity (safe fill):	965 US Gallons	Approvals:	UL142, CAN/ULC-S601



LBCT-SLSH-NA-1223-A

T: +1 866 814 2470 W: western-global.com