



# Test Report OSHA Verification

Pure Safety Group, Inc.  
607 East Sam Houston Pkwy S  
Suite 800, Pasadena, TX 77053

**Test Report Number:** 2026021615044  
**Job Number:** Test 1802  
**Product SKU#:** 15044  
**Product Type:** Horizontal Lifeline  
**Product Description:** HLL Attachment System for Applications under 60'  
**Testing Standard:** OSHA 1910.140(c)(11)(ii), OSHA 1926.502(d)(8)  
**Dates of Manufacture:** 9/01/2025  
**Date(s) of Testing:** 2/16/2026

## VERIFICATION TESTING

Test Description	Test Date	Clause/Section	Result
Dynamic Performance (One User)	2/16/2026	OSHA 1910.140(c)(11)(ii) OSHA 1926.502(d)(8)	Meets or Exceeds
Dynamic Performance (Two Users)	2/16/2026	OSHA 1910.140(c)(11)(ii) OSHA 1926.502(d)(8)	Meets or Exceeds

This test report covers these additional products:

Please contact [quality@guardianfall.com](mailto:quality@guardianfall.com) for signed report.

Test Equipment		
Equipment	Model	Serial
Load Cell	1210AF-10K-B	444522A
Tape Measure	4932471629	F9Q9R
Test Weight	310 lb	GFP001, 7HME, GFP002

### Requirements

<b>1910.140(c)(11)(ii)</b>	Is part of a complete personal fall arrest system that maintains a safety factor of at least two.	Meets or exceeds
<b>1926.502(d)(8)</b>	Horizontal lifelines shall be designed, installed, and used, under the supervision of a qualified person, as part of a complete personal fall arrest system, which maintains a safety factor of at least two.	Meets or exceeds

#### Dynamic Performance (One User)

*requirements per OSHA 1910.140(c)(11)(i), 1926.502(d)(8)*

Samples	Sample #
	<b>01</b>
Post Drop Line Sag (in.)	16
End Load Force ( $\leq 2500$ lb)	2002.31
Specimen Maintained Load?	Yes
<b>Result/Assessment</b>	Pass

#### Dynamic Performance (Two Users)

*requirements per OSHA 1910.140(c)(11)(i), 1926.502(d)(8)*

Samples	Sample #
	<b>02</b>
Post Drop Line Sag (in.)	14
End Load Force ( $\leq 2500$ lb)	2080.99
Specimen Maintained Load?	Yes
<b>Result/Assessment</b>	Pass

### Notes

All measurements expressed at approximately 95% confidence level using coverage factor K=2