



**GUARDIAN**<sup>®</sup>

## CR3-EDGE WEB

Personal Self-Retracting  
Lifeline

The Guardian CR3-Edge Web is the perfect personal SRL solution for leading edge applications - offering both superior performance and weight. The CR3-Edge Web utilizes a unique and proprietary blend of Aramid and UHMWPE to create an extremely durable, yet lightweight webbing, that's been tested to the standard on the most problematic substrate in the industry. The CR3-Edge Web SRL-P has all the capability and safety of a cable lifeline at a fraction of the weight, mitigating working fatigue and allowing you to be more efficient in the most demanding conditions.

Class

**2**

Anchor above  
or below dorsal  
D-ring

**HEIGHT SAFETY.  
SIMPLIFIED.**

[guardianfall.com](http://guardianfall.com)



# CR3-EDGE WEB

Personal Self-Retracting Lifeline



**Class**  
**2**  
Anchor above  
or below dorsal  
D-ring



4200257

4200250



Suitable for  
**LEADING EDGE**

Se puede utilizar en aplicaciones borde expuesto

## Key features & benefits

### Leading Edge Web Lifeline

Proprietary blend and weave that significantly reduces overall SRL Weight while maintaining Class 2 compliance

### Dual-lock SRL connector

Provides quick and easy installation onto most full body harnesses

### Lightweight energy absorber

Acts as cushion between the housing and worker to increase comfort

### Lightweight thermoplastic housing

Durable construction for long-lasting use in the toughest conditions

### Multiple hook options available

Choose steel or aluminum snap or rebar hooks, depending on job requirements and anchorage type

## Specifications

**User weight range (including tools and equipment)** | ANSI 130-310 lb | OSHA 100-310 lb (LE) | OSHA 100-420 lb (NON-LE)

**Max. Arresting Force** | 1,350 lb

**Ave. Arresting Force** | 1,150 lb

**Min. Setback Distance from edge** | 0" (LE)

**Max. Arresting Distance** | 10' 6" (LE)

(NON-LE) ANSI 130-310 lb, 3' | OSHA 100-310 lb, 3' | OSHA 311-420 lb, 3'6"

**Min. Required Fall Clearance** | At or above D-Ring (NON-LE) 100-420 lb, 7' | Below D-Ring (LE) 100-310, 18'

**Max. Allowable Free Fall** | 5'

**Materials** | Polyester, nylon, stainless steel

**Lifeline Material** | Aramid and UHMWPE blend webbing

**Length** | 8'

## Hook Options



Steel snap hook



Steel rebar hook



Aluminum snap hook



Aluminum rebar hook



Steel tie-back hook

## Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI Z359.7**

This product is compliant with the following safety regulations and consensus standard:

**OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021**

For more information:

**+1 (800) 466 6385**

[customer.service@guardianfall.com](mailto:customer.service@guardianfall.com)



Tested in the  
**United States**

# CR3-EDGE WEB

Personal Self-Retracting Lifeline



Class

2

Anchor above  
or below dorsal  
D-ring

Part number(s)	Description	Hook type	Length	OSHA User Weight Range	ANSI User Weight Range
4200250	CR3-Edge Web Personal SRL, Single, Class 2	Steel snap hook	8 ft	100-420 lb	130-310 lb
4200251	CR3-Edge Web Personal SRL, Single, Class 2	Aluminum snap hook	8 ft	100-420 lb	130-310 lb
4200252	CR3-Edge Web Personal SRL, Single, Class 2	Steel rebar hook	8 ft	100-420 lb	130-310 lb
4200253	CR3-Edge Web Personal SRL, Single, Class 2	Aluminum rebar hook	8 ft	100-420 lb	130-310 lb
4200254	CR3-Edge Web Personal SRL, Single, Class 2	Tie-back hook	8 ft	100-420 lb	130-310 lb
4200255	CR3-Edge Web Personal SRL, Dual, Class 2	Steel snap hooks	8 ft	100-420 lb	130-310 lb
4200256	CR3-Edge Web Personal SRL, Dual, Class 2	Aluminum snap hooks	8 ft	100-420 lb	130-310 lb
4200257	CR3-Edge Web Personal SRL, Dual, Class 2	Steel rebar hooks	8 ft	100-420 lb	130-310 lb
4200258	CR3-Edge Web Personal SRL, Dual, Class 2	Aluminum rebar hooks	8 ft	100-420 lb	130-310 lb
4200259	CR3-Edge Web Personal SRL, Dual, Class 2	Tie-back hooks	8 ft	100-420 lb	130-310 lb

## Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI Z359.7**

This product is compliant with the following safety regulations and consensus standard:  
**OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021**

For more information:

**+1 (800) 466 6385**

**customer.service@guardianfall.com**



Tested in the  
**United States**