



**GUARDIAN**[®]

CR5

Self-Retracting Lifeline

The CR5 6 ft Class SRL is part of Guardian's strongest lineup of SRLs in the industry. This lightweight personal SRL can be used in either fall arrest or travel restraint applications.



**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



CR5

Self-Retracting Lifeline



1400198CSA

Class
SRL
Anchor at or above dorsal D-ring

1400203CSA



Key features & benefits

Swivel top connection point

Swivels 360-degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling

Impact modified thermoplastic housing

Super lightweight and durable for long-lasting use in the toughest applications

Digitally enabled labels

QR code for quick and easy access to up-to-date safety and product information

Guardian shock pack cover

Helps increase product longevity and protect safety labeling

Reinforced webbing guide

Adds strength and reduces webbing friction

Multiple hook options available

Choose steel or aluminum snap depending on job requirements and anchorage type

Specifications

User Weight Range (including tools and equipment) | 100-310 lb (45 -140 kg)

Class | SRL

Length | 6 ft (1,83 m)

Maximum Arrest Distance | 3 ft (0,9 m)

Maximum Arrest Force | 1,350 lb (6 kN)

Average Deployment Force | 1,150 lb (5,1 kN)

Average Arrest Force | 1,150 lb (5,1 kN)

Minimum Required Fall Clearance | 6 ft 6 in (1,9 m)

Service Temperature | -40° to 130° F (-40° to 54,4° C)

Materials | polyester, impact modified thermoplastic resin, HMPE webbing, steel, aluminum

Hook Options



Steel snap hook



Aluminum snap hook

Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory and certified under CSA's ISO/IEC 17065 accreditation.

This product is compliant with the following safety regulations:
CSA Z259.2.2-17

For more information:
+1 (800) 267 6855
info@guardianfall.com

Designed and Tested in the
United States.

CR5

Self-Retracting Lifeline



Part number	Description	Hook type	Length	User Weight Range
1400198CSA	CR5 SRL, Web, Class SRL	Steel snap hook	6 ft (1,8 m)	100-310 lb (45-140 kg)
1400201CSA	CR5 SRL, Web, Class SRL	Aluminum snap hook	6 ft (1,8 m)	100-310 lb (45-140 kg)
1400203CSA	CR5 Dual SRL, Web, Class SRL	Steel snap hooks	6 ft (1,8 m)	100-310 lb (45-140 kg)
1400206CSA	CR5 Dual SRL, Web, Class SRL	Aluminum snap hooks	6 ft (1,8 m)	100-310 lb (45-140 kg)

Declaration of conformity

This product has been tested in an **ISO 17025** accredited laboratory and certified under **CSA's ISO/IEC 17065** accreditation.

This product is compliant with the following safety regulations:
CSA Z259.2.2-17

For more information:
+1 (800) 267 6855
info@guardianfall.com

Designed and
Tested in the
United States.