



360-RING ANCHOR

Anchorage Connector

The Guardian 360-Ring Anchor is a reusable temporary fall protection anchor that provides a full 360° working radius for enhanced mobility and productivity. Designed for use on wood roof structures, it installs in seconds using timber screw fasteners, delivering a fast, secure, and reliable anchorage solution.



**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



360-RING ANCHOR

Anchorage Connector



Key features & benefits

Versatile wood anchor
Installs easily with timber screws for fast, secure placement in residential or commercial applications

Reusable design
Allows convenient repositioning as work progresses, improving efficiency and safety on the job

360-Ring pivoting connection point
Large 3" connection ring enables full-range movement and balanced load distribution for increased worker mobility

Heavy-duty zinc-plated steel
Corrosion-resistant construction delivers long-lasting durability and strength

Compatible with horizontal lifelines
Can be used to create safe, continuous tie-off fall protection solutions

Specifications

- User Weight Range** | ANSI: 130-310 lb (59-141 kg)
OSHA 100-420 lb (45-191 kg)
- Minimum Breaking Strength** | 5,000 lb (22,2 kN)
- Substrates** | Wood
- Anchorage Connector Type (ANSI Z359.18)** | Type A
- Materials** | Zinc-plated steel

Part Numbers	Description	User weight range
6400000	360-Ring Anchor, no fasteners	100-420 lb (45-191 kg)
6400001	360-Ring Anchor, fasteners included	100-420 lb (45-191 kg)
6500000	360-Ring Anchor Fasteners, 0.25" x 4" timber screws	-

US Sales:
+1 (800) 466 6385
customer.service@guardianfall.com



Designed and tested in the
United States

This product is compliant with the following safety regulations and consensus standard:
ANSI Z359.18-2017 | OSHA 1910.140 & 1926.502