

*Images rendered

GUARDIAN®

ANSI Class
1
Anchor at or above dorsal D-ring

CSA Class
SRL
Anchor at or above dorsal D-ring

HERO™

Self-Retracting Lifeline

The Guardian Hero™ Class 1 Web and Cable Self-Retracting Lifeline is engineered to keep professionals moving confidently in overhead work-at-height applications. Built with a high-strength, lightweight web lifeline or durable cable lifeline, precision-engineered components, and a performance-driven design, Hero™ delivers dependable fall protection without sacrificing mobility. Available in single and dual leg models, multiple lifeline lengths, and hook configurations, Hero™ is designed to keep professionals protected across a wide range of work-at-height tasks and applications.

As the industry's first dual-labelled ANSI Z359.14-2021 qualified and CSA Z259.2.2-2017 certified Self-Retracting Lifeline platform, Hero™ delivers dependable line-lock performance to minimize nuisance lock ups and support smooth movement throughout the workday. Double-recessed label design protects important safety information from job site wear, helping simplify inspections throughout the life of the SRL. An integrated gray housing provides instant visual identification for Class 1 overhead applications, making it easy to identify the appropriate SRL for the job.

Every Hero™ Class 1 SRL is validated through extensive laboratory testing and demanding field evaluations to ensure dependable performance where it matters most. Built to Protect. Engineered to Perform. Hero™ helps workers stay productive, protected, and prepared for whatever the job demands.

nsc Safety Congress & Expo
BEST IN SHOW
Safety+Health

HEIGHT SAFETY. SIMPLIFIED.

guardianfall.com

HERO™
Self-Retracting Lifeline

nsc Safety Congress & Expo BEST IN SHOW Safety+Health

ANSI Class	CSA Class
1	SRL
Anchor at or above dorsal D-ring	Anchor at or above dorsal D-ring



Key features & benefits

One SRL. Two Standards
As the industry's first dual-labelled ANSI Z359.14-2021 qualified and CSA Z259.2.2-2017 certified Self-Retracting Lifeline platform provides one trusted solution engineered for job sites across North America.

Enhanced Mobility. Reliable Safety
Dependable line-lock performance minimizes nuisance lockups while allowing smooth movement throughout the workday, helping workers stay productive without compromising safety.

Inspection Ready
Double-recessed label design helps protect important safety information from job site wear, making inspections faster, easier, and more reliable throughout the life of the SRL.

Instant Visual Identification
Integrated gray housing provides immediate visual identification for overhead applications.

Proven Performance
Every Hero™ SRL is validated through extensive laboratory testing and demanding field evaluations to ensure dependable performance where it matters most.

Specifications

User Weight Range*
OSHA Non-LE | 100 - 310 lb (45 - 140 kg)
ANSI Non-LE | 130 - 310 lb (59 - 140 kg)
CSA | 100 - 310 lb (45 - 140 kg)

**Including tools and equipment*

Scan for more product specifications.

Declaration of conformity
These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI/ASSP Z359.7.**

This product is compliant with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021 | CSA Z259.2.2-2017

Canada Sales:
+1 (800) 267 6855
info@guardianfall.com

US Sales:
+1 (800) 466 6385
customer.service@guardianfall.com

Designed and tested in the **United States**

HERO™
Self-Retracting Lifeline

GUARDIAN

nsc Safety Congress & Expo BEST IN SHOW Safety+Health

Part number	Description	Hook Type	Length	User Weight Range
Now Available				
4200125	Hero™ SRL, Class 1, Single Web	Steel Rebar	6 ft (1,82 m)	See specifications
4200131	Hero™ SRL, Class 1, Dual Web	Steel Snap	6 ft (1,82 m)	See specifications
4200163	Hero™ SRL, Class 1, Single Web	Steel Snap	11 ft (3,35 m)	See specifications
Available December				
4200126	Hero™ SRL, Class 1, Single Web	Steel Snap	6 ft (1,82 m)	See specifications
4200130	Hero™ SRL, Class 1, Dual Web	Steel Rebar	6 ft (1,82 m)	See specifications
4200128	Hero™ SRL, Class 1, Single Web	Aluminum Snap	6 ft (1,82 m)	See specifications
4200133	Hero™ SRL, Class 1, Dual Web	Aluminum Snap	6 ft (1,82 m)	See specifications
4200129	Hero™ SRL, Class 1, Single Web	Aluminum Rebar	6 ft (1,82 m)	See specifications
4200134	Hero™ SRL, Class 1, Dual Web	Aluminum Rebar	6 ft (1,82 m)	See specifications
4200132	Hero™ SRL, Class 1, Dual Web	Steel Tie-Back*	6 ft (1,82 m)	See specifications
4200127	Hero™ SRL, Class 1, Single Web	Steel Tie-Back*	6 ft (1,82 m)	See specifications
4200162	Hero™ SRL, Class 1, Single Web	Steel Rebar	11 ft (3,35 m)	See specifications
4200164	Hero™ SRL, Class 1, Single Web	Aluminum Rebar	11 ft (3,35 m)	See specifications
Coming Soon				
4200166	Hero™ SRL, Class 1, Single Cable	Steel Snap	20 ft (6,09 m)	See specifications
4200165	Hero™ SRL, Class 1, Single Cable	Steel Snap	30 ft (9,14 m)	See specifications
4200169	Hero™ SRL, Class 1, Single Cable	Steel Snap	50 ft (15,24m)	See specifications

** Not CSA qualified*

Hook Types


Steel snap hook


Steel rebar hook


Aluminum snap hook


Aluminum rebar hook


Steel tie-back hook

Canada Sales:
+1 (800) 267 6855
info@guardianfall.com

US Sales:
+1 (800) 466 6385
customer.service@guardianfall.com

Designed and tested in the **United States**

Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI/ASSP Z359.7.**

This product is compliant with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021 | CSA Z259.2.2-2017