



Class

**2**

Anchor above  
or below dorsal  
D-ring

# HERO™

## Self-Retracting Lifeline

The Guardian Hero™ Class 2 Web or Cable Self-Retracting Lifeline is engineered for professionals working in demanding leading-edge environments where versatility and dependable performance are essential. Built with a high-strength, lightweight web lifeline or durable cable lifeline, precision-engineered components, and a performance-driven design, Hero™ delivers dependable fall protection without sacrificing mobility. Available in single and dual leg models, multiple lifeline lengths, and hook configurations, Hero™ is designed to keep professionals protected across a wide range of work-at-height tasks and applications.

As the industry's first dual-labelled ANSI Z359.14-2021 qualified and CSA Z259.2.2-2017 certified Self-Retracting Lifeline platform, Hero™ delivers dependable line-lock performance to minimize nuisance lock ups and support smooth movement throughout the workday. Double-recessed label design protects important safety information from job site wear, helping simplify inspections throughout the life of the SRL. An integrated gold housing provides instant visual identification for Class 2 leading-edge applications, helping workers quickly identify the appropriate SRL for the task.

Hero™ Class 2 Self-Retracting Lifelines are compatible with overhead-to-foot-level tie-offs and are suitable for leading edge applications including steel and concrete. Engineered to Perform. Hero™ helps workers stay productive, protected, and prepared for whatever the job demands.

## HEIGHT SAFETY. SIMPLIFIED.

[guardianfall.com](https://guardianfall.com)



# HERO™

## Self-Retracting Lifeline

Class

2

Anchor above  
or below dorsal  
D-ring

ANSI and CSA labeling

Swivel top connection point

Thermoplastic housing

Double-recessed label

4200151

Integrated energy absorber

Various hook types available

4200148

### Key features & benefits

#### One SRL. Two Standards

As the industry's first dual-labelled ANSI Z359.14-2021 qualified and CSA Z259.2.2-2017 certified Self-Retracting Lifeline platform provides one trusted solution engineered for job sites across North America.

#### Enhanced Mobility. Reliable Safety

Dependable line-lock performance minimizes nuisance lockups while allowing smooth movement throughout the workday, helping workers stay productive without compromising safety.

#### Inspection Ready

Double-recessed label design helps protect important safety information from job site wear, making inspections faster, easier, and more reliable throughout the life of the SRL.

#### Instant Visual Identification

Integrated gold housing provides immediate visual identification for leading-edge applications.

#### Proven Performance

Designed and tested on concrete and steel substrates to perform in demanding leading-edge applications.

### Specifications

#### User Weight Range\*

OSHA LE | 100 - 310 lb (45 - 140 kg)

OSHA Non-LE | 100 - 420 lb (45 - 190 kg)

ANSI | 130 - 310 lb (59 - 140 kg)

CSA | 100 - 310 lb (45 - 140 kg)



Scan for  
more product  
specifications.

\*Including tools and equipment

#### Canada Sales:

+1 (800) 267 6855

info@guardianfall.com

#### US Sales:

+1 (800) 466 6385

customer.service@guardianfall.com




Designed and  
tested in the  
United States

### Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI/ASSP Z359.7.

This product is compliant with the following safety regulations and consensus standard:  
OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021 Qualified | CSA Z259.2.2-2017 Certified



| Part number              | Description                      | Hook Type      | Length         | User Weight Range  |
|--------------------------|----------------------------------|----------------|----------------|--------------------|
| <b>Now Available</b>     |                                  |                |                |                    |
| 4200145                  | Hero™ SRL, Class 2, Dual Web,    | Steel Snap     | 6 ft (1,82 m)  | See specifications |
| 4200135                  | Hero™ SRL, Class 2, Single Web   | Steel Rebar    | 8 ft (2,43 m)  | See specifications |
| 4200154                  | Hero™ SRL, Class 2, Single Cable | Steel Rebar    | 8 ft (2,43 m)  | See specifications |
| 4200157                  | Hero™ SRL, Class 2, Dual Cable   | Steel Rebar    | 8 ft (2,43 m)  | See specifications |
| 4200151                  | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 10 ft (3,04 m) | See specifications |
| <b>Available October</b> |                                  |                |                |                    |
| 4200137                  | Hero™ SRL, Class 2, Single Web   | Steel Snap     | 6 ft (1,82 m)  | See specifications |
| 4200137                  | Hero™ SRL, Class 2, Single Web   | Steel Snap     | 6 ft (1,82 m)  | See specifications |
| 4200136                  | Hero™ SRL, Class 2, Single Web   | Steel Rebar    | 6 ft (1,82 m)  | See specifications |
| 4200144                  | Hero™ SRL, Class 2, Dual Web     | Steel Rebar    | 6 ft (1,82 m)  | See specifications |
| 4200138                  | Hero™ SRL, Class 2, Single Web   | Aluminum Rebar | 6 ft (1,82 m)  | See specifications |
| 4200146                  | Hero™ SRL, Class 2, Dual Web     | Aluminum Rebar | 6 ft (1,82 m)  | See specifications |
| 4200139                  | Hero™ SRL, Class 2, Single Web   | Steel Snap     | 8 ft (2,43 m)  | See specifications |
| 4200147                  | Hero™ SRL, Class 2, Dual Web     | Steel Snap     | 8 ft (2,43 m)  | See specifications |
| 4200152                  | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 8 ft (2,43 m)  | See specifications |
| 4200158                  | Hero™ SRL, Class 2, Dual Cable   | Steel Snap     | 8 ft (2,43 m)  | See specifications |
| 4200143                  | Hero™ SRL, Class 2, Dual Web     | Steel Rebar    | 8 ft (2,43 m)  | See specifications |
| 4200143                  | Hero™ SRL, Class 2, Dual Web     | Steel Rebar    | 8 ft (2,43 m)  | See specifications |
| 4200153                  | Hero™ SRL, Class 2, Single Cable | Aluminum Snap  | 8 ft (2,43 m)  | See specifications |
| 4200148                  | Hero™ SRL, Class 2, Dual Web     | Aluminum Snap  | 8 ft (2,43 m)  | See specifications |
| 4200140                  | Hero™ SRL, Class 2, Single Web   | Aluminum Snap  | 8 ft (2,43 m)  | See specifications |

Continues on next page.

## Hook Types



Steel snap hook



Steel rebar hook



Aluminum snap hook



Aluminum rebar hook



Steel tie-back hook

## Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI/ASSP Z359.7**.

This product is compliant with the following safety regulations and consensus standard:  
**OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021 Qualified | CSA Z259.2.2-2017 Certified**

## Canada Sales:


**+1 (800) 267 6855**  
**info@guardianfall.com**

## US Sales:

**+1 (800) 466 6385**  
**customer.service@guardianfall.com**



Designed and  
tested in the  
**United States**



| Part number        | Description                      | Hook Type      | Length           | User Weight Range  |
|--------------------|----------------------------------|----------------|------------------|--------------------|
| 4200159            | Hero™ SRL, Class 2, Dual Cable   | Aluminum Snap  | 8 ft (2,43 m)    | See specifications |
| 4200141            | Hero™ SRL, Class 2, Single Web   | Aluminum Rebar | 8 ft (2,43 m)    | See specifications |
| 4200155            | Hero™ SRL, Class 2, Single Cable | Aluminum Rebar | 8 ft (2,43 m)    | See specifications |
| 4200149            | Hero™ SRL, Class 2, Dual Web     | Aluminum Rebar | 8 ft (2,43 m)    | See specifications |
| 4200160            | Hero™ SRL, Class 2, Dual Cable   | Aluminum Rebar | 8 ft (2,43 m)    | See specifications |
| 4200142            | Hero™ SRL, Class 2, Single Web   | Steel Tie-Back | 8 ft (2,43 m)    | See specifications |
| 4200150            | Hero™ SRL, Class 2, Dual, Web    | Steel Tie-Back | 8 ft (2,43 m)    | See specifications |
| 4200156            | Hero™ SRL, Class 2, Single Cable | Steel Tie-Back | 8 ft (2,43 m)    | See specifications |
| 4200161            | Hero™ SRL, Class 2, Dual Cable   | Steel Tie-Back | 8 ft (2,43 m)    | See specifications |
| <b>Coming Soon</b> |                                  |                |                  |                    |
| 4200168            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 20 ft (6,09 m)   | See specifications |
| 4200167            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 30 ft (9,14 m)   | See specifications |
| 4200171            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 50 ft (15,24 m)  | See specifications |
| 4200170            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 65 ft (19,81 m)  | See specifications |
| 4200181            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 100 ft (30,48 m) | See specifications |
| 4200180            | Hero™ SRL, Class 2, Single Cable | Steel Snap     | 130 ft (39,62 m) | See specifications |

## Hook Types



Steel snap hook



Steel rebar hook



Aluminum snap hook



Aluminum rebar hook



Steel tie-back hook

## Declaration of conformity

These products been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by **ANSI/ASSP Z359.7**.

This product is compliant with the following safety regulations and consensus standard:  
**OSHA 1910.140 & 1926.502 | ANSI Z359.14-2021 Qualified | CSA Z259.2.2-2017 Certified**

## Canada Sales:

**+1 (800) 267 6855**  
**info@guardianfall.com**

## US Sales:

**+1 (800) 466 6385**  
**customer.service@guardianfall.com**



Designed and  
tested in the  
**United States**