



ROOF CART

Mobile Fall Protection Unit

The Guardian Roof Cart offers unmatched portability at just 430 lb (195 kg), that's 45% lighter than comparable systems on the market. Lift it into position, clip into the anchor points, and get to work. As the job moves, the Roof Cart can relocate in minutes, protecting up to 3 workers in fall arrest or 2 workers in travel restraint. It ships fully assembled and job site ready on a standard pallet.



**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



ROOF CART

Mobile Fall Protection Unit



6600000



6600000



Key features & benefits

Versatile fall protection

Can be used to keep 3 workers in fall arrest, or 2 in travel restraint. One unit, two applications, full crew protection

45% lighter, 100% mobile

At just 430 lb (195 kg), the Roof Cart is dramatically lighter than comparable systems, making it easier to lift, move, and reposition on the fly

Rolls where the work goes

Premium flat-free tires, rated at 300 lb (136 kg) each with a total capacity of 1,200 lb (544 kg), allow for fast, effortless relocation as the job progresses

Lift. Clip. Go!

A quick, simple three-step setup gets your team anchored and working in minutes, no tools or complex install required

Ships job site ready

Arrives fully assembled on a standard pallet - no on-site build, no wasted time

Includes a locking toolbox

Specifications

User Weight Range | OSHA 100-310 lb (45-141 kg)

Applications | 3 workers in Fall Arrest or 2 workers in Travel Restraint.

Area Footprint | 40" x 48"

Substrates | TPO, EPDM, ISO, EPS, metal, wood, and built-up roofing

Material | Steel

Part Number	Description	User weight range
6600000	Roof Cart - Mobile Fall Protection Unit	100-310 lb (45-141 kg)

US Sales:

+1 (800) 466 6385

customer.service@guardianfall.com



Designed, tested and
manufactured in the
United States

This product is compliant with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502