TRAUMA STRAP

Part #: 10733

Instruction Manual



2	Introduction
2	Inspection
2	Maintenance
3	Attachment
4	Use

✕ **Do not throw instructions away.**

⚠ **Read and understand instructions before using this equipment.**

Introduction

PRIOR TO USE, READ AND UNDERSTAND ALL INSTRUCTIONS INCLUDED WITH EQUIPMENT AT TIME OF SHIPMENT.

Maximum worker capacity: 420 lb (191 kg).

Materials: nylon, polyester, and steel.

The Trauma Strap is not to be used as an anchor, lanyard, or any other form of fall protection, except in the manner detailed by these instructions.

Seek medical attention immediately if exposed to a fall/suspension.

The Trauma Strap is not intended to replace a rescue plan. The employer must always have a jobsite-specific rescue plan in place, and the means to implement that plan.

Misuse or alteration to this product may result in SERIOUS INJURY OR DEATH!

Inspection

Prior to each use, inspect Trauma Strap for any frays, cuts, broken fibers, burns, discoloration, knots, tears, abrasions, cracking, rust, and any other damage.

If any of these conditions exist, IMMEDIATELY remove Trauma Strap from service. Competent Person must inspect at least every 12 months.

Maintenance

Cleaning after use is important for maintaining the safety and longevity of the Trauma Strap. Remove all dirt, corrosives, and contaminants from Trauma Strap before and after each use. If Trauma Strap cannot be cleaned with plain water, use mild soap and water, then rinse and wipe dry. To fully dry, unravel the contents and hang them to dry. NEVER clean Trauma Strap with corrosive substances.

When not in use, store equipment where it will not be affected by heat, light, excessive moisture, chemicals, or other degrading elements.

Attachment

Install Trauma Strap immediately above where leg straps meet side/shoulder straps (as shown).

Paso 1

Pass Trauma Strap web loop behind harness strap and pull back around.



Step 2

Pull Trauma Strap pouch through web loop and choke down to harness strap. Pouch must be on outside of harness strap.



Step 3

Secure Trauma Strap snap buckle around harness strap.



Step 4

Repeat steps 1-3 on second side.



Step 5

Trauma Strap is now installed and ready to use.

GUARDIAN

Use:

1.) Unzip Trauma Strap pouches fitted on both sides of the harness.



2.) Connect the strap end to the ring end, and ensure strap buckle is fully locked and secured.



3.) Put your feet into the loop that you have made.



4.) Stand on the loop and examine pressure on thighs.



5.) Adjust strap as necessary to accommodate your height.



CORREA PARA TRAUMA

Parte #: 10733

Manual de instrucciones



5	Introducción
6	Inspeccion
6	Mantenimiento
6	Anexo
7	Use

Introducción

ANTER DE USARSE, LEA Y ENTIENDA TODAS LAS INSTRUCCIONES INCLUIDAS CON EL EQUIPO AL MOMENTO DEL EMBARQUE.

Capacidad máxima del trabajador:

420 lb (191 kg).

Materiales: nylon, polyester, y metal.

La correa para trauma no es para ser utilizado como anclaje, cuerda de seguridad, o cualquier otra forma de protección de caídas, excepto en la manera detallada en estas instrucciones. Busque atención médica inmediatamente si es expuesto a una caída/suspensión.

No es la intención de la correa para trauma el reemplazar un plan de rescate. El empleador debe de siempre tener un plan de rescate específico en su lugar de trabajo, y los medios para implementar el plan.

Mal uso o alteración de este producto puede resultar en SERIAS HERIDAS O MUERTE.

✕ **No tire las instrucciones.**

⚠ **Lea y comprenda las instrucciones antes de utilizar este equipo.**

Inspeccion

Antes de cada uso, inspeccione la correa para trauma de cualquier deshilado, corte, fibras rotas, quemaduras, descoloración, nudos, rasgaduras, abrasiones, grietas, corrosión, o cualquier otro daño. **Si cualquiera de estas condiciones existe, INMEDIATAMENTE retire la correa para trauma de servicio. Una Persona Competente debe de inspeccionar al menos cada 12 meses.**

Mantenimiento

Limpiar después de uso es importante para mantener la seguridad y longevidad de la correa para trauma. Retire toda la suciedad, corrosivos, y contaminantes de la correa para trauma antes y después de cada uso. Si la correa para trauma no puede ser limpiada con agua, utilice ligeramente jabón y agua, después enjuague y seque. Completamente seco desenrede el contenido y cuélguelos para que sequen. NUNCA limpie las correas para trauma con sustancias corrosivas. Cuando no esté en uso, almacene el equipo donde no sea afectado por el calor, luz, excesiva humedad, químicos, o cualesquiera otros elementos degradables.

Anexo

Instale la Correa para Trauma inmediatamente arriba de donde las correas de las piernas coinciden las correas laterales/hombros (como la imagen).

Paso 1

Pase el lazo de la Correa para Trauma atrás de la correa del arnés y jálelo alrededor.



Paso 2

Jale la bolsa de la correa para trauma a través del lazo y apriete hacia la correa del arnés. La bolsa debe de estar hacia afuera de la correa del arnés.



Paso 3

Asegure la hebilla de presión de la Correa para Trauma en la correa del arnés.



Paso 4

Repita los pasos 1-3 en el Segundo lado.



Paso 5

La Correa para Trauma está ahora instalada y lista para su uso.

GUARDIAN

Uso:

1.) Abra la cremallera de las bolsas de la Correa para Trauma en ambos lados del arnés.



2.) Conecte el final de la correa al final del aro, y asegure la hebilla de la correa está completamente conectada y asegurada.



3.) Coloque su pie dentro del lazo que ha hecho.



4.) Párese en el lazo y examine la presión en los muslos.



5.) Ajuste la correa tan necesaria como para acomodar su altura.



USA
607 East Sam Houston Parkway South
Suite 800
Pasadena, TX 77503
800 466 6385
customer.service@guardianfall.com

CANADA
580 Notre Dame Avenue, Unit 16
Sudbury, ON
P3C 5L2
800 466 6385
customer.service@guardianfall.com

WARRANTY: Guardian warrants to Buyer that all products are free from defects in material, workmanship, and design (if a Supplier-responsible design), however this warranty does not cover conditions resulting from normal wear and tear, neglect, abuse, accident or otherwise. Guardian's obligations under this warranty apply for the lifetime of the products and are limited to the replacement of product only. This warranty is not transferable to any other Guardian service and does not apply to product that is resold after having been put into service. No other person, firm, entity, or the like is authorized to assume or assign for Guardian any other liability in connection with the sale or use of Guardian's products. Furthermore, this warranty is void if any product is changed or altered in any way, or if the product is used in a manner other than for which it is intended. There are no implied warranties of merchantability or fitness for a particular purpose, which are specifically disclaimed.

Guardian® and its logo are registered trademarks of Pure Safety Group Inc. dba Guardian Fall in the US and other countries.