

Belt Anchor Adapters

Installation and Usage Instructions

Please read instructions carefully and fully before installation and/or usage.



IMPORTANT NOTES

- Inspect prior to each use and discard if rips, tears, excessive wear, or cracks are noted.
- Never exceed 6 lbs/carabiner
- Prior to use verify carabiners function and lock properly
- Where applicable read caution on the belt where the belt adapters will be installed

PART NO.	MAX. WEIGHT
BLTAD2	**6 lbs.
EZBLTAD2	**6 lbs.

**See note in instruction steps

WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS NOTED, PRODUCT REPLACEMENT IS REQUIRED.



1 Keeping the carabiner so that the screw collar is away from your body slide the tip of the desired belt through the opening of the belt adaptor. Continue sliding into the desired location which provides the most comfort and convenience.



3 Open the carabiner gate by unscrewing the screw collar counterclockwise and insert the tether attachment point (D-Ring, Key Ring, etc.) of the tool onto the carabiner. Once in place be sure to screw the collar clockwise until tight into place preventing the carabiner from inadvertently opening.



****NOTE:** Do not attach tool tethers directly to the carabiners, for stowing tools only.



2 Once in place choose the desired tether ready tools to connect to the carabiners.



4 When needing to use a tool start by unscrewing the screw collar in a counterclockwise direction and then open the gate allowing the tool to be removed from the carabiner.

INSTALLATION



Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103
www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113

THE DROP STOPS HERE