

DEKTITE®


PIPE FLASHING

The original flexible pipe flashing system with a 20 year warranty.



PRODUCT FEATURES

- Made of long life, flexible, weatherproof gray EPDM rubber.
- Flexible, corrosion resistant aluminum base conforms to any panel configuration.
- EPDM will not crack or break.
- Pipe diameter markings are clearly indicated for accurate fitting.
- Designed for 1/4" to 13" diameter pipes.
- One piece construction is easy to install.
- Pleated cone adjusts to any roof pitch and allows for complete flexibility.
- EPDM has a continuous service temperature range of -65°F to +250°F (grey in color).
- Proven resistance to ozone and ultra-violet light.



SELECTOR GUIDE

PART NO.	DESCRIPTION	PIPE OUTSIDE DIAMETER (IN.)	DEKTITE BASE DIAMETER (IN.)	DEKTITE HEIGHT (IN.)	BOX QTY	APPLICATIONS
4003910	1	1/4 - 2	4-3/4	3	10	Plumbing, Heating, Air Conditioning, Electrical and Exhaust Vents.
4004910	2	1-3/4 - 3-1/4	6-1/4	4	10	
4009910	3	1/4 - 5	7-3/4	4	10	
4011910	4	3 - 6	9-1/4	5	10	
4016910	5	4 - 7	10-3/4	5	5	
4025910	8	7 - 13	16-1/2	6	5	

Note: When used on roofs where pitch is steeper than 20 degrees, or when used on deep ribbed profile roof panel (1-1/2" deep corrugation or more), consider using next larger size Dektite that will accommodate the same pipe diameter.



PERFORMANCE DATA

ASTM METHOD	TEST DESCRIPTION	SPECIFICATION	TEST RESULTS	
D412	Tensile Strength (min. psi rating)	1450 psi min.	1537 psi	
D412	Ultimate Elongation (%)	350 min.	535	
D1171	Resistance to Ozone— min. rating	100 (no cracks)	Passed	
D673	Heat Aging – 70 hours at 212°F	– Change in Hardness (points)	± 15 max.	+8
		– Change in Tensile Strength (%)	± 30 max.	-4.7
		– Change in Elongation (%)	± 50 max.	-26
D2137	Low Temperature Brittleness— 3 mins. at -40°F	Non-brittle	Passed	
D624	Tear Resistance Die C (min.) per inch of width min.	125 lbs. per inch of width	130 lbs.	
U.L. 94	Flame Resistance	U.L. 94 H.B.	Passed	

INSTALLATION GUIDELINES

- 1 Cut Dektite at appropriate pipe diameter marking.
- 2 Slide Dektite flashing down over pipe.
- 3 Apply sealant on underside of flexible aluminum base.
- 4 Press Dektite base into contours of panel configuration.
- 5 Fasten Dektite to surface with Buildex Scots® self-drilling fasteners. Apply extra sealant around base if desired.

RECOMMENDED FASTENER	PART NO.	DESCRIPTION	BOX QTY
	1175153	1/4-14 x 1-1/8" Scots Tek's 1	2,500



Notes:

- Dektite can be installed over or between the ribs of standard panels.
- DO NOT install over SSR or architectural panel seams.
- Generally no sealant is required where the Dektite collar provides a compression fit around the pipe. However, some metal pipes and flues include a seam which may require a local application of sealant at the point where the Dektite collar crosses the seam.