

DS7c Multipin - 30 A

Ratings

- **Voltage**
50 VAC or 600 VAC Max/130 VDC*
* For DC order 600V model.
- **Amperage Rating**
30 A Current Interrupting (AC Only)
- **Temperature Range**
Min -40°F/Max 140°F
See pg 254 for temperatures outside of this range.
- **Environmental Ratings**
IP66/IP67/IP69/IP69K
- **Wiring Capacity**
Based on THHN wire sizes.
Min 14 AWG Max 8 AWG
Aux Contacts - 8 AWG
- **Certifications**
NOM

See pg 55-56 for DS7c dimensions.

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American Configurations

VOLTAGE	POLARITY	PART #		PART #	
		POLY	METAL	POLY	METAL
50 V	4P	33-34540	37-34540	33-38540	37-38540
50 V	5P	33-34550	37-34550	33-38550	37-38550
50 V	6P	33-34560	37-34560	33-38560	37-38560
50 V	7P	33-34570	37-34570	33-38570	37-38570
600 V	3P+G	33-34531	37-34531	33-38531	37-38531
600 V	4P+G	33-34541	37-34541	33-38541	37-38541
600 V	5P+G	33-34551	37-34551	33-38551	37-38551
600 V	6P+G	33-34561	37-34561	33-38561	37-38561

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



Mushroom Pawl



Padlock Pawl



Self-Ejecting Devices

Requires straight insertion receptacle or inlet and self-ejecting plug or connector.

RECEPTACLE OPTIONS

SUFFIX

INLET OPTIONS

SUFFIX

With 2 Auxiliary/Pilot Contacts	Recept # -172	With 2 Auxiliary/Pilot Contacts	Inlet # -172
With 3 Auxiliary/Pilot Contacts	Recept # -173	With 3 Auxiliary/Pilot Contacts	Inlet # -173
Straight Insertion	Recept # -352²	Self-Ejecting Plug Release**	Inlet # -338
Self-Ejecting Connector Release**	Recept # -354²	Without Lockout Hole	Inlet # -A155
Mushroom Pawl	Recept # -375	Notes: ** For self-ejecting connectors and plugs, a 443 suffix must be added to the handle part number. See pages 233-234 for more information. ² This option includes the Self-Returning Lid.	
Padlock Pawl	Recept # -843		
Screw-Type Locking Pawl	Recept # -845		
Metal Pawl (on poly receptacle)	Recept # -824		
Self-Returning Lid (Manual Close)	Recept # -NC		

Order Example: 50 V DS7c + mushroom pawl

DS7c Poly receptacle 4P = 33-34540-375

! See pages 231-240 for detailed information on these options



INSTALLATION ACCESSORIES – SIZE 4

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

HANDLES

HANDLE WITH NPT		PART # POLY	PART # METAL
	1/2"	514P0N05	594P0N05
	3/4"	514P0N07	594P0N07
	1"	514P0N10	594P0N10
	1 1/4"	514P0N12	594P0N12
	1 1/2"	514P0N15	594P0N15

For available cord grips, see pg 159.

POLY HANDLE WITH CORD GRIP		CABLE RANGE	PART #
		.680-.980"	714P0DP4
		.980-1.260"	714P0EP4
		1.260-1.560"	714P0FP1

METAL HANDLE WITH CORD GRIP		CABLE RANGE	PART #
		.770-.850"	794P0DS1
		.875-1.000"	794P0DS3
		1.000-1.125"	794P0ES2
		1.250-1.375"	794P0FS1
		1.438-1.562"	794P0FS2*
		1.562-1.688"	794P0FS3*

*May require stripping of cable jacket.

POLY HANDLE		CABLE RANGE	PART #
		.511-1.377"	514P0D35

POLY HANDLE WITH BUILT IN DRAWPLATES		CABLE RANGE	PART #
		.511-1.377"	514P0D35473

Makes connector closures easier.

SANTOPRENE HANDLE		CABLE RANGE	PART #
		.551-.787"	554P0D20L
		.708-.984"	554P0D25L
		.984-1.377"	554P0D35L
		1.377-1.771"	554P0D45L
		1.771-1.929"	554P0D49L

ANGLES

POLY ANGLE		ANGLE	PART #
	30°	514M3	
	70°	514M7	

METAL ANGLE		ANGLE	PART #
	0°	594M0	
	30°	594M3	
	30°	794M3L	
	Oversized 30°	794M3	Mounts on oversize box only. Order with 7T5F0Nxx. See pg 50.
	70°	594M7	

BOXES

POLY CONDUIT ENTRY WITH NPT		ANGLE	SIZE	PART #	Notes
	30°	1/2"	514B3N05		For poly devices only.
	30°	3/4"	514B3N07		
	30°	1"	514B3N10		* Interior volume with receptacle installed.
	30°	1 1/4"	514B3N12		

* 28.1 in³

POLY WALL BOX WITH ANGLE		ANGLE	PART #	Notes
	70°	514C7000		70° poly boxes are not drilled.

* 181.24 in³

POLY ANGLE WITH METAL BOX WITH NPT		ANGLE	SIZE	PART #	Notes
	70°	1/2"	714C7N05		* Interior volume with receptacle installed.
	70°	3/4"	714C7N07		
	70°	1"	714C7N10		
	70°	1 1/4"	714C7N12		
	70°	1 1/2"	714C7N15		

* 177.7 in³

METAL BOX WITH NPT		ANGLE	SIZE	PART #
	0°	1"	7T4F0N10	
	0°	1 1/4"	7T4F0N12	
	0°	1 1/2"	7T4F0N15	
	0°	2"	7T4F0N20	

POLY ANGLE WITH METAL BOX WITH NPT		ANGLE	SIZE	PART #	Notes
	30°	1"	714C3N10		For metal angle, replace "71" prefix with "79".
	30°	1 1/4"	714C3N12		* Interior volume with receptacle installed.
	30°	1 1/2"	714C3N15		
	30°	2"	714C3N20		

* 61.0 in³ Poly Angle

* 59.9 in³ Metal Angle

NPT on top or bottom (if rotated). For other configurations contact Customer Service.

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES		PART #	Notes
		31-6A346	Set of Two (2) Recommended for all assembly applications, for easier connector closure.

PROTECTIVE INLET/PLUG CAP		PART #	Notes
		61-6A426	For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP		PART #	Notes
		DS6MC	Aluminum - For Inlets/Plugs Only. -A155 suffix required on inlet part # to retain water ingress protection.

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP		PART #	Notes
		31-6A226	For Poly Inlets/Plugs Only.
		39-6A226	For Metal Inlets/Plugs Only.

In order to achieve max water ingress protection of Type 3R/IP55, spring loaded caps should be ordered with inlets equipped with -A155 suffix.

EASY RETROFIT ADAPTER PLATES		PART #	Notes
		see pg 240	Mount to existing boxes.

RECEPTACLE LOCKING PIN		PART #	Notes
		LP-843	Requires Padlockable Pawl option (-843) on receptacle.

DR7c Multipin - 50 A

Ratings

- **Voltage**
50 VAC or 600 VAC Max/130 VDC*
* For DC order 600V model.
- **Amperage Rating**
50 A Non-Current Interrupting
- **Temperature Range**
Min -40°F/Max 140°F
See pg 254 for temperatures outside of this range.
- **Environmental Ratings**
IP66/IP67/IP69/IP69K
- **Wiring Capacity**
Based on THHN wire sizes.
Min 14 AWG Max 8 AWG
Aux Contacts - 8 AWG
- **Certifications**
NOM

For DR7c dimensions, see pgs 103-104.

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American Configurations

VOLTAGE	POLARITY	PART #		PART #	
		POLY	METAL	POLY	METAL
50 V	4P	31-34940	39-34940	31-38940	39-38940
50 V	5P	31-34950	39-34950	31-38950	39-38950
50 V	6P	31-34960	39-34960	31-38960	39-38960
50 V	7P	31-34970	39-34970	31-38970	39-38970
600 V	3P+G	31-34931	39-34931	31-38931	39-38931
600 V	4P+G	31-34941	39-34941	31-38941	39-38941
600 V	5P+G	31-34951	39-34951	31-38951	39-38951
600 V	6P+G	31-34961	39-34961	31-38961	39-38961

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



Mushroom Pawl

Padlock Pawl

RECEPTACLE OPTIONS

SUFFIX

INLET OPTIONS

SUFFIX

With 2 Auxiliary/Pilot Contacts	Recept # -172	With 2 Auxiliary/Pilot Contacts	Inlet # -172
With 3 Auxiliary/Pilot Contacts	Recept # -173	With 3 Auxiliary/Pilot Contacts	Inlet # -173
Straight Insertion	Recept # -352²	Without Lockout Hole	Inlet # -A155
Mushroom Pawl	Recept # -375		
Padlock Pawl	Recept # -843		
Screw-Type Locking Pawl	Recept # -845		
Metal Pawl (on poly receptacle)	Recept # -824		
Self-Returning Lid (Manual Close)	Recept # -NC		

Notes: ² This option includes the Self-Returning Lid.

! See pages 231-240 for detailed information on these options

Order Example: 50 V DR7c + mushroom pawl
DR7c Poly receptacle 4P = 31-34940-**375**

