

PN12c Multipin - 15 A

Ratings
• Voltage 480 VAC Max/480 VDC
• Amperage Rating 15 A Non-Current Interrupting
• Environmental Ratings Type 4X/IP66/IP67 (Poly & Metal) Type 3R/IP54/IP55 (Stainless Steel)
• Temperature Range Min -40°F/Max 140°F See pg 254 for temperatures outside of this range.
• Wiring Capacity Based on THHN wire sizes. Min 18 AWG Max 14 AWG
• Certifications UL 2238, NOM See pgs. 111-112 for PN12c dimensions

Receptacle (female)



Inlet (male)

Inlet (male)



! Don't forget to add installation accessories to your order

North American Configurations

VOLTAGE	POLARITY	PART #			PART #		
		POLY	METAL	STAINLESS STEEL	POLY	METAL	STAINLESS STEEL
480 V	11P+G	03-A4001	07-A4001	07-A4001-SS	03-A8001	07-A8001	07-A8001-SS

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options

	Reverse Interiors
	Flush Mount [replaces female casing]
	Locking Pawl
	8 IP55 rating with Flush Mount casing.

! See pages 231-240 for detailed information on these options

Order Example: 480 V PN12c + Reverse Interiors
PN12c Receptacle 11P+G = 03-A4001-001



INSTALLATION ACCESSORIES – SIZE 1

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

HANDLES

HANDLE WITH NPT	PART # POLY	PART # METAL
Poly 1/2"	511P0N05	791P0N05L
3/4"	511P0N07	791P0N07L
Metal 1"	511P0N10	791P0N10L

For available cord grips, see pg 159.

POLY HANDLE WITH CORD GRIP	CABLE RANGE	PART #
	.350-.520"	711P0BP6
	.520-.680"	711P0CP5
	.680-.980"	711P0DP4

METAL HANDLE WITH CORD GRIP		
	.438-.500"	791P0BS3L
	.500-.562"	791P0BS4L
	.562-.625"	791P0CS1L
	.625-.750"	791P0CS4L
	.750-.875"	791P0DS1L
	.875-1.000"	791P0DS3L

POLY 90° HANDLE WITH NPT		
1/2"	751P9N05	
3/4"	751P9N07	
1"	751P9N10	

STAINLESS STEEL HANDLE WITH CORD GRIP		
.438-.500"	7X1P0BS3	
.500-.562"	7X1P0BS4	
.562-.625"	7X1P0CS1	
For Stainless Steel devices only.		
.625-.750"	7X1P0CS4	
.750-.875"	7X1P0DS1	
.875-1.000"	7X1P0DS2	

POLY HANDLE		
	.350-.700"	511P0D18

POLY ANGLED HANDLE		
	.354-.708"	511P6D18

ANGLES

POLY ANGLE		
MB Box 30°	511M3	70° Panel mounting only.

METAL ANGLE		
0°	591M0	45° 591M4

FS/FD Box 30°		
	791M3FS	

STAINLESS STEEL ANGLE		
30°	7X1M3	For Stainless Steel devices only.

BOXES

POLY CONDUIT ENTRY WITH NPT			PART #
* 7.0 in ³	30°	1/2"	511B3N05
	30°	3/4"	511B3N07

* Interior volume with receptacle installed.

POLY WALL BOX WITH NPT			PART #
* 3.4 in ³	0°	1/2"	511B0N05
	0°	3/4"	511B0N07

* Interior volume with receptacle installed.

METAL WALL BOX WITH NPT			PART #
* 3.8 in ³	0°	1/2"	591B0N05
	0°	3/4"	591B0N07

* Interior volume with receptacle installed.

POLY WALL BOX WITH ANGLE			PART #
	70°		511C7000

70° poly boxes are not drilled.

METAL BOX WITH NPT			PART #
0°	1/2"		7T1F0N05
0°	3/4"		7T1F0N07
0°	1"		7T1F0N10
0°	1 1/4"		7T1F0N12

* Interior volume with receptacle installed.