

# KUZCO LIGHTING | LED

**Filename:** PD30501-BK\_CL-UNV - Rise

**Manufacturer:** KUZCO LIGHTING

**Luminaire:** PENDANT

**Luminaire Cat:** PD30501-BK\_CL-UNV - Rise

**Lamp:** DC LED Module

**Lamp Cat:** DC LED Module

**Ballast Desc:** Vin = 120 - 277VAC , Iin = 0.17AMP ; Vout = 12 - 40VDC , Iout = 300mA

**Ballast Cat:** Novbo - NE016277030 - 2GH

**Lamp Output:** Total luminaire Lumens: 771

**Max Candela:** 75.3 at Horizontal: 300°, Vertical: 63°

**Input Wattage:** 12.1

**Luminous Opening:** Rectangle (L: 4.57", W: 10")

**Test:** 3766--25

**Test Date:** 21 October 2025

**Test Lab:** EVERFINE

**Photometry :** Type C

**CIE Class:** General Diffuse

**Cutoff Class:** Noncutoff

## Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	47.5	6.2%
0-40	85.5	11.1%
0-60	196.5	25.5%
60-90	215.8	28%
70-100	221.1	28.7%
90-120	205.9	26.7%
0-90	412.3	53.5%
90-180	358.7	46.5%
0-180	771.0	100%

## Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	5.0	0.7%	90-100	73.8	9.6%
10-20	15.8	2.0%	100-110	69.6	9%
20-30	26.7	3.5%	110-120	62.4	8.1%
30-40	38.0	4.9%	120-130	52.9	6.9%
40-50	49.6	6.4%	130-140	42.0	5.4%
50-60	61.3	8.0%	140-150	30.4	3.9%
60-70	68.5	8.9%	150-160	18.7	2.4%
70-80	72.7	9.4%	160-170	8.3	1.1%
80-90	74.6	9.7%	170-180	0.5	0.1%

