



**Filename:** WS25125-BN-UNV - Pandora

**Manufacturer:** KUZCO LIGHTING

**Luminaire:** WALL MOUNT/WALL SCONCE

**Luminaire Cat:** Pandora - WS25125 - BN

**Lamp:** LED with DC Driver

**Ballast Desc:** Vin = 120 VAC , Iin = 0.32AMP ; Vout = 18 - 40 VDC , Iout = 500mA

**Ballast Cat:** Novbo - NE024120050-2G

**Lamp Output:** Total luminaire Lumens: 1100.9

**Max Candela:** 388.5 at Horizontal: 0°, Vertical: 77.5°

**Input Wattage:** 18.6

**Luminous Opening:** Circular (Dia: 4.33")

**Test:** 2759-24

**Test Date:** 25 October 2024

**Test Lab:** KUZCO LIGHTING

**Photometry :** Type C

**CIE Class:** General Diffuse

**Cutoff Class:** Noncutoff

**Nema Type:** 7 X 7

#### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	34.0	3.1%
0-40	80.3	7.3%
0-60	244.7	22.2%
60-90	361.5	32.8%
70-100	370.4	33.6%
90-120	320.0	29.1%
0-90	606.2	55.1%
90-180	494.7	44.9%
0-180	1,100.9	100%

#### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	1.0	0.1%	90-100	120.9	11%
10-20	8.6	0.8%	100-110	108.3	9.8%
20-30	24.4	2.2%	110-120	90.8	8.2%
30-40	46.3	4.2%	120-130	70.5	6.4%
40-50	70.7	6.4%	130-140	50.0	4.5%
50-60	93.8	8.5%	140-150	31.3	2.8%
60-70	112.1	10.2%	150-160	16.2	1.5%
70-80	123.3	11.2%	160-170	5.9	0.5%
80-90	126.2	11.5%	170-180	0.8	0.1%

