

⚠ WARNINGS AND CAUTIONS

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Please Note:

- This Alora LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- For dimming, an ELV (Electronic Low Voltage) or TRIAC or 0-10V type of dimmer is required
- 120-277V input

NOTICE

- The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.
- This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

ASSEMBLY INSTRUCTIONS

Step 1

Remove the mounting plate (1c) from within the canopy (2a) by loosening the two decorative nuts provided (2b). Attach the mounting plate (1c) to the junction box (1a) using two junction box screws (not provided) (1e). Next thread the top end of the fixture suspension rods (3b) to the fixture hub (3a) and secure the bottom end of the fixture suspension rods (3b) to the fixture ring using the Allan key provided (3c).

Step 2

Determine the desired length the fixture will hang by selecting from the assorted rod sizes supplied (2d). Slide selected rods through the fixture wires and thread the rod assembly to fixture suspension hub (3a). Feed fixture wires through canopy pivot (2c) and canopy (2a) and thread canopy pivot to fixture assembly.

Step 3

Make proper electrical connections between LED and DC driver, LED-Negative, LED+ Positive using wire nuts provided (See Illustration 3 and refer to diagram on driver)

Step 4

Make proper electrical connections (**black to hot "L"**, **white to neutral "N"**, **ground to "GND"**) with wire nuts (1b) provided in hardware package. Connect 0-10V dimming wire, DIM+ to purple, DIM- to gray, with wire nuts provided

Step 5

Now align the holes in the canopy with the threaded screws (1d) on the mounting plate. Push the canopy up towards the ceiling so that the threaded screws (1d) pass through the holes and thread on the decorative nuts (2b). This will secure canopy to mounting plate.

You are now ready to enjoy your fixture.

