Ceiling LED Pendant

PD39307-UNV-RT

3a.

INSTALLATION SHEET

Non-Powered

START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all time during this installation
- · Read instructions carefully before you start assembly
- · Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120-277V input

Remove fixture from its original package

2. Remote driver (4a) must be installed and voltage wires brought to the mounting location prior to fixture installation. Make proper electrical connections (black to hot "L", white to neutral "N", green to "GND") with wire nuts provided in hardware package. Secure driver lid (4d) to driver box (4b) with screws (4c)

Recommended Max Voltage Wire Length

12 AWG= 80ft

14 AWG= 50ft

18 AWG= 30ft

- Connect LED+/LED- wire from remote driver (4a) to approximate location. Make proper LED+/LED- wire connection with wire nuts provided
- **4.** Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package. Secure non-power mounting plate (3c) to non-power junction box (3a) with screws (3e)
- Slide diffuser (6a) over LED module (6c) of rope segment. Secure diffuser (6a) with connector (6b) on rope segment and thread clockwise to secure (See Illustration 1)
- **6.** Attach canopy (2a) to mounting plate (1c) with canopy screws (2b). Secure non-power canopy (5a) to non-power mounting plate (3c) with screws (5b)









