

Represented by



Product Specification Sheet

Illing Part#

36110RHS

89-400 ORANGE HS FOIL FOR PE .008 C1S FSM-1 "SFYP"

Part #: 36110RHS

Size:	89-400 NECK FINISH
Color:	ORANGE
Material:	CONTINUOUS THREAD CAP
Style:	NBE-340T HS FOIL FOR PE
Additional Info:	.008 C1S FSM-1 "SFYP"
Case Pack:	624 / EACH
Pallet Pack:	9,360 / EACH



www.illingpackaging.com

Represented by



ILLINGTM
P A C K A G I N G

Product Specification Sheet

Illing Part#

36110RHS

SHALLOW SKIRTED CLOSURES

89-400-9613 S



Specifications:

DIAMETER 89 mm

THREAD PROFILE 400

NECK FINISH 89-400

CLOSURE TOP Stipple

CLOSURE SIDEWALL Fine Ribbed

MATERIAL PP

PACKAGING & FREIGHT INFORMATION

PACK TYPE	PCS/CTN	CTNS/PALT	PCS/PALT	CTN WT*	PALT WT*	FRT CLASS
Stack	624	15	9,360	20 ⁽¹⁾	296 ⁽¹⁾	125 ⁽¹⁾
Stack	624	15	9,360	23 ⁽²⁾	296 ⁽²⁾	125 ⁽²⁾
CARTON DIMENSIONS: 24 x 16 x 15				PALLET DIMENSIONS: 48 x 40 x 50		

(1) Unlined Closures (2) Lined Closures *Approximate

MARKETS

Food, Food Service, Agricultural, Automotive, Industrial and Medical Products, Dressings & Sauces, Personal Care & Cosmetics, Soup Base, Pharmaceuticals, Nutraceuticals & Powdered Drinks.

OPTIONS

Available in white, standard, and custom colors. Liners can be cut with a pull-tab or tri-tab easy-open feature.

CLOSURE BENEFITS

- A great general-purpose closure
- Fine-ribbed sides are easier to grip
- Our most popular closure style




PHOENIXTM

PHXPKG.COM

P 630 420 4750 E greatpkg@phxpkg.com
1899 High Grove Lane Naperville, IL 60540

SHALLOW SKIRTED CLOSURES

89-400-9613 S




NOTES: (UNLESS OTHERWISE SPECIFIED) 1. ALL DIMENSIONS ARE IN INCHES. 2. SEE CHART FOR DIMENSIONAL TOLERANCE.				4	04.08.15	Re-define Reference Dimensions	DN
				REV	DATE	DESCRIPTION	BY
THIS OR FACSIMILE THEREOF IS THE EXCLUSIVE PROPERTY OF PHOENIX AND MAY NOT BE REPRODUCED WITHOUT THE EXPRESSED WRITTEN CONSENT OF PHOENIX. SOME OR ALL OF THE ITEMS DEPICTED ON THIS DRAWING MAY BE COVERED BY CURRENT PATENTS OR PATENTS APPLIED FOR BY PHOENIX.				TOLERANCE	PITCH/TPI	.200 / 5	TURNS 1-3/16
				.X	±0.1	DRAWN	DMN
				.XX	±0.02	DATE	07.27.06
				.XXX	±0.010	SCALE	1 : 1
89 - 400 - 9613 S							4



SHALLOW SKIRTED CLOSURES

89-400-9613 S



Represented by



Product Specification Sheet

Illing Part#

36110RHS




Freshness and Protection
for Today's Packaging

FoilSeal™ Data Sheet

.008" C1S FS1-16

Revision: FS116-06012010

Product	.008" C1S FS1-16		
Scope	One piece board backed heat induction foil innerseal will provide an aggressive bond with clean peel removal from PE and PP containers. (.0005" mil foil version of FS 1-13, easy access / "puncture foil" when wax bonded to pulp).		
Composition	Material	Standard	Metric
	Backing	.008"	.2032 mm
	Foil	.0005"	.0127 mm
	Heat Seal	.002"	.0508 mm
 Composition does not include adhesive, resin or wax bonding layers (if any).			
FDA Status:	21 CFR 177.1210	Recommended Storage and Handling:	
Drug Master File (DFM):	#4544	Canadian DMF:	EU / EP Reg.:
GTR Oxygen:	Essentially Zero	MVTR:	Essentially Zero
Print Location (if any):	Heat Seal Layer and/or Backing		

Selig materials are compliant with current USFDA Food allergen Guidelines.
Selig materials are compliant with California Proposition 65 labeling requirements.
Selig materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

MSDS's are not required as Selig is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

The information contained within this product data bulletin is to be used as a general guide in determining which structures are offered for sealing to specific container materials. All of the information which we provide is reliable to the best of our knowledge, but the accuracy thereof is not guaranteed. We suggest that consumers determine suitability for their own application.

www.seligsealing.com

Corporate Headquarters
Selig Sealing Products, Inc.
342 E Wabash St
Forrest, IL 61741, USA
Phone: +1 (815) 785-2100
Fax: +1 (815) 657-7584

North American Sales
Selig Sealing Products, Inc.
184 Shuman Blvd., Suite 310
Naperville, IL 60563, USA
Phone: +1 (630) 922-3158
Fax: +1 (630) 922-8469

European Sales and Manufacturing
Selig UK, LTD 635-637 Ajax Avenue
Slough Trading Estate
Slough Berkshire SL14BH UK
Phone: +44 (0) 1753 773 000
Fax: +44 (0) 1753 773 111

Canadian Manufacturing
Selig Canada, ULC
145 Edward Street
Aurora, Ontario Canada, L4G 1W3
Phone: +1 (905) 727-0114
Fax: +1 (905) 727-8544

Swiss Manufacturing
Selig Switzerland LTD
Bahnhofstrasse 11
CH-8172 Niederglatt
Phone: +41 (0) 44 851 50 50
Fax: +41 (0) 44 851 50 51