





45-400 WHITE PP RIBBED SIDES & MATTE TOP CAP WITH F217.035 PL LINER

Part #: 3644P

Size:	45-400 NECK
Color:	WHITE
Material:	PP
Style:	RIBBED SIDES & MATTE TOP CAP
Additional Info:	F217.035 PL LINER
Case Pack:	2000 / EACH
Pallet Pack:	70000 / EACH



SECTION A-A



STATIC TORQUE RECOMMENDATION: 17-27 in-lbs
REQUIREMENT. MAY VARY DEPENDING UPON CONTAINER MATERIAL,
NECK FINISH, AND CAPPING EQUIPMENT

DIMENSIONS ENCLOSED IN () INDICATE REFERENCE DIMENSIONS
AND NO TOLERANCE LIMITS ARE ESTABLISHED

DIMENSIONS PRECEDED BY AN *** INDICATE THE DIMENSION IS
PROCESS SENSITIVE. PROCESS SENSITIVE DIMENSIONS ARE
VERIFIED TO BE WITHIN THE TOLERANCE LIMITS DURING THE
PRODUCTION RUN. ALL REMAINING DIMENSIONS ARE VERIFIED AT
PRODUCTION VALIDATION.

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING IS PROTECTED BY COPYRIGHT AND CONTAINS
INFORMATION PROPRIETARY TO MOLD-RITE PLASTICS AND ITS
SUBSIDIARIES. ANY REPRODUCTION, DISCLOSURE, OR USE OF
ITS CONTENTS OR ANY PART THEREOF IS EXPRESSLY
PROHIBITED EXCEPT AS MOLD-RITE PLASTICS AND ITS
SUBSIDIARIES OTHERWISE MAY AGREE IN WRITING.

THIS MASTER DOCUMENT IS CONTROLLED ELECTRONICALLY.
PRINTED OR DOWNLOADED COPIES ARE UNCONTROLLED.
DOCUMENT USERS ARE RESPONSIBLE FOR ENSURING THEY HAVE
THE LATEST REVISION PRIOR TO USE.

THE PART DIMENSIONS DEPICTED ARE THOSE WHICH HAVE GENERALLY BEEN FOUND TO BE FUNCTIONAL BASED ON INDUSTRY EXPERIENCE.
BECAUSE OF VARIABILITY IN CONTAINER FINISHES, EACH CLOSURE/FINISH SYSTEM SHOULD BE INDIVIDUALLY EVALUATED AND TESTED TO
ENSURE IT MEETS APPLICABLE PERFORMANCE CRITERIA.

MOLD-RITE PLASTICS AND ITS SUBSIDIARIES RESERVE THE RIGHT TO REVISE ANY OR ALL SPECIFICATIONS AND REQUIREMENTS.

REFERENCE	DIMENSION	TOLERANCE	UNITS
ϕE	1.656 [42.06]	± 0.010 [0.25]	in [mm]
ϕT	1.752 [44.5]	± 0.010 [0.25]	in [mm]
H	0.390 [9.91]	± 0.010 [0.25]	in [mm]
OD	1.865 [47.37]	± 0.012 [0.30]	in [mm]
OAH	0.445 [11.30]	± 0.010 [0.25]	in [mm]
PART WEIGHT	3.90	± 0.50	g

THREAD DETAIL INFORMATION:	6 THREADS PER INCH	0.167" [4.24] PITCH	360° FULL DEPTH THREADS
-------------------------------	-----------------------	---------------------	----------------------------



DRAWING TITLE:

45-400 CT CLOSURE
RMX (RIBBED SIDE - MATTE TOP)

MATERIAL: POLYPROPYLENE

DRAWING TYPE: CUSTOMER DISTRIBUTION CODE: D


REPLACES DRAWINGS: C-5010

MODEL NUMBER: PM 10297 45-400 CT

DWG SIZE: 8.5" x 11" DRAWING NUMBER: REVISION:

SCALE: SHEET: 1 OF 3 CQA-10302 00.AE

5:1 & NOTED



148 EQUALLY SPACED RIBS
DETAIL RIBS
SCALE 4 : 1

MOLD NUMBER	GATE LOCATION
45003	SIDE
45007	SIDE


DIMENSIONS ENCLOSED IN () INDICATE REFERENCE DIMENSIONS AND NO TOLERANCE LIMITS ARE ESTABLISHED. PROPRIETARY AND CONFIDENTIAL THIS DRAWING IS PROTECTED BY COPYRIGHT AND CONTAINS INFORMATION PROPRIETARY TO MOLD-RITE PLASTICS AND ITS SUBSIDIARIES. ANY REPRODUCTION, DISCLOSURE, OR USE OF ITS CONTENTS OR ANY PART THEREOF IS EXPRESSLY PROHIBITED EXCEPT AS MOLD-RITE PLASTICS AND ITS SUBSIDIARIES OTHERWISE MAY AGREE IN WRITING. THE PART DIMENSIONS DEPICTED ARE THOSE WHICH HAVE GENERALLY BEEN FOUND TO BE FUNCTIONAL BASED ON INDUSTRY EXPERIENCE. BECAUSE OF VARIABILITY IN CONTAINER FINISHES, EACH CLOSURE/FINISH SYSTEM SHOULD BE INDIVIDUALLY EVALUATED AND TESTED TO ENSURE IT MEETS APPLICABLE PERFORMANCE CRITERIA. MOLD-RITE PLASTICS AND ITS SUBSIDIARIES RESERVE THE RIGHT TO REVISE ANY OR ALL SPECIFICATIONS AND REQUIREMENTS.						
	08/07/2023	00	AE	UPDATE DRAWING FORMAT	LES	LES
	12/27/2021	00	AD	CORRECT RIB COUNT NOTE TO MATCH PHYSICAL PARTS. UPDATE RECOMMENDED NECK FINISH "H" TOLERANCE FROM BILATERAL (+/-) TO RECOMMENDED MINIMUM.	LES	LES
	07/27/2017	00	AC	UPDATED OD TOLERANCE, T DIMENSION AND PART WEIGHT BASED ON HISTORICAL DATA, ADDED MOLD GATE LOCATION TABLE	BDG	DAS
	12/27/2016	00	AB	CORRECTED PART WEIGHT (WAS 3.6), ±0.012 [0.30] OD TOLERANCE WAS ±.010[0.25]	JDM	JDM
	06/03/2016	00	AA	UPDATE DRAWING FORMAT, REFER TO C-5010 FOR REVISION HISTORY	JDM	JDM
	DATE	REV	N/P	DESCRIPTION	ENG	DRW
REVISION HISTORY REVISIONS: REV: A PHYSICAL CHANGE TO THE PART IMPACTING FIT, FORM OR FUNCTION N/P: DRAWING OR SPECIFICATION CHANGE ONLY						



DRAWING TITLE:
**45-400 CT CLOSURE
RMX (RIBBED SIDE - MATTE TOP)**


THIS MASTER DOCUMENT IS CONTROLLED ELECTRONICALLY. PRINTED OR DOWNLOADED COPIES ARE UNCONTROLLED. DOCUMENT USERS ARE RESPONSIBLE FOR ENSURING THEY HAVE THE LATEST REVISION PRIOR TO USE.

DRAWING TYPE: CUSTOMER	DISTRIBUTION CODE: D
DWG SIZE: 8.5" x 11"	DRAWING NUMBER: CQA-10302
SCALE: 1:1 & NOTED	REVISION: 00.AE
SHEET: 2 OF 3	



SECTION B-B
SCALE 1 : 1

0.050" [1.27mm]
MINIMUM RECOMMENDED
LAND FOR PROPER
INDUCTION SEAL



DETAIL THREAD
SCALE 4 : 1

RECOMMENDED NECK FINISH IS DETERMINED FOR PROPER FUNCTIONAL PERFORMANCE WITH MOLD-RITE CLOSURE. USE OF MOLD-RITE CLOSURE WITH CONTAINER NOT MATCHING RECOMMENDED NECK FINISH SHOULD BE TESTED AND CONFIRMED FOR APPLICATION BY THE USER.

NOMINAL ORIENTATION OF CLOSURE (IF INDICATED) IS BASED ON NOMINAL DIMENSIONS OF BOTH CLOSURE AND RECOMMENDED NECK FINISH. FOR EXACT ORIENTATION, EACH CONTAINER SHOULD BE EVALUATED ON A CASE BY CASE BASIS.

DIMENSIONS ENCLOSED IN () INDICATE REFERENCE DIMENSIONS AND NO TOLERANCE LIMITS ARE ESTABLISHED

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING IS PROTECTED BY COPYRIGHT AND CONTAINS INFORMATION PROPRIETARY TO MOLD-RITE PLASTICS AND ITS SUBSIDIARIES. ANY REPRODUCTION, DISCLOSURE, OR USE OF ITS CONTENTS OR ANY PART THEREOF IS EXPRESSLY PROHIBITED EXCEPT AS MOLD-RITE PLASTICS AND ITS SUBSIDIARIES OTHERWISE MAY AGREE IN WRITING

THE PART DIMENSIONS DEPICTED ARE THOSE WHICH HAVE GENERALLY BEEN FOUND TO BE FUNCTIONAL BASED ON INDUSTRY EXPERIENCE. BECAUSE OF VARIABILITY IN CONTAINER FINISHES, EACH CLOSURE/FINISH SYSTEM SHOULD BE INDIVIDUALLY EVALUATED AND TESTED TO ENSURE IT MEETS APPLICABLE PERFORMANCE CRITERIA.

MOLD-RITE PLASTICS AND ITS SUBSIDIARIES RESERVE THE RIGHT TO REVISE ANY OR ALL SPECIFICATIONS AND REQUIREMENTS.

NECK FINISH DIMENSIONS ASSUME ZERO THICKNESS (NO) LINER				
REFERENCE	DIMENSION	TOLERANCE	UNITS	
ϕE	1.631 [41.43]	± 0.017 [0.43]	in [mm]	
ϕT	1.725 [43.82]	± 0.017 [0.43]	in [mm]	
S	0.046 [1.17]	± 0.015 [0.38]	in [mm]	
H	0.400 [10.16]	MINIMUM	in [mm]	
THREADS PER INCH	6			
PITCH	0.167 [4.24]		in [mm]	



DRAWING TITLE:


**45-400 CT CLOSURE
RECOMMENDED NECK FINISH**

THIS MASTER DOCUMENT IS CONTROLLED ELECTRONICALLY. PRINTED OR DOWNLOADED COPIES ARE UNCONTROLLED. DOCUMENT USERS ARE RESPONSIBLE FOR ENSURING THEY HAVE THE LATEST REVISION PRIOR TO USE.

DRAWING TYPE: CUSTOMER	DISTRIBUTION CODE: D
DWG SIZE: 8.5" x 11"	DRAWING NUMBER:
SCALE: 1:2 & NOTED	REVISION:
SHEET: 3 OF 3	CQA-10302 00.AE


TRI-SEALTM PRODUCT DATA SHEET


- This data sheet describes F-217® products
- This product is a three-ply co-extruded liner consisting of a foamed Low Density Polyethylene (LDPE) core sandwiched between two layers of solid Low Density Polyethylene



MRP Description - (024)F217.035 PL

Typical Product Attributes
Construction

Structure	Solid LDPE / Foamed LDPE / Solid LDPE	Solid LDPE / Foamed LDPE / Solid LDPE
Color	White or as Specified	White or as Specified
Density		
for 20 ~ 30 mil (0,51 ~ 0,76 mm)	0,48 ± 0,03 g / cm ³	30 ± 2 lbs / ft ³
for 35 ~ 125 mil (0,89 ~ 3,18 mm)	0,40 ± 0,03 g / cm ³	25 ± 2 lbs / ft ³
Thickness Tolerance		
for 20 ~ 60 mil (0,51 ~ 1,52 mm)	± 0,127 mm	± 5 mil
for 65 ~ 90 mil (1,65 ~ 2,29 mm)	± 0,178 mm	± 7 mil
for 95 ~ 125 mil (2,41 ~ 3,18 mm)	± 0,254 mm	± 10 mil
Available Width		
for 20 ~ 60 mil (0,51 ~ 1,52 mm)	22,2 ~ 1016,0 mm	7/8 ~ 40 inch
for 65 ~ 125 mil (1,65 ~ 3,18 mm)	25,4 ~ 228,6 mm	1 ~ 9 inch
Width tolerance	± 1,6 mm	± 1/16 inch

Regulatory Compliance

FDA Compliance	21 CFR 177.1520 (Olefin Polymers) 21 CFR 177.1210 (Closures with Sealing Gaskets for Food Containers) 21 CFR 175.300 (Resinous and Polymeric Coatings)
Drug Master File (DMF)	2434
Other Compliances	USFDA Food Allergen Guidelines; California Proposition 65 Labeling Requirements; Limitations of Heavy Metals in Packaging per CONEG & EU 94/62/EC, Article 11

 Original Date: 08/05/1997
 Revised Date: 01/31/2011
 Revision Number: 5
 Revised by SR

DISCLAIMER: This information is believed to be accurate at the time of printing and is subject to change without notice. Providing this information does not convey any licenses under any patent rights or other intellectual property rights of TRI-SEAL or others. **TRI-SEAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT.** TRI-SEAL's only warranties for this product are those written warranties as may be agreed to by TRI-SEAL and its customers. **TRI-SEAL SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.**