

Represented by



Product Specification Sheet

Illing Part# 3H3010BRN

5 GALLON BROWN-30 HDPE TE TEAR BAND TAB COVER WITH RUBBER GASKET

Part #: 3H3010BRN

Size:	5 Gallon
Color:	Brown
Material:	HDPE
Style:	Tamper Evident
Additional Info:	With EPDM Rubber Gasket
Case Pack:	300
Pallet Pack:	600



www.illingpackaging.com



Product Specifications Lids

e.HOFMANN
 PLASTICS

TECHNICAL DATA

Fits Pails: PR1200, PR1300, PR1400, PR1700, PR1907, PR1910, PR2000, PR2300

Lid	LR1940 - Tearstrip Lid with Gasket (EPDM Rubber)
-----	--

Wall Thickness	LR1940	2.16mm	0.085in
----------------	--------	--------	---------

Weight (approx.) without bail	LRT940	255g	8.99oz
-------------------------------	--------	------	--------

Material	HDPE
----------	------

Thermal range	-18°C (0°F) to 66°C (150°F)
---------------	-----------------------------

Lid Colour	Standard in White, other colors available.
------------	--

PRODUCT CODE

Lid: LR1940



TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production. Can be restricted by pail specifications.

OPENING & CLOSING

TO OPEN: Remove tear tab, then lift cover.

TO CLOSE: Place lid on pail, and use capping machine, or press on with hands/mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

DIMENSIONS

	CM	INCHES
Lid Height	3.505	1.38
External Diameter	31.72	12.49

PACKAGING OF LIDS

• Warehousing of 1940 Lids:

300 per tray - 600 per pallet

• Max 4 pallets high for warehousing of lids

