

Represented by



ILLING[™]
P A C K A G I N G

Product Specification Sheet

Illing Part#

3I3204W

2 GALLON WHITE PP OH RECTANGLE PAIL WITH METAL HANDLE

Part #: 3I3204W

Size:	2 Gallon
Color:	White
Material:	PP
Style:	OH Plastic Rectangle Pail
Additional Info:	With Metal Handle
Case Pack:	825 each
Pallet Pack:	1,650 each

ENVISION
DESIGN DECORATE DELIVER

LabelILLING[™]

Shrink Labeling

AI SMART
PACKAGING

ILLING
GLOBAL
S O U R C I N G

www.illingpackaging.com


SPECIFICATION SHEET

April 2016

InPack (8L -2 US gal)
PAIL # 63052
LID # 63451 (Hinge lid)
» TECHNICAL DATA

Capacity under lid: • 7.660 L / 2.024 US gal.

 Wall thickness: • Pail: (0.045 in.)
 • Lid : (0.045 in.)

Material: • Pail & lid: PPC


Thermal range: • 0°C (32°F) to 82°C (180°F)

Standard color : • White or other colors upon request

Weight (approx.) without handle or gasket:

 • Pail: (256 g) 9.030 oz
 • Lid : (70 g) 2.469 oz

Handle: • Plastic



(Materials are recyclable or can be recovered for energy)

» TOP LOADING RESISTANCE

53 kg (116 lbs) at 23°C / 73°F, 30 days. Product temperature when filling pails and warehouse temperature will affect pail performance. IPL recommends to make necessary testing prior to full production.

» PRINTING (Not available)
» CLOSING INSTRUCTION

TO CLOSE: Align lid, then press and snap all around while releasing air by pressing the center of the lid to burp container. A pail closing roller or mobile plate device can be used. If using an automated closing device, use proper lid air removing system.

» WAREHOUSING OF EMPTY PAILS

Two pallets high in warehousing


» RECOMMENDATIONS

- Do not exceed pallet edges with pails
- Staggered pattern is recommended for greater stability
- Double faced pallets with close together boards on both sides are recommended for best results
- To improve stability, release air from pail when putting the lid
- Stretch wrapping machine tension should be adjusted to pail
- Use slip-sheet to improve pails stability if necessary

ILLING PT#: 3I3204W & 3I3204W

» PALLETIZATION OF FILLED PAILS

To determine the number of pails you can stack according to the product packed, divide the top loading resistance by the total weight of one filled pail. Take that number not rounded up and add the first unit.


 25 pails per layer
Stacked pails recommendation:
 4 pails high/ pallet

Approvals: Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Advice: Handling conditions vary a lot from customer to customer, tests are recommended throughout the process of denesting, filling, conveying, palletization, warehousing, transportation and utilization by end users, etc. Specifications can be modified without notice. Please contact your IPL representative to confirm these data.

Quality Assurance: .. IPL is ISO 9001 certified and quality procedures are documented in our quality system.


CANADA IPL PLASTICS INC. - 140, Commercial Street, St-Damien, Quebec Canada G0R 2Y0

Tel: (418) 789-2880 - Fax: (418) 789-3153 - Toll free (Service): 1-800-463-0270

USA IPL PRODUCTS, LTD. - 401 SE Thompson Drive, Lee's Summit (Missouri) USA 64082

Tel: (816) 246-8200 - Fax: (816) 246-8119

 Approved by: *Stéphane Mercier*

www.ipl-plastics.com

Rev. 010516