



145 West Commercial Ave.
Moonachie, NJ 07074

Dimmer Compatibility

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacture

Product Family Name:
Item Number: 776712
Ordering Code: LED4G16/30K/FIL/M/3
Item Number:
Ordering Code:

Manufacturer		Product	Model Number
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IllumaTech	IPI06
		SureSlide	6633-P
		Vizia	VPI06-1LZ
	Lutron	Toggler	TG-600
		Lumea	LGCL-600
		Diva	DV-600
		Skylark	S-600
		Maestro	MAW-600
	Legrand	Titan	CD703-PW
		Harmony	D703-PTC
		Harmony	H703-PTC
CFL/LED	Leviton	IllumaTech	IPL06
		Sureslide	6674
		Decora	6672
		Decora Slide	DSL06-1LZ
	Lutron	Skylark	CTCL-153
		Diva	DVCL-153PL
		Maestro	MACL-153MLH
		Skylark	SCL-153P
		Toggler	TGCL-153PH
		Radio RA	RA2RR-6CL-PD
	Legrand	Harmony	DCL453-PTC
		Harmony	HCL453PTC
		Adorne Paddle	ADPD453LM2
Electronic Low Voltage	Leviton	Vizia	VPE04
		IllumaTech	IPE04
		Decora	6615-P
	Lutron	Skylark Countour	CTELV-303P
		Diva	DVELV-300P
		Maestro	MAELV-600
		Skylark	SELVB-300P
		VIERTI	VTEL-600M-W
	Legrand	Scene Director	SCELV
Magentic Low Voltage	Leviton	Vizia	VPM-06
		Decora	6613-P
	Lutron	Maestro	MALV-600
	Legrand	Harmony	DLV703-PW
		Titan	CDLV703-PW
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ
	Leviton	Decora Smart Z-Wave Technology	DZ6HD
	Leviton	Decora Smart WiFi Technology	DW1KD
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-10NXD
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL
	GE	Z WAVE	ZW3005
Universal	Legrand	Adorne SofTap	ADTP703TU
		Miro Decorator	DRD4-W
		Harmony	H703PTUTC
		Adorne Whisper	ADWR700MMTUW2
		Adorne Touch	ADTH700MMTUM2
	Cooper	Decorator	DAL06P-C2-K-L
		Skye	SAL06P-W-K-L

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the ligh

were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dim
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be p
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, wl light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimr
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel
Low End (L.E.) Dead Travel	

Contact Information:
Bulbrite Industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite Industries Inc.
All Rights Reserved.

ty Guide

in a lab simulated environment. Actual results may vary.

Lamps per Dimmer

Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	5	6	Dims down to 1% with 5+
Good	3	6	Dims down to 1%, flickering at LE with 1
Good	1	6	Dims down to 1%, flickering at LE with 1
Best	1	6	Dims down to 1%

Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	1	6	Dims down to 15%, flickering at LE with 1-2

Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 15%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	2	6	Dims down to 1%
Best	1	6	Dims down to 1%
Not Compatible	1	6	Doesn't work with 1-6
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%

Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best			Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%

Best	1	6	Dims down to !%
Best	1	6	Dims down to 1%
Good	1	6	Dims down to 20%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%

its to first turn on if they

ming range, does not turn off.
resent, dimming not smooth.
rich means there may be periods of time when the slider (or other form of control button) is moved without affecting the
ning range - can dim down to 20% or less of light output.
l is when the slider can be moved without affecting the light level.