SORAA BRILLIANT HL PAR30S 120V 14W - DIMMER COMPATIBILITY LIST - North America

| Dimmer Manufacturer | Dimmer family | Dimmer Model | Dimming phase | Number of lamps per dimmer tested | Dim (%) | Comments |
|------------------------|-------------------------------------|-------------------------|---------------|-----------------------------------|---------|----------|
| Creston | | DIN-1DIMU4 | Reverse | 5 | 4% | |
| Lutron | Caseta | PD-5NE | Reverse | 5 | 6% | |
| Lutron | Diva | DVCL-153P | Forward | 5 | 3% | |
| Lutron | Diva | DVELV-300P | Reverse | 5 | 3% | |
| Lutron | Diva | DVLV-600P | Forward | 5 | 9% | |
| Lutron | Grafik Eye QS | QSGRJ-3P | Forward | 5 | 2% | |
| Lutron | Interface | PHPM with Grafik Eye QS | Reverse | 5 | 1% | |
| Lutron | Maestro | MACL-153M | Forward | 5 | 10% | |
| Lutron | Radio Ra2 | RRD-6NA | Reverse | 5 | 3% | |
| Lutron | Remote Power Modules / Homeworks | HW / LP-RPM-4A-120 | Reverse | 5 | 0% | |
| Lutron | Skylark | SLV-600P | Forward | 5 | 9% | |
| Lutron | Skylark | SELV-300P | Reverse | 5 | 3% | |
| Marlin | Stellar RMS 4 | Stellar RMS 4 | Reverse | 5 | 4% | |

Notes:

Compatibility tests are conducted by Soraa (unless stated otherwise) only as guidance for the user

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site

Results may vary due to variability in component choices and manufacturing processes by the dimmer manufacturer

Regards compatibility tests conducted by dimmer manufacturer, please contact Soraa or the manufacturer for more details and/or reports.

(*) Test results with this dimmer added to the compatibility list as of this Revision

| % | Dims to < 20% (of the measured light output) |
|------------|---|
| % | Dims to 20-30% (of the measured light output) |
| NC | Not compatible (or dims to >30%) |
| Blank cell | Not tested |