



Tested Unit Item Number: 773603

Tested Unit Ordering Code: LED10FLUSH/5/SCCT/927-950/UW/H/D

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	a IllumaTech	IPI06	Good	1	6	Not smooth, jumps, dead travel (HE 15%,LE 20%)
		b SureSlide	6633-P	Bad	1	6	Not smooth w/ 6, flickers heavily w/ 5
		c Vizia	VPI06-1LZ	Best	1	6	
	Lutron	d Toggler	TG-600	Good	1	6	Slight flicker @ MIN w/ <6, dims to <1%
		e Lumea	LGCL-600	Bad	1	6	80% @ MAX with >2
		f Diva	DV-600	Good	1	6	Delay while dimming, LE dead travel (30%)
		g Skylark	S-600	Best	1	6	
		h Maestro	MAW-600	Bad	2	6	Not compatible with <2
	Legrand	i Titan	CD703-PW	Not Compatible	2	6	
		j Harmony	D703-PTC	Bad	2	6	Not compatible with <2
		k Harmony	H703-PTC	Bad	2	6	Not compatible with <2
CFL/LED	Leviton	l IllumaTech	IPL06	Good	1	6	HE dead travel (15%), significant delay
		m Sureslide	6674	Good	1	6	HE dead travel (30), significant delay
		n Decora	6672	Best	1	6	
		o Decora Slide	DSL06-1LZ	Best	1	6	
	Lutron	p Skylark	CTCL-153	Best	1	6	
		q Diva	DVCL-153PL	Best	1	6	
		r Maestro	MACL-153MLH	Best	1	6	
		s Skylark	SCL-153P	Best	1	6	
		t Toggler	TGCL-153PH	Best	1	6	
		u Radio RA	RA2RR-6CL-PD	Best	1	6	
	Legrand	v Harmony	DCL453-PTC	Best	1	6	
		w Harmony	HCL453PTC	Good	1	6	Not smooth, jumps in the middle
		x Adorne Paddle	ADPD453LM2	Best	1	6	Dims to 2%
Electronic Low Voltage	Leviton	y Vizia	VPE04	Best	1	6	
		z IllumaTech	IPE04	Bad	1	6	Not smooth, slight flicker while dimming
	Lutron	aa Decora	6615-P	Bad	1	6	Not smooth, slight flicker while dimming
		ab Skylark Countour	CTELV-303P	Best	1	6	
		ac Diva	DVELV-300P	Best	1	6	
		ad Maestro	MAELV-600	Best	1	6	
		ae Skylark	SELVB-300P	Best	1	6	
		af VIERTI	VTEL-600M-W	Best	1	6	
Magnetic Low Voltage	Leviton	ah Vizia	VPM-06	Good	1	6	Slight flicker while adjusting
		ai Decora	6613-P	Best	1	6	LE dead travel (20%)
	Lutron	aj Maestro	MALV-600	Not Compatible		6	
		ak Harmony	DLV703-PW	Best	1	6	Fully dims by 20%
	Legrand	al Titan	CDLV703-PW	Bad	2	6	Not smooth with 1, significant delay when raising from MIN
Smart Dimmer	Leviton	am Decora Digital (Bluetooth)	DDMX1-BLZ	Good	1	6	Not smooth, stable
	Leviton	an Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	
	Leviton	ao Decora Smart WiFi Technology	DW1KD	Best	1	6	
	Lutron	ap Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	
	Lutron	aq Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims to 3%
	GE	ar Z WAVE	ZW3005	Best	1	6	Very slight flicker WHILE DIMMING at low levels
Universal	Legrand	as Adorne SoftTap	ADTP703TU	Best	1	6	
		at Miro Decorator	DRD4-W	Not Compatible		6	
		au Harmony	H703PTUTC	Bad	2	6	Not smooth, not compatible with 1
		av Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims completely
		aw Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims completely
	Cooper	ax Decorator	DAL06P-C2-K-L	Bad	1	6	Not compatible >4.
		ay Skye	SAL06P-W-K-L		1	6	

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	Description
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (HE) Dead Travel Low End (LE) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.

©2025 Bulbrite Industries Inc.

All Rights Reserved.