



Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name:
Item Number: 776834
Ordering Code: LED2G16/27K/FIL/HB/3
Item Number:
Ordering Code:

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	a IllumaTech	IPI06	Bad	4	6	Not smooth, flickers with <4, brightens when dimming <3
		b SureSlide	6633-P	Bad	2	6	30% brightness with 1, flickers with 1
		c Vizia	VPI06-1LZ	Good	2	6	75% brightness with 1
		d Toggler	TG-600	Best	1	6	
	Lutron	e Lumea	LGCL-600	Good	1	6	80% brightness
		f Diva	DV-600	Best	1	6	
		g Skylark	S-600	Best	1	6	
		h Maestro	MAW-600	Not Compatible	5	6	Flickers heavily <5, dims when brightening 90%-100% with 5/6
	Legrand	i Titan	CD703-PW	Not Compatible	5	6	50% MAX with 2-4, 10% MAX with 1
		j Harmony	D703-PTC	Not Compatible	5	6	70% MAX with 2-4, 10% MAX with 1
		k Harmony	H703-PTC	Not Compatible	5	6	80% MAX with 2-4, 10% MAX with 1
CFL/LED	Leviton	l IllumaTech	IPL06	Good	1	6	HE dead travel 10%, fully extinguished by 20%
		m Sureslide	6674	Good	1	6	HE dead travel 25%
		n Decora	6672	Good	1	6	HE dead travel 10%
		o Decora Slide	DSL06-1LZ	Best	1	6	
	Lutron	p Skylark	CTCL-153	Best	1	6	
		q Diva	DVCL-153PL	Best	1	6	
		r Maestro	MACL-153MLH	Good	1	6	90% MAX <4
		s Skylark	SCL-153P	Good	1	6	90% MAX <4
	Legrand	t Toggler	TGCL-153PH	Good	1	6	90% MAX <4
		u Radio RA	RA2RR-6CL-PD	Best	1	6	
		v Harmony	DCL453-PW	Bad	2	6	40% MAX with <2
		w Harmony	HCL453PTC	Best	1	6	
Electronic Low Voltage	Leviton	y Vizia	YPE04	Best	1	6	
		z IllumaTech	IPE04	Not Compatible		6	Not smooth, at all, dims when brightening with all quantities
		aa Decora	6615-P	Not Compatible		6	Not smooth, at all, dims when brightening with all quantities
		ab Skylark Countour	CTELV-303P	Best	1	6	
	Lutron	ac Diva	DVELV-300P	Best	1	6	
		ad Maestro	MAELV-600	Best	1	6	
		ae Skylark	SELVB-300P	Good	1	6	Lag in operation
		af VIER TI	VTEL-600M-W	Best	1	6	
	Legrand	ag Scene Director	SCELV	Best	1	6	
Magnetic Low Voltage	Leviton	ah Vizia	VPM-06	Bad	2	6	80% MAX with 1, not smooth
	Lutron	ai Decora	6613-P	Bad	4	6	80% MAX with <4
		aj Maestro	MALV-600	Not Compatible		6	
	Legrand	ak Harmony	DLV703-PW	Bad	2	6	25% MAX with 1
		al Titan	CDLV703-PW	Bad	2	6	25% MAX with 1
Smart Dimmer	Leviton	am Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	
	Leviton	an Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	
	Leviton	ao Decora Smart WiFi Technology	DW1KD	Best	1	6	
	Lutron	ap Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	Dims to 2%
	Lutron	aq Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims to 2%
	GE	ar Z WAVE	ZW3005	Best	1	6	
Universal	Legrand	as Adorne SoftTap	ADTP703TU	Not Compatible	2	6	Not compatible with 1
		at Miro Decorator	DRD4-W	Not Compatible	2	6	Not compatible with 1
		au Harmony	H703PTUTC	Not Compatible	2	6	Not compatible with 1, dims to 30% with 2-6
		av Adorne Whisper	ADWR700MMTUW2	Best	1	6	
		aw Adorne Touch	ADTH700MMTUW2	Best	1	6	
	Cooper	ax Decorator	DAL06P-C2-K-L	Not Compatible	4	6	Not compatible with <4
		ay Skye	SAL06P-W-K-L			6	

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	Description
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (HE) Dead Travel Low End (LE) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.

© 2025 Bulbrite Industries Inc.

All Rights Reserved.