

## **Dimmer Compatibility Guide**

Tested Unit Item Number: 776322
Tested Unit Ordering Code: LED4C53/30K/FIL/GRAD/BLU
Related Item Number: 776321
Related Ordering Code: LED4C53/30K/FIL/GRAD/SMK

				Model Number	Overall Rating	Lamps per l		Notes
	Manufacturer		Product			Recommended	Maximum	
						Minimum	Tested*	
ncandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	а	IllumaTech	IPI06	Good	1	6	Flickers while dimming, dims completely
			SureSlide	6633-P	Best	1	6	Dims completely
		С	Vizia	VPI06-1LZ	Not Compatible	2	6	Not compatible with 1
	Lutron		Toggler	TG-600	Best	1	6	Dims completely
		е	Lumea	LGCL-600	Best	1	6	Dims completely
			Diva	DV-600	Best	1	6	Dims completely
			Skylark	S-600	Best	1	6	Dims completely
		h	Maestro	MAW-600	Not Compatible		6	
	Legrand	i	Titan	CD703-PW	Best	1	6	Dims completely
			Harmony	D703-PTC	Good	1	6	Not smooth, dims completely
		k	Harmony	H703-PTC	Best	1	6	Dims completely
			IlliumaTech	IPL06	Best	1	6	Dims completely
CFL/LED	Leviton		Sureslide	6674	Best	1	6	Dims completely
			Decora	6672	Best	1	6	Dims completely
			Decora Slide	DSL06-1LZ	Best	1	6	Dims completely
	Lutron		Skylark	CTCL-153	Best	1	6	Dims completely
			Diva	DVCL-153PL	Best	1	6	Dims completely
			Maestro	MACL-153MLH	Best	1	6	Dims completely
			Skylark	SCL-153P	Best	1	6	Dims completely
			Toggler	TGCL-153PH	Best	1	6	Dims completely
			Radio RA	RA2RR-6CL-PD	Best	1	6	Dims completely
	Legrand		Harmony	DCL453-PTC	Best	1	6	Dims completely
			Harmony	HCL453PTC	Best	1	6	Dims completely
			Adorne Paddle	ADPD453LM2	Best	1	6	Dims to 6%
			•	•				
Electronic Low Voltage	Leviton		Vizia	VPE04	Best	1	6	Dims completely
			IllumaTech	IPE04	Not Compatible		6	
			Decora	6615-P	Not Compatible		6	
	Lutron		Skylark Countour	CTELV-303P	Best	1	6	Dims completely
			Diva	DVELV-300P	Best	1	6	Dims completely
			Maestro	MAELV-600	Best	1	6	Dims completely
			Skylark	SELVB-300P	Best	1	6	Dims completely
			f VIERTI	VTEL-600M-W	Best	1	6	Dims completely
	Legrand	a	Scene Director	SCELV	Best	1	6	Dims completely
Magnetic Low Voltage	Leviton		Vizia	VPM-06	Best	1	6	Dims completely
			Decora	6613-P	Best	1	6	Dims completely
	Lutron		Maestro	MALV-600	Not Compatible		6	
	Legrand		Harmony	DLV703-PW	Good	1	6	Very slight flicker while dimming, dims completely
		а	Titan	CDLV703-PW	Not Compatible		6	
Smart Dimmer	Leviton	or	Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	Dims completely
	Leviton		Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	Dims completely
		_						
	Leviton		Decora Smart WiFi Technology	DW1KD	Best	1	6	Dims completely
	Lutron	a	Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	Dims to 6%
	Lutron	a	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims to 4%
	GE	а	Z WAVE	ZW3005	Best	1	6	Dims completely
				•				,
Universal	Legrand	_	Adorne SofTap	ADTP703TU	Not Compatible		6	
			Miro Decorator	DRD4-W	Best	1	6	Dims completely
			Harmony	H703PTUTC	Not Compatible		6	
			Adorne Whisper	ADWR700MMTUW2		1	6	Dims completely
		av	Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims completely
	Cooper		lo i	DALOOD OO 1/ 1	NI LO CLI		6	
	Cooner	a	Decorator	DAL06P-C2-K-L	Not Compatible		0	

\*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.
†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Description						
One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.						
One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.						
One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.						
Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.						
Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.						

©2025 Bulbrite Industries Inc.