ACROBAT" 160

63MM - 160MM (2" - 6")

MADE FOR

MECHANICAL HVAC PLUMBING





STANDARD FEATURES

- Small footprint, lightweight
- Tool-less conversion from 4-jaw to 3-jaw carriage for tight work spaces
- Narrow jaws allow fusions for flanges to outlet branch of tees and most fittings
- Single insert design
- Removable upper jaws
- Hard anodized aluminum wear surfaces for corrosion resistance
- Low-power consumption
- DataLogger * compatible
- Premium shipping container serves as work surface
- Open-frame HPU design offers easy access for maintenance
- Microprocessor-controlled heater with antistick, Teflon-coated butt plates







The Acrobat 160 is a low-force fusion machine that allows operators to butt fuse pipe in tight work spaces. With its small footprint and optimal weight, it is an easy machine to manipulate when performing overhead fusions in tight spaces as well as on the ground.

For even tighter spaces, the Acrobat 160 can be configured from 4 jaws to 3 jaws without using tools. It also comes with a Hydraulic Power Unit (HPU) and inserts for commonly butt-fused polypropylene pipe sizes. The facer and heater can be loaded from the top or bottom (in the 3-jaw configuration) of the carriage giving the operator better access and flexibility regardless of the joining challenge.

ADDITIONAL IMAGES













SEE SECOND PAGE FOR DETAILED SPECIFICATIONS

Copyright © 2024 McElroy Manufacturing, Inc. The contents of this specification page are for informational use only and subject to change without notice. All trademarks are property of McElroy Manufacturing, Inc. unless otherwise noted. All Rights Reserved. 09/06/2024



ACROBAT 160

63MM - 160MM (2" - 6")

SPECIFICATIONS

MODELS		POWER		CARRIAGE DIMENSIONS	
A714501	Low Force, 120V	120V Heater	100-120V, 1,200 Watts, 50 / 60 Hz, 1 Ph	Length	4-Jaw - 23.5" (596.9mm) 3-Jaw - 19" (482.6mm)
A714502 WEIGHTS	Low Force, 240V	240V Heater	220-240V, 1,200 Watts, 50 Hz, 1 Ph	Width	4-Jaw - 15" (381mm) 3-Jaw - 15" (381mm)
Carriage	4-Jaw - 40 lbs. (18.1 Kg) 3-Jaw - 29 lbs. (13.2 Kg)	120V Facer	100-120V, 50 / 60 Hz, 1 Ph, 5 Amps	Height	4-Jaw - 14" (355.6mm) 3-Jaw - 12" (304.8mm)
Heater	14 lbs. (6.4 Kg)	240V Facer	220-240V, 50 / 60 Hz, 1 Ph, 7 Amps	SHIPPING DIMENSIONS	
Facer	35 lbs. (15.9 Kg)	240V Heater	·	Length 32" (812.8 mm)	
Shipping Weight	390 lbs. (176.9 Kg)	Plug type	CEE 7/7 (DIN 49441)	Width	45" (1,143 mm)
		120V Heater Plug type	NEMA 5-15P	Height	31" (787.4 mm)
		240V Facer Plug	CEE 7/7 (DIN 49441)	Fusion machine, facer, heater, insulated heater stand, facer stand, EP800AD HPU (Hydraulic Power Unit), 125mm inserts and shipping container.	
		120V Facer Plug	NEMA 5-15P		
		type		12311111 1113613	s and shipping container.
		MACHINE DIMENSIONS			
		Machine Length	23.5" (596.9mm)		
		Machine Width	15" (381mm)		
		Machine Height	14" (355.6mm)		