HP Everyday Adhesive Matte Polypropylene, 2 Pack





The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



High-quality prints for your day-to-day production

Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

Gain efficiency

Help keep your production process moving smoothly. This easy-to-use film features a permanent self-adhesive for secure, reliable mounting.

Make the versatility of this material work for you

ICC profiles help you get the right color right away. Take advantage of compatibility with Original HP pigment- and dye-based inks on this versatile, easy-to-use printing material.

Target customers	Applications	Benefits
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production
Retail store in-house printing	Trade show and event displays	A permanent self-adhesive for secure, reliable mounting
Event designers	Temporary exhibitions	Compatible with Original HP pigment- and dye- based inks for HP DesignJet printers
Advertising agencies	Architecture competitions	
Geographic Information Systems (GIS)		
Government (printing se adhesive maps)	lf-	

Technical specifications



HP Everyday Adhesive Matte Polypropylene, 2 Pack

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/paperpresets.

Ink compatibility	Original HP pigment- and dye-based inks for HP DesignJet printers						
Weight (without liner)	106 g/m² per ISO 536 Test Method						
Weight (with liner)	185 g/m²per ISO 536 Test Method						
Thickness (without liner)	162 microns/6.4 mil per ISO 534 Test Method						
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method						
Opacity (with liner)	>96% per TAPPI T-425 and ISO 2471 Test Methods						
Brightness (with liner)	>105 per ISO 2470 Test Method						
Whiteness (with liner)	>135 per ISO 11475 Test Method						
Finish	Matte						
Operating temperature	15 to 30° C / 59 to 86° F						
Operating humidity	20 to 60% RH						
Environmental	REACH compliant ¹						
Lamination	Cold lamination. Can be laminated with most commercially available cold laminate films.2						
Shelf life	1 year, unopened in original packaging						
Storage temperature	15 to 35° C / 59 to 95° F						
Storage humidity	20 to 70% RH						
Country of origin	Product of China and Malaysia						
Ordering information	Product numbers (Quantity	Roll sizes	UPC Codes	Region		
	C0F18A 2	2 Pack	610 mm x 22,9 m (24 in x75 ft)	848412012934	Worldwide		
	C0F19A 2	2 Pack	914 mm x 22,9 m (36 in x75 ft)	848412012941	Worldwide		
	C0F20A 2	2 Pack	1067 mm x 22,9 m (42 in x 75 ft)	848412012958	Worldwide		
	C0F22A 2	2 Pack	1524 mm x 22,9 m (60 in x 75 ft)	848412012965	Worldwide		
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <u>HPLFMedia.com/hp/MediaWarranties</u> . To obtain warranty service, please contact Br Management Group customer support at <u>HPLFMedia.com/hp/en/contactus</u> .						

¹ See the HP REACH Declaration published at <u>HP Printing Products and Consumable Supplies</u>.

For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2025 HP Development Company, L.P. © 2025 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.



² Based on testing HP media printed with Original HP inks using a 3-mil vinyl film laminate that contains a water-based acrylic pressure-sensitive adhesive and a 3-mil vinyl film laminate that contains a solvent acrylic pressure-sensitive adhesive—the formulations of which HP believes represent the majority of cold film laminates that are commercially available based on historical testing. Films without the above-mentioned formulations may not be compatible.