




HP Light Fabric



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Produce brilliant, high-impact displays with this competitively priced, wrinkle-resistant light textile

Find new profit potential with this reasonably priced light fabric

Create high-impact displays and banners for events and retail POP. This economically priced polyester fabric produces brilliant prints that resist creases and wrinkles. Offer custom work and optimize the cost advantages of this easy-to-use, knitted polyester fabric. And discover new profit potential with this versatile, lightweight textile.

REACH compliant¹

Differentiate your offering with a compelling alternative to PVC for banners and displays. This flame-resistant² light fabric is REACH compliant¹—a regulation of the European Union adopted to improve the protection of human health and the environment from risks that can be posed by chemicals.

See excellent ink saturation for vibrant image quality

Deliver crisp image quality and bright colors with the wide color gamut produced by HP Latex Inks.

Target customers	Applications	Benefits
Print service providers	Trade show and event displays	Wide color gamut
	POP/POS and retail displays	Wrinkle and crease resistant
	Banners	An alternative to PVC for banners and displays
	Interior decorations	Flame resistant ²
	Pop-up/roll-up displays	Rub- and scratch-resistant prints ³

Technical specifications



HP Light Fabric
For the latest ICC/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink compatibility	Original HP Latex Inks for HP Latex printers			
Weight	220 g/m² per ISO 536 Test Method, (6.2 oz)			
Thickness	398 microns/15.7 mil per ISO 534 Test Method			
Tensile strength	MD > 400 N/25 mm / CD > 1100 N/25 mm per ASTM D 882-02			
Finish	Matte			
Opacity	>79% per TAPPI T-425 Test Method			
Brightness	92 per TAPPI T-452 Test Method			
Whiteness	138 per ISO 11475 Test Method			
Water resistance	Water resistant with HP Latex Inks ⁴			
Wind orientation	Image side in			
Finishing	Recommend cutting with a hot knife			
Operating temperature	15 to 35° C / 59 to 95° F			
Operating humidity	30 to 80% RH			
Flame resistance	B1, M1, and NFPA701 approved fire certifications ²			
Dry time	Instant dry			
Shelf life	1 year, unopened in original packaging			
Storage temperature	5 to 40° C / 41 to 104° F			
Storage humidity	5 to 95% RH			
Environmental	REACH compliant ¹			
Country of origin	Product of Germany			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	J7U83A	1067 mm x 45,7 m (42 in x 150 ft)	848412015065	Worldwide
	J7U84A	1372 mm x 45,7 m (54 in x 150 ft)	848412015072	Worldwide
	J7U85A	1524 mm x 45,7 m (60 in x 150 ft)	848412015089	Worldwide
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact BMG customer support.			

¹ See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).

² B1, M1, and NFPA701 approved fire certifications.

³ Rub resistance testing by HP Image Permanence Lab according to ASTM F1319.

⁴ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.

⁵ It is necessary to use the take-up reel with the HP Latex 210 and platen cover (B2W90A) with the HP Latex 210, 260 and 280 Printers. The platen cover is included with the HP Latex 360 Printer.

For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

