**HP Removable Adhesive Fabric** 



## The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising inage quality, reliability, and consistency-with every print.



# Print high-quality, repositionable graphics that stick to non-porous surfaces

#### Easy-to-install, reposition, and remove

Enjoy the ease of working with this repositionable adhesive-back fabric that is easy to install, reposition, and remove with virtually no residue. The special adhesive is designed to stick to non-porous surfaces to create seamless, photographic image quality wall and floor graphics. Tested and approved for indoor smooth floor graphics.<sup>1</sup>

#### REACH compliant<sup>2</sup>

Offer an adhesive fabric that complies with high health standards. Help meet environmental and safety objectives with this flame-resistant,<sup>3</sup> adhesive fabric. HP Removable Adhesive Fabric is REACH compliant<sup>2</sup>—a regulation of the European Union adopted to improve the protection of human health and the environment from risks that can be posed by chemicals.

#### Grab attention with vibrant image quality for a variety of applications

Capture realistic graphic detail for applications from wall murals and event signage to retail displays. Achieve a high-quality look with this versatile, easy-to-handle, repositionable self-adhesive fabric—ideal for a wide range of indoor and outdoor applications.

Target customers	Applications	Benefits	
Print service providers	Wall murals	Designed for easy installation, repositioning, and removal without wrinkles or tearing for a wide range of applications	
Government agencies	Wall cut-outs	Ability to contour cut and apply without stretching	
Graphic artists	Indoor and short-term outdoor signage	Smooth, matte finish for deep blacks, vivid colors, and high ink saturation	
Sign shops	Point-of-purchase displays	Outstanding photographic image quality	
Retail	Trade show graphics	Class A, ASTM E84 flame resistance <sup>3</sup>	
	Decals	Compatible with Original HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL and HP Latex Inks	
	Window graphics	Slip resistant for floor graphics1	
	Floor graphics		



#### **HP Removable Adhesive Fabric**

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets

### **Technical specifications**

Ink compatibility	HP Bright Off	ice Inks, HP Vivid Photo Inks, HP Page\	Wide and HP Latex Ir	nks		
Material	Polyester fab	<del>-</del>				
Weight (With liner)	289 g/m² per ISO 536 Test Method					
Thickness (With liner)	304 microns/12 mil per ISO 20534 Test Method					
Liner	120 g/m², double-sided PE-coated silicone paper					
Adhesive	Clear, removable, and repositionable adhesive					
Removability	Up to 3 years removable/repositionable indoors					
Opacity	>85% per TAPPI T-425 Test Method and ISO 2471 Test Method					
Brightness	>87 per TAPPI T-452 Test Method					
Whiteness	118 per ASTM E313-98 Test Method					
Finish	Matte					
Slip rating	Certified according to <u>ANSI A1371/A326.3 and AS HB198:2014 (AS/NZS 4586)</u> 1					
Operating temperature	15 to 25° C / 59 to 77° F					
Operating humidity	20 to 80% RH					
Water resistance	Moderately water-resistant <sup>4</sup>					
Wind orientation	Print side out					
Core size	3-in core with a removable 2-in core adapter					
Dry time	Immediate					
Flame resistance	Class A, ASTM E84 approved fire certifications³					
Lamination	For additional protection, liquid or spray coatings are recommended					
PageWide Cutter	The weight of this material is higher than the recommended weight limit for the HP PageWide XL cutter, which may reduce the expected life of the cutter					
Shelf life	1 year, unopened in original packaging					
Storage temperature	10 to 27° C / 50 to 80° F					
Storage humidity	35 to 65% RH					
Environmental	REACH compliant <sup>2</sup>					
Finishing/post processing	Use a carbide knife for kiss and die cutting					
Installation tip	To install the graphic, peel 101 millimeters (4 inches) of the release liner off the graphic and place on wall or surface. Continue to peel back 101 millimeters (4 inches) of the liner incrementally while mounting.					
Country of origin	Product of China					
Ordering information	Product numl	oers Roll sizes	UPC codes	Region		
	8SU04A	610 mm x 30,5 m (24 in x 100 ft)	848412025675	United States, Europe		
	8SU05A	914 mm x 30,5 m (36 in x 100 ft)	848412025682	United States, Europe		
	8SU06A	1067 mm x 30,5 m (42 in x 100 ft)	848412025699	United States, Europe		
	8SU08A	1372 mm x 30,5 m (54 in x 100 ft)	848412025729	United States, Europe		
	8SU09A	1524 mm x 30,5 m (60 in x 100 ft)	848412025736	United States, Europe		
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <a href="https://en/mediawarranties">https://en/mediawarranties</a> . To obtain warranty service, please contact BMG customer support at <a href="https://en/contactus">https://en/contactus</a> .					

Recommended on indoor smooth, non-porous, sealed flat and dry surfaces for up 3 months. Slip resistance for dry environments based on testing by Sotter Engineering Corporation, June 2020, according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586).

#### For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2023 HP Development Company, L.P. © 2023 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.



HP is a registered trademark of HP Development Company, LP. and is used by Brand Management Group under license from HP Development Company, LP.

<sup>&</sup>lt;sup>2</sup> See HP REACH Declaration published at <u>HP Printing Products and Consumable Supplies</u>.

<sup>&</sup>lt;sup>3</sup> Class A, ASTM E84 approved fire certifications.

Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLEMedia.com/hp/print permanence.