

SFP-25GB-DW-C-15-DE-AO

Dell® Compatible TAA 10/25GBase-DWDM SFP28 Transceiver Dual-Rate 100GHz (SMF, Tunable, 15km, LC, DOM)

Features

- Operating Data Rate: 9.8 to 25.78Gbps
- C-Band 100GHz Tunable Tx(MZM-DBR)/Rx(APD)
- Compliant with SFF-8402 and SFF-8690
- Supports ASP (Automated Self-Pairing) Functions
- Supports ROD (Remote DDM) Functions
- Supports Optical and Electrical Loopback Functions
- Hot-Pluggable Electrical Interface
- Class 1 Laser Safety
- Operating Temperature: 0 to 70 Celsius
- Single 3.3V Power Supply
- RoHS Compliant and Lead-Free



Applications

- 25GBase
- Access, Metro and Enterprise

Product Description

This Dell® compatible dual-rate SFP28 transceiver provides 10/25GBase-DWDM throughput up to 15km over single-mode fiber (SMF) using a tunable wavelength via an LC connector. Our transceiver is built to meet or exceed OEM specifications and is guaranteed to be 100% compatible with Dell®. It has been programmed, uniquely serialized, and tested for data-traffic and application to ensure that it will initialize and perform identically. All of our transceivers comply with Multi-Source Agreement (MSA) standards to provide seamless network integration. Additional product features include Digital Optical Monitoring (DOM) support which allows access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

AddOn's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."



ITU Channel Wavelength Guide

ITU Channel	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Frequency (THz)	Center Wavelength (nm)
14	191.40	1566.31	38	193.80	1546.92
15	191.50	1565.50	39	193.90	1546.12
16	191.60	1564.68	40	194.00	1545.32
17	191.70	1563.86	41	194.10	1544.53
18	191.80	1563.05	42	194.20	1543.73
19	191.90	1562.23	43	194.30	1542.94
20	192.00	1561.42	44	194.40	1542.14
21	192.10	1560.61	45	194.50	1541.35
22	192.20	1559.79	46	194.60	1540.56
23	192.30	1558.98	47	194.70	1539.77
24	192.40	1558.17	48	194.80	1538.98
25	192.50	1557.36	49	194.90	1538.19
26	192.60	1556.56	50	195.00	1537.40
27	192.70	1555.75	51	195.10	1536.61
28	192.80	1554.94	52	195.20	1535.82
29	192.90	1554.13	53	195.30	1535.04
30	193.00	1553.33	54	195.40	1534.25
31	193.10	1552.52	55	195.50	1533.47
32	193.20	1551.72	56	195.60	1532.68
33	193.30	1550.92	57	195.70	1531.90
34	193.40	1550.12	58	195.80	1531.12
35	193.50	1549.32	59	195.90	1530.33
36	193.60	1548.52	60	196.00	1529.55
37	193.70	1547.72	61	196.10	1528.77

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Relative Humidity (Non-Condensing)	%	5		95		
Operating Case Temperature	Tc	0		70	°C	
Storage Temperature	Tstg	-40		85	°C	
Supply Voltage	V	0		4		
Data Rate	DR ₂₅	24.3		25.78	Gbps	1
	DR ₁₀	9.8	10.3	12.5		2

Notes :

1. RS high logic.
2. RS low logic.

Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage		3.135	3.3	3.465	Vcc	
Power Dissipation	PC			3.5	W	@3.3V
Power Supply Noise Tolerance	PSNT			66	mVp-p	1
Transmitter						
Differential Input Voltage	VIN	190		700	mV	AC coupled
Differential Input Impedance	ZIN	90	100	110	Ω	
Tx_Disable	Input Low	VIL	-0.3		0.8	V
	Input High	VIH	2.0		Vcc+0.3	V
	Assert Time	tOFF			100	us
	Negate Time	tON			2.0	ms
Tx_Disable to Start Reset	treset	10			us	High
Time to Initialize	tInit			90	s	3
Tx_Fault	Output Low	VFOL	-0.3		0.4	V
	Output High	IFOH	-50		37.5	μ A
RS1 (Rate Select for Tx)		VIL	-0.3		0.8	V
		VIH	2.0		Vcc+0.3	V
Receiver						
Differential Output Voltage	VOUT	300		850	mV	AC coupled
Differential Output Impedance	ZOUT	90	100	110	Ω	
Rx_LOS (Loss of Signal)	Output Low	VLOSL	-0.3		0.4	V
	Output High	ILOSH	-50		37.5	μ A
	Assert time	tLOS-ON			100	us
	De-Assert time	tLOS-OFF			100	us
RS0 (Rate Select for Rx)		VIL	-0.3		0.8	V
		VIH	2		Vcc+0.3	V

Notes:

1. From 10Hz to 10MHz.
2. LVTTL, normal at low, high is shutdown (Poff).
3. Including reset of Tx_Fault.

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes	
Transmitter							
Average Launch Power	Pavg	-1.0		3.0	dBm		
Optical Power Flatness	ΔPO	-1.0		1.0	dB	All channels	
Transmitter Disabled Power	Poff			-30	dBm	1	
Optical Center Wavelength	λC	1528.77		1566.31	nm	2	
Optical Center Frequency	FfC	191.40		196.10	THz	2	
Center Wavelength Spacing			100		GHz	2	
Wavelength Stability	Beginning of Life	λp_BOL	-1.7	λC	1.7	GHz	3
	End of Life	λp_EOL	-2.5	λC	2.5	GHz	3
Wavelength Tuning Speed	TTUNE			30	ms	4	
Spectral Width				0.5	nm	@-20dB	
Side-Mode Suppression Ratio	SMSR	30			dB		
Extinction Ratio	ER	8.0			dB	PRBS2 ³¹ -1	
Relative Intensity Noise	RIN ₂₀ OMA			-130.0	dB/Hz		
Optical Return Loss tolerance	ORL			20.0	dB		
Transmitter Reflectance				-26.0	dB		
Optical Eye Mask		IEEE802.3cc 114.6 25GBASE-LR/ER {X1,X2,X3,Y1,Y2,Y3} = {0.31,0.40,0.45,0.34,0.38,0.40}				Hit ratio 5E ⁻⁵	
Receiver							
Optical Sensitivity	25.78Gbps or 24.33Gbps	S1			-19.0		5
	10.7Gbps, 10.3Gbps, 9.8Gbps	S2			-19.0		6
	11.3Gbps to 11.1Gbps	S3			-19.0		7
Optical Overload		OL	-4.0			dBm	8
Operating wavelength		λo	1525		1575	nm	
Rx_LOS (Loss of Signal)	Assert	LOSA	-30.0			dBm	9
	De-Assert	LOSD			-23.0	dBm	
	Hysteresis	LOSH	0.5		5.0	dB	
Return Loss of Receiver					-26.0	dB	
RSSI Calibration		RCAL	Internally Calibrated (The host side can be read by an external way)				
Auxiliary Management and Control Channel							
Bit Rate		BR _{AMCC}		1200		Gbps	
Modulation Depth		AMCC _{MD}	5		10	%	
Dynamic Range		DR _{AMCC}	-4		-24	dBm	10

Notes:


1. @Tx Disable is high.

2. ITU-T 694.1 grid wavelength.
3. λ C=ITU grid wavelength.
4. From any channel to and other channel. ASP disable.
5. PRBS2³¹, BER 5x10⁻⁵, source ER=8.0dB, SMF 15km, G652.
6. PRBS2³¹, BER 5x10⁻¹², source ER=8.0dB, SMF 15km, G652.
7. PRBS2³¹, BER 5x10⁻⁴, source ER=8.0dB, SMF 15km, G652.
8. PRBS2³¹, source ER=8.0dB.
9. Rx squelch activated.
10. AMCC_{MD}: 5%, 1200bps.


Pin Descriptions

Pin	Symbol	Name/Description	Plug Seq.	Notes
1	VeeT	Transmitter Ground.	1	
2	Tx_Fault	Transmitter Fault Status Output.	3	
3	Tx_Disable	Transmitter Disable Control Input.	3	
4	SDA	I ² C Data (Input/Output).	3	
5	SCL	I ² C Clock (Input/Output).	3	
6	MOD_ABS	Indicates that the module is present. Grounded internally.	3	
7	RS0	Rate Select 0. Internally pulled down. 51kΩ.	3	
8	Rx_LOS	Receiver Loss of Signal Status Output.	3	
9	RS1	Rate Select 1. Internally pulled down. 51kΩ.	3	
10	VeeR	Receiver Ground.	1	
11	VeeR	Receiver Ground.	1	
12	RD-	Receiver Inverted Data Output.	3	
13	RD+	Receiver Non-Inverted Data Output.	3	
14	VeeR	Receiver Ground.	1	
15	VccR	Receiver 3.3V Power Supply.	2	
16	VccT	Transmitter 3.3V Power Supply.	2	
17	VeeT	Transmitter Ground.	1	
18	TD+	Transmitter Non-Inverted Data Input.	3	
19	TD-	Transmitter Inverted Data Input.	3	
20	VeeT	Transmitter Ground.	1	


Pin-Out Details



Recommended Interface Circuit



Mechanical Specifications



About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is engrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications from ranging from NEBS Level 3 to ISO 9001:2005 with every new development while maintaining the signature reliability of its products.



U.S. Headquarters

Email: sales@addonnetworks.com

Telephone: +1 877.292.1701

Fax: 949.266.9273

Europe Headquarters

Email: salesupportemea@addonnetworks.com

Telephone: +44 1285 842070