

MCA4J80-N003-FTF-AO

Mellanox® MCA4J80-N003-FTF Compatible TAA 800GBase-CU OSFP to OSFP-RHS Direct Attach Cable (Active Twinax, 3m)

Features:

- OSFP MSA Compliant
- Transmission Data Rate Up to PAM4 106.25Gbps Per Channel
- InfiniBand NDR Compatible
- Linear PAM4 Programmable Equalizer Optimized for 56GBaud
- Enabled Auto-Negotiation and Link Training
- Low Power Consumption
- Supports Device Programming by MCU with I2C
- Low Latency:
- Operating Temperature: 0 to 70 Celsius
- 3.3V Power Supply
- RoHS Compliant and Lead-Free



Applications:

- 800GBase InfiniBand

Product Description

This Mellanox® MCA4J80-N003-FTF compatible 800GBase-CU OSFP to OSFP-RHS direct attach cable that operates over active copper with a maximum reach of 3.0m (9.8ft). It has been programmed, uniquely serialized, and data-traffic and application tested to ensure it is 100% compliant and functional. This direct attach cable is TAA (Trade Agreements Act) compliant, and is built to comply with MSA (Multi-Source Agreement) standards. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

AddOn's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."



Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	Vcc	-0.3	3.3	3.6	V
Storage Temperature	Tstg	-40		85	°C
Operating Case Temperature	Tc	0		70	°C
Humidity	RH	5		85	%
Data Rate	DR		800		Gbps

Physical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Length	L			3	M
AWG			28		AWG
Jacket Material	Plastic Braided Mesh Technology Net				

Electrical Specifications

Parameter	Symbol	Min.	Typ.	Max.	Unit
Power Supply Voltage	Vcc	3.1	3.3	3.5	V
Input Amplitude		800		1200	mVpp
Input Low Voltage	VIL	-0.3		0.35*Vcc	V
Input High Voltage	VIH	0.65*Vcc		Vcc+0.3	V
Output Logic Low	VOL			0.25*Vcc	V
I ² C Master-Mode Output Frequency			400		kHz
800G End Power Consumption			1.2	1.5	W

High-Speed Specifications

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Raw Cable Impedance	Zca	90	100	110	Ω	
Mated Connector Impedance	Zmated	85		115	Ω	
Maximum Insertion Loss @26.56GHz	SDD21	11		19.75	dB	
Differential- to Common-Mode Return Loss	SCD11/22	$RL_{cd}(f) \geq \begin{cases} 22 - 10(f/26.56) & 0.05 \leq f < 26.56 \\ 15 - 3(f/26.56) & 26.56 \leq f \leq 40 \end{cases}$			dB	1
Differential to Common-Mode Conversion Loss	SCD21-SDD21	$Conversion_loss(f) - \begin{cases} 10 & 0.05 \leq f < 12.89 \\ 14 - 0.3108f & 12.89 \leq f \leq 40 \end{cases}$			dB	1
Common-Mode to Common-Mode Return Loss	SCC11/22	$RL_{cc}(f) \geq 1.8$			dB	1
Minimum COM	COM	3			dB	
Minimum Cable Assembly ERL	ERL	8.25			dB	
BER				2.4×10^{-4}		

Notes:

1. For $0.05 \leq f \leq 40$ GHz, where f is the frequency in GHz.

Pin Descriptions


Pin	Symbol	Name/Description	Logic	Plug Sequence	Direction	Notes
1	GND	Module Ground.		1		
2	TX2p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
3	TX2n	Transmitter Data Inverted.	CML-I	3	Input from Host	
4	GND	Module Ground.		1		
5	TX4p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
6	TX4n	Transmitter Data Inverted.	CML-I	3	Input from Host	
7	GND	Module Ground.		1		
8	TX6p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
9	TX6n	Transmitter Data Inverted.	CML-I	3	Input from Host	
10	GND	Module Ground.		1		
11	TX8p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
12	TX8n	Transmitter Data Inverted.	CML-I	3	Input from Host	
13	GND	Module Ground.		1		
14	SCL	2-Wire Serial Interface Clock.	LVCMOS-I/O	3	Bi-Directional	1
15	Vcc	+3.3V Power.		2	Power from Host	
16	Vcc	+3.3V Power.		2	Power from Host	
17	LPWn/PRSn	Low-Power Mode/Module Present.	Multi-Level	3	Bi-Directional	2
18	GND	Module Ground.		1		
19	RX7n	Receiver Data Inverted.	CML-O	3	Output to Host	
20	RX7p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
21	GND	Module Ground.		1		
22	RX5n	Receiver Data Inverted.	CML-O	3	Output to Host	
23	RX5p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
24	GND	Module Ground.		1		
25	RX3n	Receiver Data Inverted.	CML-O	3	Output to Host	
26	RX3p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
27	GND	Module Ground.		1		
28	RX1n	Receiver Data Inverted.	CML-O	3	Output to Host	
29	RX1p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
30	GND	Module Ground.		1		
31	GND	Module Ground.		1		
32	RX2p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
33	RX2n	Receiver Data Inverted.	CML-O	3	Output to Host	
34	GND	Module Ground.		1		
35	RX4p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	

36	RX4n	Receiver Data Inverted.	CML-O	3	Output to Host	
37	GND	Module Ground.		1		
38	RX6p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
39	RX6n	Receiver Data Inverted.	CML-O	3	Output to Host	
40	GND	Module Ground.		1		
41	RX8p	Receiver Data Non-Inverted.	CML-O	3	Output to Host	
42	RX8n	Receiver Data Inverted.	CML-O	3	Output to Host	
43	GND	Module Ground.		1		
44	INT/RSTn	Module Interrupt/Module Reset.	Multi-Level	3	Bi-Directional	2
45	Vcc	+3.3V Power.		2	Power from Host	
46	Vcc	+3.3V Power.		2	Power from Host	
47	SDA	2-Wire Serial Interface Data.	LVCMOS-I/O	3	Bi-Directional	1
48	GND	Module Ground.		1		
49	TX7n	Transmitter Data Inverted.	CML-I	3	Input from Host	
50	TX7p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
51	GND	Module Ground.		1		
52	TX5n	Transmitter Data Inverted.	CML-I	3	Input from Host	
53	TX5p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
54	GND	Module Ground.		1		
55	TX3n	Transmitter Data Inverted.	CML-I	3	Input from Host	
56	TX3p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
57	GND	Module Ground.		1		
58	TX1n	Transmitter Data Inverted.	CML-I	3	Input from Host	
59	TX1p	Transmitter Data Non-Inverted.	CML-I	3	Input from Host	
60	GND	Module Ground.		1		


Notes:

1. Open-drain with pull-up resistor on the host.
2. See “Pin Assignments” below.

Pin Assignments



Mechanical Specifications



Bending Radius

Wire Gauge	OSFP Type 2			OSFP-RHS		
	OD (Ref.)	Bend Radius "R"	Min. Bend Radius "L"	OD (Ref.)	Bend Radius "R"	Min. Bend Radius "L"
28AWG	10.2mm	21mm	81mm	10.2mm	21mm	65mm

About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is ingrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications ranging from NEBS Level 3 to ISO 9001:2015 with every new development while maintaining the signature reliability of its products.



U.S. Headquarters

Email: sales@addonnetworks.com

Telephone: +1 877.292.1701

Fax: 949.266.9273

Europe Headquarters

Email: salesemea@addonnetworks.com

Telephone: +44 1285 842070