



## E10GSFPTX-OPC

Intel® E10GSFPTX Compatible TAA 100/1000/10000Base-TX SFP+ Transceiver (Copper, 30m, RJ-45)

### Features

- SFF-8432 Compliance
- RJ-45 Connector
- Copper Media Type
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



### Applications:

- 10GBase Ethernet
- Access and Enterprise

### Product Description

This Intel® E10GSFPTX compatible SFP+ transceiver provides 100/1000/10000Base-TX throughput up to 30m over a copper connection via a RJ-45 connector. This TX module supports 100/1000/10000Base auto-negotiation and can be configured to fit your needs. It is guaranteed to be 100% compatible with the equivalent Intel® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. It is built to meet or exceed the specifications of Intel®, as well as to comply with MSA (Multi-Source Agreement) standards to ensure seamless network integration. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

OptioConnect's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."



### Absolute Maximum Ratings

| Parameter                  | Symbol           | Min.  | Max. | Unit |
|----------------------------|------------------|-------|------|------|
| Maximum Supply Voltage     | V <sub>CC</sub>  | 3.135 | 3.6  | VDC  |
| Storage Temperature        | T <sub>S</sub>   | -40   | 85   | °C   |
| Operating Case Temperature | T <sub>C</sub>   | 0     | 70   | °C   |
| Operating Humidity         | RH               | 5     | 95   | %    |
| Maximum Bitrate            | B <sub>max</sub> |       | 11.4 | Gbps |

### Electrical Characteristics (TOP=25°C, V<sub>CC</sub>=3.3Volts)

| Parameter                        | Symbol          | Min.  | Typ. | Max.                 | Unit | Notes |
|----------------------------------|-----------------|-------|------|----------------------|------|-------|
| Power Supply Voltage             | V <sub>CC</sub> | 3.135 | 3.30 | 3.465                | V    |       |
| Low Speed Input Voltage          |                 | -0.5  |      | V <sub>CC</sub> +0.3 | V    |       |
| Two-Wire Interface Input Voltage |                 | -0.3  |      | V <sub>CC</sub> +0.5 | V    |       |
| Power (30m @ 25C ambient)        |                 |       | 2.3  | 2.5                  | W    |       |

## Pin Descriptions

| Pin | Symbol     | Name/Descriptions                                    | Ref. |
|-----|------------|------------------------------------------------------|------|
| 1   | VeeT       | Transmitter Ground                                   | 1    |
| 2   | Tx_Fault   | Transmitter Fault LVTTTL-O                           |      |
| 3   | Tx_Disable | Transmitter Disable LVTTTL-I                         |      |
| 4   | SDA        | 2-wire Serial Interface Data Line LVTTTL-I/O         |      |
| 5   | SCL        | 2-wire Serial Interface Clock LVTTTL-I/O             |      |
| 6   | Mod_ABS    | Module Absent, connect to VeeT or VeeR in the module |      |
| 7   | RS0        | Rate Select 0 LVTTTL-I                               |      |
| 8   | Rx_LOS     | Receiver Loss of Signal Indication LVTTTL-O          |      |
| 9   | RS1        | Rate Select 1 LVTTTL-I                               |      |
| 10  | VeeR       | Receiver Ground                                      | 1    |
| 11  | VeeR       | Receiver Ground                                      | 1    |
| 12  | RD-        | Receiver Inverted Data Output CML-O                  |      |
| 13  | RD+        | Receiver Non-Inverted Data Output CML-O              |      |
| 14  | VeeR       | Receiver Ground                                      | 1    |
| 15  | VccR       | Receiver 3.3V Supply                                 |      |
| 16  | VccT       | Transmitter 3.3V Supply                              |      |
| 17  | VeeT       | Transmitter Ground                                   | 1    |
| 18  | TD+        | Receiver Inverted Data Output CML-I                  |      |
| 19  | TD-        | Transmitter Inverted Data Input CML-I                |      |
| 20  | VeeT       | Module Transmitter Ground                            | 1    |

### Notes:

1. The module signal grounds should be isolated from the module case.

Mechanical Specifications



## **OptioConnect**

### **Innovation for the Future of High-Speed Networking**

#### **Who We Are**

OptioConnect is reshaping the landscape of communication and high-speed networking through intelligent technology. With a core focus on cutting edge technology, we deliver smarter fiber optic solutions for enterprise networks, data centers, and next-gen telecom infrastructures.

#### **What We Do**

At OptioConnect, we fuse advanced engineering with intelligent automation to drive the future of networking. Our AI-integrated solutions are designed to optimize performance and streamline operations with:

- Superior Performance
- Network and traffic optimization
- Intelligent energy management
- Seamless OEM compatibility
- Scalable cost-efficiency

#### **Smarter Networks by Design**

Innovation isn't just a goal—it's our process. We embed AI and machine learning across our R&D and product lines, enabling adaptive performance, automated tuning, and faster deployment cycles. The result? Networks that don't just work—they learn, evolve, and outperform.

#### **Our Team**

Our engineers, data scientists, and network architects bring decades of experience and a future-focused mindset. We provide hands-on support with intelligent insights that turn complex challenges into simple solutions.

#### **Our Mission**

To deliver AI-enhanced connectivity that reduces cost, increases speed, and maximizes efficiency—empowering our partners to operate at the forefront of a rapidly evolving digital world.

#### **Let's Connect**

Discover how OptioConnect's intelligent infrastructure solutions can power your network's next leap forward.

[www.optioconnect.com](http://www.optioconnect.com) | [info@optioconnect.com](mailto:info@optioconnect.com)

