

## SFP-10GB-PDAC3MLZ-J-AO

Juniper Networks® Compatible TAA 10GBase-CU SFP+ to SFP+ Direct Attach Cable (Passive Twinax, 3m, 30AWG, LSZH)

### Features

- SFF-8431/8432 and INF-8074i Compliant
- IEEE802.3ba Standard
- Up to 10.3125Gbps
- Passive copper
- Operating Temperature 0 to 70 Celsius
- 30AWG
- RoHS 2.0 compliant and lead-free



### Applications

- 10GBase-CU

### Product Description

This is a Juniper Networks® compatible 10GBase-CU SFP+ to SFP+ LSZH direct attach cable that operates over passive copper with a maximum reach of 3.0m (9.8ft). It has been programmed, uniquely serialized, and data-traffic and application tested to ensure it is 100% compliant and functional. This direct attach cable is TAA (Trade Agreements Act) compliant, and is built to comply with MSA (Multi-Source Agreement) standards. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

AddOn's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."



## Regulatory Compliance

- ESD to the Electrical PINs: compatible with MIL-STD-883 Method 3015.
- ESD to the Duplex LC Receptacle: compatible with IEC 61000-4-2.
- Immunity: compatible with IEC 61000-4-3.
- EMI: compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B.
- Laser Eye Safety: compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1, 2.
- RoHS: compliant with 2002/95/EC 4.1&4.2 2005/747/EC.

## Absolute Maximum Ratings

| Parameter                  | Symbol | Min. | Typ. | Max. | Unit |
|----------------------------|--------|------|------|------|------|
| Supply Voltage             | Vcc    | 3.13 | 3.3  | 3.47 | V    |
| Storage Temperature        | Tstg   | -40  |      | 85   | °C   |
| Operating Case Temperature | Tc     | 0    |      | 70   | °C   |
| Humidity                   | RH     | 5    |      | 85   | %    |
| Data Rate                  |        |      | 10   |      | Gbps |

## Physical Characteristics

| Parameter       | Symbol      | Min. | Typ. | Max. | Unit |
|-----------------|-------------|------|------|------|------|
| Length          | L           |      |      | 3    | M    |
| AWG             |             |      |      | 30   | AWG  |
| Jacket Material | LSZH, Black |      |      |      |      |

## Electrical Characteristics

| Parameter                  | Symbol   | Min.   | Typ. | Max.  | Unit |
|----------------------------|----------|--|------|-------|------|
| Resistance                 | Rcon     |  |      | 3     | Ω    |
| Insulation Resistance      | Rins     |  |      | 10    | MΩ   |
| Raw Cable Impedance        | Zca      | 95   | 100  | 110   | Ω    |
| Mated Connector Impedance  | Zmated   | 85   | 100  | 110   | Ω    |
| Insertion Loss at 12.89GHz | SDD21    |  |      | 17.04 | dB   |
| Return Loss at 12.89GHz    | SDD11/22 | $\text{Return\_Loss}(f) \geq \begin{cases} 12 - 2\sqrt{f}, & 0.05 \leq f < 4.1 \\ 6.3 - 13\log_{10}\left(\frac{f}{5.5}\right), & 4.1 \leq f \leq 10 \end{cases}$ |      |       | dB   |
| Rise Time (20-80%)         |          |  |      | 34    | ps   |

## Pin Descriptions

| Pin | Logic      | Symbol     | Name/Description   | Plug Sequence | Note |
|-----|------------|------------|--|---------------|------|
| 1   |            | VeeT       | Module Transmitter Ground.   | 1             | 3    |
| 2   | LVTTTL-O   | Tx_Fault   | Module Transmitter Fault.  | 3             | 4    |
| 3   | LVTTTL-I   | Tx_Disable | Transmitter Disable. Turns off transmitter laser output.   | 3             | 5    |
| 4   | LVTTTL-I/O | SDA        | 2-Wire Serial Interface Data. Same as MOD_DEF2 in INF-8074i.   | 3             |      |
| 5   | LVTTTL-I/O | SCL        | 2-Wire Serial Interface Clock. Same as MOD_DEF1 in INF-8074i.  | 3             |      |
| 6   |            | MOD_ABS    | Module Absent. Connected to VeeT or VeeR in the module.  | 3             |      |
| 7   | LVTTTL-I   | RS0        | Rate Select 0. Optionally controls the SFP+ module receiver.   | 3             | 6    |
| 8   | LVTTTL-O   | Rx_LOS     | Receiver Loss of Signal indication. In FC, designated as Rx_LOS. In Ethernet, designated as Signal Detect. | 3             | 4    |
| 9   | LVTTTL-I   | RS1        | Rate Select 1. Optionally controls SFP+ module transmitter.  | 3             | 6    |
| 10  |            | VeeR       | Module Receiver Ground.  | 1             | 3    |
| 11  |            | VeeR       | Module Receiver Ground.  | 1             | 3    |
| 12  | CML-O      | RD-        | Receiver Inverted Data Output.   | 3             |      |
| 13  | CML-O      | RD+        | Receiver Non-Inverted Data Output.   | 3             |      |
| 14  |            | VeeR       | Module Receiver Ground.  | 1             | 3    |
| 15  |            | VccR       | Module Receiver 3.3V Supply.   | 2             |      |
| 16  |            | VccT       | Module Transmitter 3.3V Supply.  | 2             |      |
| 17  |            | VeeT       | Module Transmitter Ground.   | 1             | 3    |
| 18  | CML-I      | TD+        | Transmitter Non-Inverted Data Input.   | 3             |      |
| 19  | CML-I      | TD-        | Transmitter Inverted Data Input.   | 3             |      |
| 20  |            | VeeT       | Module Transmitter Ground.   | 1             | 3    |

### Notes:

1. Labeling as inputs (I) and outputs (O) are from the perspective of the module.
2. The case makes electrical contact to the cage before any of the board edge contacts are made.
3. The module signal ground contacts, VeeR and VeeT, should be isolated from the module case.
4. This contact is an open collector/drain output contact and shall be pulled up on the host. Pull-ups can be connected to one of several power supplies; however, the host board design shall ensure that no module contact has a voltage exceeding module VccT/R+0.5V.
5. Tx\_Disable is an input contact with a 4.7kΩ to 10kΩ pull-up to the VccT inside the module.
6. If implementing SFF-8079, contacts 7 and 9 in SFF-8431 are used for AS0 and AS1, respectively.

## Electrical Pin-Out Details



## Mechanical Specifications



### Notes:

1. 2 pairs.
2. 100% conductor test conditions: 5V, insulation resistance of 10MΩ, and conduction resistance maximum of 3Ω.

## About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is ingrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications ranging from NEBS Level 3 to ISO 9001:2015 with every new development while maintaining the signature reliability of its products.



## U.S. Headquarters

Email: [sales@addonnetworks.com](mailto:sales@addonnetworks.com)

Telephone: +1 877.292.1701

Fax: 949.266.9273

## Europe Headquarters

Email: [salesemea@addonnetworks.com](mailto:salesemea@addonnetworks.com)

Telephone: +44 1285 842070