



EX-SFP-1GE-T-OPC

Juniper Networks® EX-SFP-1GE-T Compatible TAA 10/100/1000Base-TX SFP Transceiver (Copper, 100m, RJ-45)

Features

- INF-8074 Compliance
- RJ-45 Connector
- Copper Media Type
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



Applications:

- 1000Base Ethernet
- Access and Enterprise

Product Description

This Juniper Networks® EX-SFP-1GE-T compatible SFP transceiver provides 10/100/1000Base-TX throughput up to 100m over a copper connection via a RJ-45 connector. It can operate at temperatures between 0 and 70C. This TX module supports 10/100/1000Base auto-negotiation and can be configured to fit your needs. Our transceiver is built to meet or exceed OEM specifications and is guaranteed to be 100% compatible with Juniper Networks®. It has been programmed, uniquely serialized, and tested for data-traffic and application to ensure that it will initialize and perform identically. All of our transceivers comply with Multi-Source Agreement (MSA) standards to provide seamless network integration. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

OptioConnect's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."



Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Supply Current	I _{cc}		320	375	mA	1
Input Voltage	V _{cc}	3.13	3.3	3.47	V	2
Maximum Voltage	V _{max}			4	V	
Surge Current	I _{surge}			30	mA	3
Power Consumption				1.5	W	

Notes:

1. 1.2W maximum power over the full range of voltage and temperature. Power consumption and surge current are higher than the specified values in the SFP MSA.
2. Referenced to GND.
3. Hot plug above steady state current. Power consumption and surge current are higher than the specified values in the SFP MSA.

Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Data Rate	DR	10		1000	Mbps	3, 4, 5
Distance Supported	L			100	m	1
Operating Temperature	T _c	0		85	°C	
Storage Temperature	T _{stg}	-40		85	°C	

Notes:

1. Category 5 UTP. BER<10⁻¹².
2. Clock tolerance is +/- 50ppm.
3. By default, the GE-GB-P is a full duplex device in preferred master mode.
4. Automatic crossover detection is enabled. External crossover cable is not required.
5. 1000Base-T operation requires the host system to have an SGMII interface with no clocks and the module PHY to be configured per Application Note AN-2036. With a SERDES that does not support SGMII, the module will operate at 1000Base-T only.

Low-Speed Signals

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
SFP Output - Low	VOL	0		0.5	V	1
SFP Output - High	VOH	Host_Vcc-0.5		Host_Vcc+0.3	V	1
SFP Input - Low	VIL	0		0.8	V	2
SFP Input - High	VIH	2		Vcc+0.3	V	2

Notes:

1. 4.7k Ω to 10k Ω pull-up to the Host_Vcc, measured at the host side of the connector.
2. 4.7k Ω to 10k Ω pull-up to the Vcc, measured at the SFP side of the connector.

High-Speed Signals

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Transmission Line - SFP						
Line Frequency	LF		125		MHz	1
Tx Output impedance	ZOUT, TX		100		Ω	2
Rx Input Impedance	ZIN, RX		100		Ω	2
Host - SFP						
Single-Ended Data Input Swing	VIN,sing	250		1200	mV	3
Single-Ended Data Output Swing	VOUT,sing	350		800	mV	3
Rise/Fall Time	Tr/Tf		175		Psec	4
Tx Input Impedance	ZIN		50		Ω	3
Rx Output Impedance	ZOUT		50		Ω	3

Notes:


1. 5-level encoding, per IEEE 802.3.
2. Differential, for all frequencies between 1MHz and 125MHz.
3. Single-ended.
4. 20-80%.

Pin Descriptions

Pin	Symbol	Name/Description	Notes
1	VeeT	Transmitter Ground (Common with Receiver Ground).	1
2	Tx_Fault	Transmitter Fault. Not Supported.	
3	Tx_Disable	Transmitter Disabled. PHY disabled on “high” or “open.”	2
4	MOD_DEF(2)	Module Definition 2. Data Line for Serial ID.	3
5	MOD_DEF(1)	Module Definition 1. Clock Line for Serial ID.	3
6	MOD_DEF(0)	Module Definition 0. Grounded within the module.	3
7	Rate Select	No Connection Required.	
8	LOS	Loss of Signal Indication.	4
9	VeeR	Receiver Ground (Common with Transmitter Ground).	1
10	VeeR	Receiver Ground (Common with Transmitter Ground).	1
11	VeeR	Receiver Ground (Common with Transmitter Ground).	1
12	RD-	Receiver Inverted Data Out. AC Coupled.	
13	RD+	Receiver Non-Inverted Data Out. AC Coupled.	
14	VeeR	Receiver Ground (Common with Transmitter Ground).	1
15	VccR	Receiver Power Supply.	
16	VccT	Transmitter Power Supply.	
17	VeeT	Transmitter Ground (Common with Receiver Ground).	1
18	TD+	Transmitter Non-Inverted Data In. AC Coupled.	
19	TD-	Transmitter Inverted Data In. AC Coupled.	
20	VeeT	Transmitter Ground (Common with Receiver Ground).	1


Notes:

1. The circuit ground is connected to the chassis ground.
2. PHY is disabled on TDIS>2.0V or open, enabled on TDIS<0.8V.
3. Should be pulled up with 4.7kΩ to 10kΩ on the host board to a voltage between 2.0V and 3.6V.
MOD_DEF(0) pulls the line “low” to indicate that the module is plugged in.
4. LVTTTL is compatible with a maximum voltage of 2.5V. Not supported on GE-GB-P.



Pin-Out of Connector Block on the Host board

Mechanical Specifications



OptioConnect

Innovation for the Future of High-Speed Networking

Who We Are

OptioConnect is reshaping the landscape of communication and high-speed networking through intelligent technology. With a core focus on cutting edge technology, we deliver smarter fiber optic solutions for enterprise networks, data centers, and next-gen telecom infrastructures.

What We Do

At OptioConnect, we fuse advanced engineering with intelligent automation to drive the future of networking. Our AI-integrated solutions are designed to optimize performance and streamline operations with:

- Superior Performance
- Network and traffic optimization
- Intelligent energy management
- Seamless OEM compatibility
- Scalable cost-efficiency

Smarter Networks by Design

Innovation isn't just a goal—it's our process. We embed AI and machine learning across our R&D and product lines, enabling adaptive performance, automated tuning, and faster deployment cycles. The result? Networks that don't just work—they learn, evolve, and outperform.

Our Team

Our engineers, data scientists, and network architects bring decades of experience and a future-focused mindset. We provide hands-on support with intelligent insights that turn complex challenges into simple solutions.

Our Mission

To deliver AI-enhanced connectivity that reduces cost, increases speed, and maximizes efficiency—empowering our partners to operate at the forefront of a rapidly evolving digital world.

Let's Connect

Discover how OptioConnect's intelligent infrastructure solutions can power your network's next leap forward.

www.optioconnect.com | info@optioconnect.com

