OSFP-800GB-2XFR4-MX-AO

NVIDIA® Compatible TAA 800GBase-2xFR4 PAM4 OSFP-IHS Transceiver (SMF, 1310nm, 2km, 2xLC, DOM, CMIS 5.0)

Features:

- Supports Both Ethernet and InfiniBand NDR
- 2x400GBASE-FR4 Optical Interface
- 2x400GAUI-4 C2M Electrical Interface
- InfiniBand NDR Electrical and Optical Interface
- Type 2 Housing with Dual LC Connector
- Support 850Gbps Aggregate Bit Rate
- I2C Management Interface Compliant to CMIS Rev5.0
- Class 1 Laser Certified
- Operating Temperature: 0 to 70 Celsius
- Hot-Pluggable OSFP Form Factor
- RoHS Compliant and Lead-Free



Applications:

- 2x400GBase Ethernet

Product Description

This NVIDIA® compatible OSFP-IHS Transceiver provides 800GBase-2xFR4 throughput up to 2km over single-mode fiber (SMF) PAM4 using a wavelength of 1310nm via a 2xLC connector. It can operate at temperatures between 0 and 70C. All of our transceivers are built to comply with Multi-Source Agreement (MSA) standards and are uniquely serialized and tested for data-traffic and application to ensure seamless network integration. Additional product features include Digital Optical Monitoring (DOM) support which allows access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

AddOn's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products."

TAA COMPLIANT

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage	Vcc	-0.5		3.6	V	
Storage Temperature	Tstg	-40		85	°C	
Operating Case Temperature	Tc	0		70	°C	1
Relative Humidity (Non-Condensing)	RH	5		95	%	
Maximum Power Dissipation	PDISS			16.5	W	
Maximum Power Dissipation (Low-Power Mode)	P_{DLP}			2	W	
Signaling Speed Per Lane	DRL		53.125		GBd	
Operating Distance		2		2000	m	

Electrical Characteristics

Parameter		Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage		Vcc	3.135	3.3	3.465	V	
Data Input Voltage Differential		IVdip-VdinI			1	V	
Control Input Voltage Differential		Vi	-0.3		Vcc+0.5	V	
Control Output Current		Io	-20		20	mA	
Instantaneous Peak Current at Hot Plug		Icc_IP			6600	mA	
Sustained Peak Current at Hot Plug		Icc_SP			5494.5	mA	
Control Input Voltage - High		V_{IH}	Vcc*0.7		Vcc+0.3	V	
Control Input Voltage - Low		V_{IL}	-0.3		Vcc*0.3	V	
2-Wire Serial Interface Clock Rate					400	kHz	
Power Supply Noise (1kHz to 1MHz Pk-Pk)					66	mVp-p	
Transmitter							
Differential Pk-Pk Input Voltage Tolerance (TP1a)			750			mV	
Pk-Pk AC Common-Mode Voltage Tolerance	**Low-Frequency (VCMLF)**				32	mV	
	Full-Band (VCMFB)				80		
Differential-Mode to Common-Mode Return Loss		RLcd	802.3ck 120G-2			dB	
Effective Return Loss		ERL	8.5			dB	
Differential Termination Mismatch					10	%	
Single-Ended Voltage Tolerance Range			-0.4		3.3	V	
DC Common-Mode Voltage Tolerance			-0.35		2.85	V	
Receiver							
Pk-Pk AC Common-Mode Voltage	**Low-Frequency (VCMLF)**				32	mV	
	Full-Band (VCMFB)				80		

Differential Pk-Pk Output Voltage	**Short-Mode**				600	mV	
	Long-Mode				845		
Eye Height		EH	15			mV	
Vertical Eye Closure		VEC			12	dB	
Common-Mode to Differential-Mode Return Loss		RLDc	802.3ck 120G-1			dB	
Effective Return Loss		ERL	8.5			dB	
Differential Termination Mismatch					10	%	
Transition Time			8.5			ps	
DC Common-Mode Voltage Tolerance			-0.35		2.85	V	
Low-Speed Control and Sense Signals							
Module Output SCL and SDA		V_{OL}	0		0.4	V	
Module Input SCL and SDA		V_{IL}	-0.3		Vcc*0.3	V	
		V_{IH}	Vcc*0.7		Vcc+0.5	V	
InitMode, ResetL, and ModSelL		V_{IL}	-0.3		0.8	V	
		V_{IH}	2		Vcc+0.3	V	
IntL		V_{OL}	0		0.4	V	
		V_{OH}	Vcc-0.5		Vcc+0.3	V	

Optical Characteristics

Parameter		Symbol	Min.	Typ.	Max.	Unit	Notes
Transmitter							
Wavelength L0, L4		λC0, λC4	1264.5	1271	1277.5	nm	
Wavelength L1, L5		λC1, λC5	1284.5	1291	1297.5	nm	
Wavelength L2, L6		λC2, λC6	1304.5	1311	1317.5	nm	
Wavelength L3, L7		λC3, λC7	1324.5	1331	1337.5	nm	
Side-Mode Suppression Ratio		SMSR	30			dB	
Total Average Launch Power		AOP_T			10.4	dBm	
Average Launch Power Per Lane		AOP_L	-3.2		4.4	dBm	1
Outer Optical Modulation Amplitude (OMAouter) Per Lane	**TDECQ<1.4dB**	TOMA	-0.2		3.7	dBm	
	1.4dB≤TDECQ≤3.4dB		-1.6+TDECQ				
Difference in Launch Power Between Any Two Lanes (OMAouter)		AOP_d			3.9	dB	
Transmitter and Dispersion Eye Closure for PAM4 (TDECQ) Per Lane		TDECQ			3.4	dB	
Transmitter Eye Closure for PAM4 (TECQ) Per Lane		TECQ			3.4	dB	
| TDECQ – TECQ |					2.5	dB	
Overshoot/Undershoot					22	%	

Transmitter Power Excursion					1.8	dBm	
Average Launch Power of Off Transmitter Per Lane		Toff			-16	dBm	
Extinction Ratio		ER	3.5			dB	
Transmitter Transition Time (Maximum)		Tr			17	ps	
$RIN_{17.1}OMA$ (Maximum)		RIN			-136	dB/Hz	
Optical Return Loss Tolerance		ORL			17.1	dB	
Transmitter Reflectance		T_R			-26	dB	2
Receiver							
Wavelength L0, L4		λC0, λC4	1264.5	1271	1277.5	nm	
Wavelength L1, L5		λC1, λC5	1284.5	1291	1297.5	nm	
Wavelength L2, L6		λC2, λC6	1304.5	1311	1317.5	nm	
Wavelength L3, L7		λC3, λC7	1324.5	1331	1337.5	nm	
Damage Threshold Per Lane		AOP_D	5.4			dBm	
Average Receive Power Per Lane		AOP_R	-7.2		4.4	dBm	
Receive Power (OMAouter) Per Lane		OMA_R			3.7	dBm	
Difference in Receive Power Between Any Two Lanes (OMAouter) Maximum		AOP_g			4.1	dB	
Receiver Reflectance		RR			-26	dB	
Receiver Sensitivity (OMAouter) Per Lane	**TECQ<1.4dB**	SOMA			-4.6	dBm	
	1.4dB≤TECQ≤3.4dB				-6+TECQ		
Stressed Receiver Sensitivity (OMAouter) Per Lane		SRS			-2.6	dBm	3
Stressed Eye Closure for PAM4 (SECQ) Per Lane Under Test				3.4		dB	
OMAouter of Each Aggressor Lane				1.4		dBm	

Notes:


1. Average launch power, per lane (minimum) is informative and not the principal indicator of signal strength.
2. Transmitter reflectance is defined looking into the transmitter.
3. Measured with conformance test signal at TP3 for the BER=$2.4x10^{-4}$.

Pin Descriptions


Pin	Logic	Symbol	Name/Description	Notes
1		GND	Module Ground.	
2	CML-I	Tx2+	Transmitter Data Non-Inverted.	
3	CML-I	Tx2-	Transmitter Data Inverted.	
4		GND	Module Ground.	
5	CML-I	Tx4+	Transmitter Data Non-Inverted.	
6	CML-I	Tx4-	Transmitter Data Inverted.	
7		GND	Module Ground.	
8	CML-I	Tx6+	Transmitter Data Non-Inverted.	
9	CML-I	Tx6-	Transmitter Data Inverted.	
10		GND	Module Ground.	
11	CML-I	Tx8+	Transmitter Data Non-Inverted.	
12	CML-I	Tx8-	Transmitter Data Inverted.	
13		GND	Module Ground.	
14	LVCMOS-I/O	SCL	2-Wire Serial Interface Clock.	
15		Vcc	+3.3V Power.	
16		Vcc	+3.3V Power.	
17	Multi-Level	LPWn/PRSn	Low-Power Mode/Module Present.	
18		GND	Module Ground.	
19	CML-O	Rx7-	Receiver Data Inverted.	
20	CML-O	Rx7+	Receiver Data Non-Inverted.	
21		GND	Module Ground.	
22	CML-O	Rx5-	Receiver Data Inverted.	
23	CML-O	Rx5+	Receiver Data Non-Inverted.	
24		GND	Module Ground.	
25	CML-O	Rx3-	Receiver Data Inverted.	
26	CML-O	Rx3+	Receiver Data Non-Inverted.	
27		GND	Module Ground.	
28	CML-O	Rx1-	Receiver Data Inverted.	
29	CML-O	Rx1+	Receiver Data Non-Inverted.	
30		GND	Module Ground.	
31		GND	Module Ground.	
32	CML-O	Rx2+	Receiver Data Non-Inverted.	
33	CML-O	Rx2-	Receiver Data Inverted.	
34		GND	Module Ground.	
35	CML-O	Rx4+	Receiver Data Non-Inverted.	
36	CML-O	Rx4-	Receiver Data Inverted.	
37		GND	Module Ground.	
38	CML-O	Rx6+	Receiver Data Non-Inverted.	
39	CML-O	Rx6-	Receiver Data Inverted.	

40		GND	Module Ground.	
41	CML-O	Rx8+	Receiver Data Non-Inverted.	
42	CML-O	Rx8-	Receiver Data Inverted.	
43		GND	Module Ground.	
44	Multi-Level	INT/RSTn	Module Interrupt/Module Reset.	
45		Vcc	+3.3V Power.	
46		Vcc	+3.3V Power.	
47	LVCMOS-I/O	SDA	2-Wire Serial Interface Data.	
48		GND	Module Ground.	
49	CML-I	Tx7-	Transmitter Data Inverted.	
50	CML-I	Tx7+	Transmitter Data Non-Inverted.	
51		GND	Module Ground.	
52	CML-I	Tx5-	Transmitter Data Inverted.	
53	CML-I	Tx5+	Transmitter Data Non-Inverted.	
54		GND	Module Ground.	
55	CML-I	Tx3-	Transmitter Data Inverted.	
56	CML-I	Tx3+	Transmitter Data Non-Inverted.	
57		GND	Module Ground.	
58	CML-I	Tx1-	Transmitter Data Inverted.	
59	CML-I	Tx1+	Transmitter Data Non-Inverted.	
60		GND	Module Ground.	


Electrical Pad Layout



Recommended Host Board Schematic



Mechanical Specifications



About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is ingrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications ranging from NEBS Level 3 to ISO 9001:2015 with every new development while maintaining the signature reliability of its products.



U.S. Headquarters

Email: sales@addonnetworks.com

Telephone: +1 877.292.1701

Fax: 949.266.9273

Europe Headquarters

Email: salesemea@addonnetworks.com

Telephone: +44 1285 842070