

### **SFP-10GB-50DW49-80-C**

MSA and TAA 10GBase-DWDM SFP+ Transceiver C-Band 50GHz (SMF, 1538.19nm, 80km, LC, DOM)

#### **Features:**

- SFF-8432 and SFF-8472 Compliance
- Duplex LC Connector
- Single-mode Fiber
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



#### **Applications:**

- 10x Gigabit Ethernet over DWDM
- 8x/10x Fibre Channel
- Access and Enterprise

#### **Product Description**

This MSA compliant SFP+ transceiver provides 10GBase-DWDM throughput up to 80km over single-mode fiber (SMF) using a wavelength of 1538.19nm via an LC connector. It can operate at temperatures between 0 and 70C. All of our transceivers are built to comply with Multi-Source Agreement (MSA) standards and are uniquely serialized and tested for data-traffic and application to ensure seamless network integration. Additional product features include Digital Optical Monitoring (DOM) support which allows access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

ProLabs' transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S.-made or designated country end products.")



## Wavelength Guide

| Channel # | Center Wavelength (nm) | Channel # | Center Wavelength (nm) |
|-----------|------------------------|-----------|------------------------|
| 18        | 1563.05                | 40        | 1545.32                |
| 19        | 1562.23                | 41        | 1544.53                |
| 20        | 1561.42                | 42        | 1543.73                |
| 21        | 1560.61                | 43        | 1542.94                |
| 22        | 1559.79                | 44        | 1542.14                |
| 23        | 1558.98                | 45        | 1541.35                |
| 24        | 1558.17                | 46        | 1540.56                |
| 25        | 1557.36                | 47        | 1539.77                |
| 26        | 1556.55                | 48        | 1538.98                |
| 27        | 1555.75                | 49        | 1538.19                |
| 28        | 1554.94                | 50        | 1537.40                |
| 29        | 1554.13                | 51        | 1536.61                |
| 30        | 1553.33                | 52        | 1535.82                |
| 31        | 1552.52                | 53        | 1535.04                |
| 32        | 1551.72                | 54        | 1534.25                |
| 33        | 1550.92                | 55        | 1533.47                |
| 34        | 1550.12                | 56        | 1532.68                |
| 35        | 1549.32                | 57        | 1531.90                |
| 36        | 1548.51                | 58        | 1531.12                |
| 37        | 1547.72                | 59        | 1530.33                |
| 38        | 1546.92                | 60        | 1529.55                |
| 39        | 1546.12                | 61        | 1528.77                |

## Absolute Maximum Ratings

| Parameter              | Symbol | Min. | Typ.    | Max.              | Unit | Notes |
|------------------------|--------|------|---------|-------------------|------|-------|
| Storage Temperature    | Tstg   | -40  |         | 85                | °C   |       |
| Operating Temperature  | Tc     | 0    |         | 70                | °C   |       |
| Supply Current         | Icc    |      | 450     | 500               | mA   | 1     |
| Data Rate              | DR     | 1.2  | 10.3125 | 11.3              | Gbps | 2     |
| Maximum Supply Voltage | Vcc    | -0.5 |         | 4.0               | V    | 1     |
| Bit Error Rate         | BER    |      |         | 10 <sup>-12</sup> |      |       |

### Notes:

1. For electrical power interface.
2. IEEE 802.3ae.

## Electrical Characteristics

| Parameter                           | Symbol  | Min. | Typ. | Max.     | Unit | Notes |
|-------------------------------------|---------|------|------|----------|------|-------|
| Power Supply Voltage                | Vcc     | 3.14 | 3.3  | 3.46     | V    |       |
| Transmitter                         |         |      |      |          |      |       |
| Input Differential Impedance        | RIN     |      | 100  |          |      |       |
| Differential Data Input Swing       | VIN,pp  | 300  |      | 850      | mV   |       |
| Transmit Disable Voltage            | VD      | 2    |      | Vcc      | V    |       |
| Transmit Enable Voltage             | VEN     | Vee  |      | Vee+0.8  | V    |       |
| Receiver                            |         |      |      |          |      |       |
| Differential Data Output Swing      | VOUT,pp | 300  |      | 850      | mV   |       |
| Data Output Rise/Fall Time (20-80%) | Tr/Tf   | 28   |      |          | ps   |       |
| LOS Fault                           | Vlosa   | 2    |      | Host_Vcc | V    |       |
| LOS Normal                          | Vlosd   | Vee  |      | Vee+0.5  | V    |       |

## Optical Characteristics

| Parameter                       | Symbol          | Min.             | Typ.        | Max.             | Unit  | Notes |
|---------------------------------|-----------------|------------------|-------------|------------------|-------|-------|
| Transmitter                     |                 |                  |             |                  |       |       |
| Output Optical Power            | Ptx             | 0                |             | 4                | dBm   | 1     |
| Optical Center Wavelength       | $\lambda_C$     | $\lambda_C-0.05$ | $\lambda_C$ | $\lambda_C+0.05$ |       | 2     |
| Extinction Ratio                | ER              | 9                |             |                  | dB    |       |
| Spectral Width (-20dB)          | $\Delta\lambda$ |                  |             | 0.6              | nm    |       |
| Side Mode Suppression Ratio     | SMSR            | 30               |             |                  | dB    |       |
| Relative Intensity Noise        | RIN             |                  |             | -128             | dB/Hz |       |
| Transmitter Dispersion Penalty  | TDP             |                  |             | 3.2              | dB    |       |
| Launch Power of Off Transmitter | Poff            |                  |             | -30              | dBm   | 1     |
| Receiver                        |                 |                  |             |                  |       |       |
| Optical Center Wavelength       | $\lambda_C$     | 1260             |             | 1620             | nm    |       |
| Average Receive Power           | Prx             | -24              |             | -7               | dBm   |       |
| Receiver Sensitivity @10.3Gbps  | S               |                  |             | -24              | dBm   | 3     |
| Receiver Reflectance            | RR              |                  |             | -27              | dB    |       |
| LOS Assert                      | LOSA            | -35              |             |                  | dBm   |       |
| LOS De-Assert                   | LOSD            |                  |             | -27              | dBm   |       |
| LOS Hysteresis                  | LOSH            | 0.5              |             |                  | dB    |       |

### Notes:

1. Average.
2.  $\lambda$  = specified ITU grid wavelength.
3. Measured with the PRBS 2<sup>31</sup>-1 test mode and BER<10<sup>-12</sup>.


## Pin Descriptions

| Pin | Symbol     | Name/Description                                                 | Notes |
|-----|------------|------------------------------------------------------------------|-------|
| 1   | VeeT       | Transmitter Ground. Common with Receiver Ground.                 | 1     |
| 2   | Tx_Fault   | Transmitter Fault.                                               |       |
| 3   | Tx_Disable | Transmitter Disable. Laser output disables on "high" or "open."  | 2     |
| 4   | SDA        | 2-Wire Serial ID Interface Data Line.                            | 3     |
| 5   | SCL        | 2-Wire Serial ID Interface Clock Line.                           | 3     |
| 6   | MOD_ABS    | Module Absent. Grounded within the module.                       | 3     |
| 7   | RS0        | Rate Select 0. Not used.                                         |       |
| 8   | LOS        | Loss of Signal Indication. "Logic 0" indicates normal operation. | 4     |
| 9   | RS1        | Rate Select 1. Not used.                                         | 1     |
| 10  | VeeR       | Receiver Signal Ground. Common with Transmitter Ground.          | 1     |
| 11  | VeeR       | Receiver Signal Ground. Common with Transmitter Ground.          | 1     |
| 12  | RD-        | Inverse Received Data Out. AC Coupled.                           |       |
| 13  | RD+        | Non-Inverted Receiver Data Out. AC Coupled.                      |       |
| 14  | VeeR       | Receiver Signal Ground. Common with Transmitter Ground.          | 1     |
| 15  | VccR       | Receiver Power Supply.                                           |       |
| 16  | VccT       | Transmitter Power Supply.                                        |       |
| 17  | VeeT       | Transmitter Signal Ground. Common with Receiver Ground.          | 1     |
| 18  | TD+        | Transmitter Non-Inverted Data In. AC Coupled.                    |       |
| 19  | TD-        | Transmitter Inverted Data In. AC Coupled.                        |       |
| 20  | VeeT       | Transmitter Signal Ground.                                       | 1     |


## Notes:

1. Circuit ground is isolated from the chassis ground.
2. Disabled: Tdis>2V or open. Enabled: Tdis<0.8V.
3. Should be pulled up with 4.7kΩ to 10kΩ on the host board to a voltage between 2V and 3.46V.
4. LOS is open collector output.


## Block Diagram of Transceiver





## Electrical Pad Layout





Top of Board



Bottom of Board



Mechanical Specifications



## About ProLabs

Our extensive experience comes as standard. For over 20 years ProLabs has delivered optical connectivity solutions that give our customers freedom and choice through our ability to provide seamless interoperability. At the heart of our company is the ability to provide state-of-the-art optical transport and connectivity solutions that are compatible with more than 100 optical switching and transport platforms.

## A Complete Portfolio of Network Solutions

ProLabs is focused on innovations in optical transport and connectivity. The combination of our knowledge of optics and networking equipment enables ProLabs to be your single source for optical transport and connectivity solutions from 100Mb to 1.6T while providing innovative solutions that increase network efficiency. We provide the optical connectivity expertise that is compatible with and enhances your switching and transport equipment.

## The Trusted Partner

Customer service is our number one value. ProLabs has invested in people, labs and manufacturing capacity to ensure compatible products, and immediate answers to your questions. With Engineering and Manufacturing offices in the U.K. and U.S. augmented by field offices throughout the U.S., U.K. and Asia, ProLabs is able to be our customers best advocate 24 hours a day.



## Contact Information

ProLabs US

Email: [sales@prolabs.com](mailto:sales@prolabs.com)

Telephone: 952-852-0252

ProLabs UK

Email: [salesupport@prolabs.com](mailto:salesupport@prolabs.com)

Telephone: +44 1285 719 600