



ELECTRICAL:
 1.CURRENT RATING: 1.5AMP
 2.CONTACT RESISTANCE: 100 MILLIOHMS MAX @ 500 VDC
 3.INSULATION RESISTANCE: 1000 MEGOHMS MIN
 4.INSULATION STRENGTH: 750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:
 1.STORAGE: -40°C TO +70°C
 2.OPERATION: -20°C TO 60°C
 COMPLY WITH TIA/EIA 568C.2 INTERNATIONAL STANDARD

MECHANICAL:
 1.IDC HOUSING MATERIAL: PBT
 2.PANEL FRAME MATERIAL: SPCC,BLACK OR INDUSTRIAL GREY ELECTROSTATIC POWDER COATING
 3.RJ45 JACK LIFE: 750 TIMES MIN
 4.IDC LIFE: 200 TIMES MIN
 5.CONTACT MATERIAL: PHOSPHOR BRONZE STAMP PIN T=0.30mm
 6.IDC CONTACT MATERIAL: PHOSPHOR BRONZE NICKEL PLATING
 7.WIRE: AWG 23-24

MAT'L		PRODUCT NO.	ADD-PPST-24P110C6
UNITS	mm	PRODUCT NAME	19-inch CAT6 24-Port Straight Patch Panel with 110-Type 1U
SCALE	1:1	DRAWING NO.	
TYPE OF PROJECTION			SHEET 1 OF 1 REV