

C-FMCMN-SFP
100Mbps 1x Open SFP Slot 1x RJ45
Media Converter



Features

- 1 x 10/100Mbps Auto-sensing RJ45 ports
- 1 x 100Mbps SFP fiber ports
- 4 KV Ethernet surge protection, adapt to a harsh outdoor environment
- Support Auto MDI/MDIX
- Flow control mode: full duplex with IEEE 802.3x standard, half-duplex with Back pressure standard
- IEEE 802.3 10Base-T and IEEE 802.3u 100Base-TX compliant
- A store-and-forward switching mechanism

Product Description

This is a mini media converter that converts a 10/100Base-TX(RJ-45) to 100Base-X via an Open SFP Port. The Open SFP Port allows users to customize between the SX, LX, or BX connections. This media converter provides a cost effective conversion from 10/100Base-TX(RJ-45) to 100Base-X, while extending the network reach beyond the 100m reach limitation of copper and saving space (3.75" x 2.25" x 1"). Our media converters are 100% compliant for all of our networking needs. Now you have a cost effective solution to your network upgrade needs.

Specifications

Parameter	
Access Method	10/100Mbps
Standard	IEEE802.3u, IEEE802.3, IEEE802.1, IEEE802.3x
Wavelength	850nm/1310nm/1550nm
Distance	Dual Fiber MM: 2km Single Fiber SM: 20/40/60/80/100/120km
Power Supply	24VDC (9~36V DC)
Operating Temperature	0~70°C
Humidity	5%~90% non-condensing
Storage Temperature	-40~85°C
Dimension	60mm (H) x 112mm(W) x 138mm(D)
House Protection	IP40 protection, Aluminum Alloy
Installation	DIN-Rail or wall mounting