

ADD-CWDM-MUXDR8EM3-47-61

8ch 19" 1U Rack Mount CWDM Mux and Demux (Duplex), 1471nm - 1611nm, w/Express, 1310, and Monitor ports, Duplex UPC/LC

Features

- 8 Channel CWDM
- 19" 1U Rack Mount Form Factor
- UPC/LC Adapters
- Operating temperature: 0°C to 70°C


Product Description

This is an 8 channel 19" 1U Rack Mount CWDM Mux and Demux that operates over wavelengths 1471nm - 1611nm and it includes Express, 1310, and Monitor ports and duplex LC connectors. This unit can be used as either a multiplexer or de-multiplexer (mux/demux), and is a plug and play system. All of our mux/demux products are 100% compliant and provide a cost effective solution for your network upgrade needs. With our certification test program, we guarantee your product will work correctly the first time.


Specifications

Parameter	Specifications	Unit
Central Wavelength	1271 ~ 1611	nm
Channel Passband	±6.5	nm
Maximum Insertion Loss	8Ch ≤3.0	dB
Isolation – Adjacent Channel	≥ 30	dB
Isolation – Non-Adjacent Channel	≥ 40	dB
Ripple in Passband	≤ 0.3	dB
Temperature Stability	≤ 0.005	dB/°C
Return Loss	≥ 45	dB
Directivity	≥ 55	dB
Maximum Power Handling	500	mW
Operating Temperature	0-70	°C
Storage Temperature	-40 ~ 85	°C

Mux Type Application Diagram



Mechanical Specifications



Parameter	Specifications
Dimensions (Box)	1.75in.(H) x 19in.(W) x 9.8in.(D)
Adapter Type	LC UPC - Standard
Mounting	19" 1U Rack Mount

CWDM Wavelengths

P/N Abbreviation	CWDM Wavelength
47	1471
49	1491
51	1511
53	1531
55	1551
57	1571
59	1591
61	1611

About AddOn Networks

In 1999, AddOn Networks entered the market with a single product. Our founders fulfilled a severe shortage for compatible, cost-effective optical transceivers that compete at the same performance levels as leading OEM manufacturers. Adhering to the idea of redefining service and product quality not previously had in the fiber optic networking industry, AddOn invested resources in solution design, production, fulfillment, and global support.

Combining one of the most extensive and stringent testing processes in the industry, an exceptional free tech support center, and a consistent roll-out of innovative technologies, AddOn has continually set industry standards of quality and reliability throughout its history.

Reliability is the cornerstone of any optical fiber network and is ingrained in AddOn's DNA. It has played a key role in nurturing the long-term relationships developed over the years with customers. AddOn remains committed to exceeding industry standards with certifications from ranging from NEBS Level 3 to ISO 9001:2005 with every new development while maintaining the signature reliability of its products.



U.S. Headquarters

Email: sales@addonnetworks.com

Telephone: +1 877.292.1701

Fax: 949.266.9273

Europe Headquarters

Email: salesupportemea@addonnetworks.com

Telephone: +44 1285 842070