



Specifications

LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available.	DRIVERS	120-277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0-10v dimming input with a range of 1%-100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.
LUMEN MAINTENANCE	Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC.
CONSTRUCTION	1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples.	CLEANING & CARE	Designed to withstand the demands of rigorous cleaning requirements. Effective cleaning and disinfection of environmental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission.
ELECTRICAL	Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 10.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power. For additional information see link: http://www.bodine.com/products/inverter.html	WARRANTY	5 year warranty on all standard components.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'		




I/O Drum

Fixture Options


I/O COLLECTION

SHAPES & DIMENSIONS


8" HEIGHT



12" HEIGHT




24" HEIGHT



CEILING CONNECTIONS


22" DIAMETER 12" canopy standard.

30" - 36" DIAMETER 12" canopy standard



48" DIAMETER | 60" DIAMETER

1000-6000 lumens with or without EM Battery available with 12" canopy standard. 7000+ lumens available only with Ultra Shallow Canopy.



4" OCTAGONAL JUNCTION BOX (BY OTHERS)

Required for powered units;
optional for unlit units

CANOPY/DRESS PLATE FINISH OPTIONS



BLACK

WHITE

STOCK SHADE MATERIALS*



LINEA IVORY
+ NOIR



LINEA IVORY
+ KHAKI



LINEA
IVORY



VEIL
PURE



TRANSLUCENT
SUEDE

*Due to manufacturing and construction process used to create the Essentials and Connected collection, Pattern+ and wood grains will not match at fixture seams. Lead times subject to change.

align Declare



MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS

I/O Drum

Lighting Details

I/O COLLECTION

PERFORMANCE – I/O DRUM 22"

Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
1001	10.99	91.10
1999	22.56	88.60
3000	34.93	85.90
4001	48.15	83.10
5002	62.27	80.30
5999	77.43	77.50
7000	93.76	74.70

PERFORMANCE – I/O DRUM 30"-36"

Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
1000	10.85	92.20
2001	22.03	90.80
3001	33.61	89.30
4001	45.62	87.70
5002	58.07	86.10
6002	70.98	84.60
7004	84.41	83.00
8002	98.39	81.30
8998	112.86	79.70
9998	128.03	78.10
10998	143.90	76.40
11998	160.42	74.80

PERFORMANCE – I/O DRUM 48"-60"

Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
1006	10.80	93.10
1999	21.61	92.50
3005	32.74	91.80
3997	43.85	91.20
5003	55.30	90.50
5996	66.76	89.80
7002	78.58	89.10
7994	90.39	88.40
9000	102.52	87.80
10006	114.87	87.10
10998	127.32	86.40
12004	140.12	85.70
12998	152.93	85.00
14016	166.38	84.20
15008	179.62	83.60
16016	193.33	82.80
17008	207.03	82.20
18012	221.26	81.40
19008	235.47	80.70
20012	250.23	80.00

LIGHT DISTRIBUTION

Based on measurement data

COLOR TEMPERATURE/CRI	MULTIPLIER
2700K / 80	0.98
2700K / 90	0.93
3000K / 80	1.02
3000K / 90	0.97
3500K / 80	1.00
3500K / 90	1.00
4000K / 80	1.08
4000K / 90	1.03

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value = $L_1 \times C_m$ where:

L_1 = (Lumen output at 3500K / 90 CRI) \times

C_m = (Color Temp. / CRI Multiplier) \times

Example:

850LM / 3000K / 80CRI

(850) \times (1.02) = 789LM



MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS

I/O Drum

Part Number Specification

I/O COLLECTION

SPECIFICATION CODE

Example: 2 QTY COL-IO-DRUM-22D-12H-WZ-830CK-STD-WPC-WH

QTY.

COL-IO-DRUM- - - - - - -

1 2 3 4 5 6 7

Complete form to order I/O fixture(s). For each number, make one selection and enter in the corresponding box above.

*Indicates modified choices; additional lead times, cost, and limited lumen outputs may apply.

1 SIZE

- 22D 22" DIA
- 30D 30" DIA
- 36D 36" DIA
- 48D 48" DIA
- 60D 60" DIA

2 HEIGHT

- 8H 8" HEIGHT
- 12H 12" HEIGHT
- 24H 24" HEIGHT

3 MATERIAL

- LIN LINEA IVORY + NOIR
- LIK LINEA IVORY + KHAKI
- LI LINEA IVORY
- VP VEIL PURE
- TS TRANSLUCENT SUEDE
- CUST* CUSTOM COLOR

4 SUSPENSION

- STD 12" - 96"
- EXT* 24" - 240"

5 LED CRI/CCT

<input type="checkbox"/> 827CK	80 CRI / 2700K	<input type="checkbox"/> 930CK	90 CRI / 3000K
<input type="checkbox"/> 830CK	80 CRI / 3000K	<input type="checkbox"/> 935CK	90 CRI / 3500K
<input type="checkbox"/> 835CK	80 CRI / 3500K	<input type="checkbox"/> 940CK	90 CRI / 4000K
<input type="checkbox"/> 840CK	80 CRI / 4000K	<input type="checkbox"/> TW	TUNABLE WHITE
<input type="checkbox"/> 927CK	90 CRI / 2700K		

6 OUTPUT

- 1000LM 1000 LM
- 2000LM 2000 LM
- 3000LM 3000 LM
- 4000LM 4000 LM
- 5000LM 5000 LM
- 6000LM 6000 LM 22"- 36"D Max Tunable White and EM Battery Option
- 7000LM 7000 LM 22"D Max Standard Output
- 8000LM 8000 LM
- 9000LM 9000 LM
- 10000LM 10000 LM
- 11000LM 11000 LM

12000LM 12000 LM 30"- 36"D Max Standard Output

13000LM 13000 LM 48"- 60"D Max Tunable White and EM Battery Option

14000LM 14000 LM

15000LM 15000 LM

16000LM 16000 LM

17000LM 17000 LM

18000LM 18000 LM

1900LM 19000 LM

20000LM 20000 LM 48"- 60"D Max Standard Output

CU* CUSTOM OUTPUT

lm

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION



I/O Drum Part Number Specification

I/O COLLECTION

CONTINUE SPECIFICATION

7 DIMMING AND CONTROLS

- P01 0-10V 1% DIMMING
- LEC* HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
- EBM 0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION
Max Lumen output limited—consult LightArt.
Not available with Tunable White.
- DALI DALI CONTROL

8 CANOPY OPTIONS

- WPC WHITE
- BPC BLACK
- RWPC RECESSED WHITE
- RBPC RECESSED BLACK

9 POWER CORD

- WH WHITE
- BK BLACK

10 CABLE CONNECTION

- CCL CABLES TO CEILING
- CCN CABLES TO CANOPY
Only Available on 22" Diameter—consult LightArt for larger sizes.

*Indicates modified choices; additional lead times, cost, and limited lumen outputs may apply.

 align  Declare



MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS

LightArt

206.524.2223 LIGHTART.COM
4770 OHIO AVE S STE B, SEATTLE, WA 98134

I/O DRUM
02/09/26 UPDATE 5/5