

# Parallelogram Hollow

## Overview

CLOUDFORM COLLECTION



## Specifications

|                   |   |                 |  |
|-------------------|---|-----------------|--|
| LIGHTING          | Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available.  | DRIVERS         | 120-277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0-10v dimming input with a range of 1%-100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.   |
| LUMEN MAINTENANCE | Reported TM-21 Lifetimes<br>L90(17k) = 52,600 hours<br>L80(17k) > 102,000 hours<br>L70(17k) > 102,000 hours   | CERTIFICATION   | Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC. |
| CONSTRUCTION      | 1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples.   | CLEANING & CARE | Designed to withstand the demands of rigorous cleaning requirements. Effective cleaning and disinfection of environmental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission.  |
| ELECTRICAL        | Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 10.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power.<br>For additional information see link:<br><a href="http://www.bodine.com/products/inverter.html">http://www.bodine.com/products/inverter.html</a> | WARRANTY        | 5 year warranty on all standard components.  |
| MOUNTING          | Adjustable stainless steel aircraft cable, contact studio for lengths over 20'. Available with multiple drop height J-hooks for group frame.  |                 |  |



Red List Free  
Ingredients




MADE IN USA  
WITH GLOBAL AND  
DOMESTIC PRODUCTS

# Parallelogram Hollow

Fixture Options

CLOUDFORM COLLECTION

## DIMENSIONS



40" L x 96" W x 4" D

40" L x 96" W x 8" D

## VARIA COLORS OPTIONS



CAULDRON  
N41



ALMOND  
N20



GYPSUM  
N06



JARDIN  
G59



CITYSCAPE  
N45



MOONSTONE  
N31



EARL GREY  
TEAK



TOFFEE  
CHESTNUT



VANILLA  
ASH



HONEY OAT



POME-  
GRANATE  
R37



REDWOOD  
N31



GINGER  
R14



SQUASH  
Y14



VAPOR  
W05



DARK  
MOCHA  
WALNUT



BROWN  
SUGAR  
WALNUT




BOURBON  
CHERRY

# Parallelogram Hollow


CLOUDFORM COLLECTION

## CEILING CONNECTIONS

### CABLES TO CEILING



### 4" OCTAGONAL JUNCTION BOX (BY OTHERS)




### CANOPY/DRESS PLATE FINISH OPTIONS



BLACK      WHITE

## DECK MOUNT



THREADED  
ROD  
*(Provided by Installer)*

ESCUTCHEON  
PLATE


CABLE  
SWAGE

THREADED  
CONNECTOR


STAINLESS  
STEEL  
CABLE

## GRID MOUNT


Contact LightArt for Grid Mount hook options




3.5" AND 4.5" J-HOOKS  
STANDARD OFFERING



4.5" AND 5.5" HOOKS  
1" DROP



5.5" AND 6.5" HOOKS  
2" DROP



6.5" AND 7.5" HOOKS  
3" DROP


# Parallelogram Hollow

## Lighting Details


CLOUDFORM COLLECTION

### LIGHT DISTRIBUTION OPTIONS

Consult factory or [lightart.com](http://lightart.com) for IES files, tested in accordance with IESNA LM79



SIDE VIEW



TOP VIEW

### PERFORMANCE – PARALLELOGRAM HOLLOW

Based on 3500K / 90CRI / Standard Distribution

| NOMINAL LUMEN OUTPUT (LM/FT) | INPUT POWER (W/FT) | EFFICACY (LM/W) |
|------------------------------|--------------------|-----------------|
| 3227                         | 33                 | 100             |
| 4583                         | 46                 | 99              |
| 5898                         | 61                 | 97              |
| 7203                         | 75                 | 96              |
| 8518                         | 90                 | 94              |
| 9824                         | 106                | 93              |
| 11138                        | 122                | 91              |
| 12444                        | 139                | 90              |
| 13758                        | 156                | 88              |
| 15064                        | 174                | 86              |

### LIGHT DISTRIBUTION

Based on measurement data

| COLOR TEMPERATURE/CRI | MULTIPLIER |
|-----------------------|------------|
| 2700K / 80            | 0.98       |
| 2700K / 90            | 0.93       |
| 3000K / 80            | 1.02       |
| 3000K / 90            | 0.97       |
| 3500K / 80            | 1.00       |
| 3500K / 90            | 1.00       |
| 4000K / 80            | 1.08       |
| 4000K / 90            | 1.03       |

### OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value =  $L_1 \times C_m$  where:

$L_1$  = (Lumen output at 3500K / 90 CRI)  $\times$   
 $C_m$  = (Color Temp. / CRI Multiplier)  $\times$

Example:

850LM / 3000K / 80CRI  
(850)  $\times$  (1.02) = 879LM



# Parallelogram Hollow

Part Number Specification

CLOUDFORM COLLECTION

## SPECIFICATION CODE

Example: 2 QTY CLF-LIGHT-PARA-4H-GIN-DM-STD-830CK-550LM-P01-WPC-WH

QTY. CLF-LIGHT-PARA -   -   -   -   -   -   -   -   -  

1 2 3 4 5 6 7 8 9

Complete form to order Cloudform Parallelogram Hollow fixture(s). For each number, make one selection and enter in the corresponding box above.

\*Indicates modified choices; additional lead times, cost, and limited lumen outputs may apply.

## 1 HEIGHT

4H  
 8H

4" HEIGHT  
8" HEIGHT

## 2 MATERIAL

### VARIA COLOR OPTIONS

CAU CHALDRON  
 MOO MOONSTONE  
 JAR JARDIN  
 CIT CITYSCAPE  
 GYP GYPSUM

POM POMEGRANATE  
 RED REDWOOD  
 GIN GINGER  
 SQU SQUASH  
 ALM ALMOND  
 VAP VAPOR

### WOOD PRINT OPTIONS

ESW BROWN SUGAR WALNUT  
 TCH TOFFEE CHESTNUT  
 VAN VANILLA ASH  
 OAT HONEY OAT  
 DMW DARK MOCHA WALNUT  
 EGT EARL GREY TEAK  
 BRC BOURBON CHERRY

## 3 MOUNTING

DM  
 GFM  
 TGRD

DECK MOUNT  
GROUP FRAME MOUNT  
T-GRID MOUNT

## 4 SUSPENSION

STD  
 EXT

12" - 96"  
12" - 240"

## 5 LED CRI / CCT

827CK 80 CRI / 2700K  
 830CK 80 CRI / 3000K  
 835CK 80 CRI / 3500K  
 840CK 80 CRI / 4000K

927CK 90 CRI / 2700K  
 930CK 90 CRI / 3000K  
 935CK 90 CRI / 3500K  
 940CK 90 CRI / 4000K  
 TW TUNABLE WHITE

## 7 OUTPUT

250LM 250 LM/FT  
 350LM 350 LM/FT  
 450LM 450 LM/FT  
 550LM 550 LM/FT Max Tunable White  
 650LM 650 LM/FT Max EM Battery Option  
 750LM 750 LM/FT

850LM 850 LM/FT  
 950LM 950 LM/FT  
 1050LM 1050 LM/FT  
 1150LM 1150 LM/FT  
 CU CUSTOM OUTPUT

lm

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION

align Declare

Red List Free  
Ingredients

MADE IN USA  
WITH GLOBAL AND  
DOMESTIC PRODUCTS

# Parallelogram Hollow

Part Number Specification

CLOUDFORM COLLECTION

CONTINUE SPECIFICATION

## 7 DIMMING AND CONTROLS

- P01 0-10V 1% DIMMING
- LEC\* HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
- EBM 0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION  
*Max Lumen output limited—consult LightArt.*  
*Not available with Tunable White.*
- DALI DALI CONTROL

## 8 CANOPY OPTIONS

- WPC WHITE
- BPC BLACK

## 9 POWER CORD

- WH WHITE
- BK BLACK

\*Indicates modified choices; additional lead times, cost, and limited lumen outputs may apply.

 align  Declare

Red List Free  
Ingredients

 MADE IN USA  
WITH GLOBAL AND  
DOMESTIC PRODUCTS

**LightArt**

206.524.2223 [LIGHTART.COM](http://LIGHTART.COM)  
4770 OHIO AVE S STE B, SEATTLE, WA 98134

PARALLELOGRAM HOLLOW  
02/09/26 UPDATE 6/6