

Somari Pendant

Overview

SOMARI COLLECTION



Specifications

| | | | |
|--------------------------|---|----------------------------|--|
| LIGHTING | Integrated LED light source offering high efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available. | MOUNTING | Hung from power cord. |
| LUMEN MAINTENANCE | Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours | ELECTRICAL | 120-277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0-10v dimming input with a range of 1%-100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%. |
| CONSTRUCTION | Shiro - PLA All Others - PETG (translucent colors) PVC free power cord | CLEANING & CARE | Lightly dust with CO2 canister or swiffer type duster |
| PHOTOMETRICS | Consult factory or website for IES files for performance light core, tested in accordance with IESNA LM79. | CERTIFICATIONS | Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC. |
| HARDWARE | TGIC-free powder coat. Adjustable hanging height. Made with RoHS compliant parts. | WARRANTY | 5 year warranty on all standard components. |



MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS


Somari Pendant

Fixture Options


SOMARI COLLECTION

DIMENSIONS


SAUCER



SMALL SAUCER
5.1" H x 10" D



MEDIUM SAUCER
7.5" H x 10" D



LARGE SAUCER
9.6" H x 10" D

SPHERE



SMALL SPHERE
5.5" H x 6" D



MEDIUM SPHERE
7.7" H x 8" D



LARGE SPHERE
9.6" H x 10" D

CYLINDER



SMALL
CYLINDER
5.4" H x 5" D



MEDIUM
CYLINDER
7.5" H x 5" D



LARGE
CYLINDER
9.8" H x 5" D


CEILING CONNECTIONS

STANDARD CANOPY


For recessed canopy, cut 6" dia hole and recess j-box or mounting structure by 1.5"



SURFACE
MOUNTED




RECESSED




TUNABLE WHITE ONLY


For recessed canopy, cut 11" dia hole and recess j-box or mounting structure by 1.5"




SURFACE
MOUNTED



RECESSED



4" OCTAGONAL JUNCTION BOX (BY OTHERS)




Somari Pendant

Lighting Details


SOMARI COLLECTION

LIGHT DISTRIBUTION OPTIONS

Consult factory or lightart.com for IES files, tested in accordance with IESNA LM79



TOP VIEW



SIDE VIEW

LIGHT DISTRIBUTION

Based on measurement data

| COLOR TEMPERATURE/CRI | MULTIPLIER |
|-----------------------|------------|
| 2700K / 90 | 0.93 |
| 3000K / 90 | 0.97 |
| 3500K / 90 | 1.00 |
| 4000K / 90 | 1.03 |

| MATERIAL | MULTIPLIER |
|----------|------------|
| HALO | 1.00 |
| SHIRO | 0.50 |
| CLOVER | 0.65 |
| SAIL | 0.80 |
| ROSA | 0.90 |
| SIENNA | 0.80 |
| LOOM | 0.65 |

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value = $L_n \times C_m \times S_c$ where:

L_n = (Nominal Lumen output at 3500K / 90 CRI) \times

C_m = (Color Temp. / CRI Multiplier) \times

S_c = (Shade Color Multiplier)

Example:

CYS Nominal / 4000k / 90CRI / Shiro

430LM \times 1.03 \times 0.2 = 89LM approximate fixture output

PERFORMANCE – SOMARI PENDANT

Based on 3500K 90CRI Halo Shade Color

| STYLE | INPUT POWER (W) | NOMINAL LUMEN OUTPUT (LM) | EFFICACY (LM/W) |
|-------|-----------------|---------------------------|-----------------|
| CYS | 6.20 | 430 | 70.40 |
| SAS | 6.20 | 422 | 69.10 |
| SPS | 6.20 | 439 | 71.90 |
| CYM | 10.18 | 734 | 72.10 |
| SAM | 10.18 | 734 | 72.10 |
| SPM | 10.18 | 753 | 74.00 |
| CYL | 14.25 | 1102 | 77.30 |
| SAL | 14.25 | 1062 | 74.50 |
| SPL | 14.25 | 1231 | 86.40 |



MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS

Somari Pendant

Part Number Specification

SOMARI COLLECTION

SPECIFICATION CODE

Example: 2 QTY COL-SOM-PEND-SAL-CV-WHT-STD-927CK-LV01-WPC-WH

COL-SOM-PEND - - - - - - -
QTY. 1 2 3 4 5 6 7 8

Complete form to order Somari Pendant fixture(s). For each number, make one selection and enter in the corresponding box above.

*Indicates modified choices; additional lead times and/or costs may apply.

1 SHAPE

- SAS SAUCER SMALL
- SAM SAUCER MEDIUM
- SAL SAUCER LARGE

- SPS SPHERE SMALL
- SPM SPHERE MEDIUM
- SPL SPHERE LARGE

- CYS CYLINDER SMALL
- CYM CYLINDER MEDIUM
- CYL CYLINDER LARGE

2 FIXTURE COLOR

- HL HALO
- SL SAIL
- CV CLOVER
- RS ROSA
- SI SIENNA
- LM LOOM
- SR SHIRO

3 SHADE CAP COLOR

- WHT WHITE
- BLK BLACK
- SCS SAME COLOR AS SHADE

4 SUSPENSION

- STD 12" - 96"
- EXT 12" - 240"

5 LED CRI / CCT

- 927CK 90 CRI / 2700K
- 930CK 90 CRI / 3000K
- 935CK 90 CRI / 3500K
- 940CK 90 CRI / 4000K
- TW TUNABLE WHITE

6 DIMMING AND CONTROLS

- LV01 0-10V 1% DIMMING 120 & 277V
- LT02 LEADING/TRAILING/TRIAC-5% DIMMING 120V ONLY
- LP01 ELV FORWARD/REVERSE PHASE-1% DIMMING 120V ONLY
- LVP LOW VOLTAGE POE-NO DRIVER PROVIDED FOR POE
Power supply by others.

7 CANOPY OPTIONS

- WPC WHITE
- BPC BLACK
- RWPC RECESSED WHITE
- RBPC RECESSED BLACK

8 POWER CORD

- WH WHITE
- BK BLACK