



Specifications

SHADE		1/32" thick 3form Varia resin. White Opal top and bottom diffuser.	HARDWARE		10"Dia canopy and dress plate mounts to standard junction box (provided by others) 1/16" stainless steel cables to ceiling Adjustable 24"-96" suspension White power cord to canopy
LIGHTING		Solid State LED System 120v-277v input; 24v driver; 0-10v dimming compatible 3000k, 3500k, 4000k options 81 CRI light source 142w Optional Driver Lutron Hi-lume Premier 0.1% EcoSystem constant Voltage LED driver with Soft-on, Fade-to-Black dimming technology	DIMMING		Dimming 0-10v
LUMEN MAINTENANCE		Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L90(17k) > 102,000 hours	MOUNTING		Fully adjustable stainless steel aircraft cable. Contact LightArt for lengths over 20'.
			CERTIFICATION		CSA approved to UL standards Declare label certified Living Building Challenge compliant Damp rated
			WARRANTY		5 year warranty on all standard components. LED system rated for operation in ambient environments up to 25°C.
			STANDARDS		6 week lead time 250+ 3form material options (contact LightArt for custom material pricing) TGIC-free powder coat PVC-free power cord

SPECIFICATION CODE

Example: 2 QTY FIVX-PIV-PC01-GO-830-STD-WP-WH

QTY.

FIVX-PIV-

1

2

3

4

5

6

7

Complete form to order Five X Pivot Circular fixture(s). For each number, make one selection and enter in the corresponding box above.
*Indicates modified choices; additional lead times and/or costs may apply.

1

SIZE

PC01

PC01 83"L × 83"W × 24"H

PC02

PC02 99"L × 71"W × 16"H

PC03

PC03 83"L × 78"W × 24"H

CUST*

CUSTOM CONFIGURATION*

2

MATERIAL

GO

NL

SO

CRCB2VCWZMCRCUST*

GED

GEDNATSILCINCRANVITWIZMIDCUS

3

LED CRI/CCT

830CK

80 CRI / 3000K

835CK

80 CRI / 3500K

840CK

80 CRI / 4000K

4

SUSPENSION

STD

12" – 96"

EXT*

24" – 240"

5

CANOPY OPTIONS

STD

STANDARD

REC*

RECESSED*

6

CANOPY COLOR

WP

WHITE

BP

BLACK

SP

MATTE SILVER

7

POWER CORD

WH

WHITE

BK

BLACK