



Specifications

SHADE		1/32" thick 3form Varia resin. White Opal top and bottom diffuser.	DIMMING		Dimming 0-10v
LIGHTING		Solid State LED System 120v-277v input; 24v driver; 0-10v dimming compatible 3000k, 3500k, 4000k options 81 CRI light source Small - 68w Medium - 92w Large - 116w X-Large - 140w	MOUNTING		Fully adjustable stainless steel aircraft cable. Contact LightArt for lengths over 20'.
LUMEN MAINTENANCE		Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L90(17k) > 102,000 hours	CERTIFICATION		CSA approved to UL standards Declare label certified Living Building Challenge compliant Damp rated
HARDWARE		10"Dia canopy and dress plate mounts to standard junction box (provided by others) Small canopy: 11"L x 6.25"W 3/64" stainless steel cables to ceiling Adjustable suspension Power cord to canopy Silver powder coated center fin	WARRANTY		5 year warranty on all standard components. LED system rated for operation in ambient environments up to 25°C.
			STANDARDS		6 week lead time 250+ 3form material options (contact LightArt for custom material pricing) TGIC-free powder coat PVC-free power cord
			align Declare. Red List Free Ingredients 		

SPECIFICATION CODE

Example: 2 QTY FIVX-RAY-BEAM-47L-GO-830CK-STD-WPC-WH

QTY. FIVX-RAY-BEAM------

1 2 3 4 5 6

Complete form to order Five X Ray fixture(s). For each number, make one selection and enter in the corresponding box above.

*Indicates modified choices; additional lead times and/or costs may apply.

1 CONFIGURATION

- ☐ 47L 47" L × 20" W × 6" H
- ☐ 63L 63" L × 20" W × 6" H
- ☐ 78L 78" L × 20" W × 6" H
- ☐ 94L 94" L × 20" W × 6" H

2 MATERIAL

- ☐ GO GESSO
- ☐ NL NATURAL
- ☐ SO SILKEN OYSTER
- ☐ CR CINDER
- ☐ CB2 CRANBERRY ×2
- ☐ VC VITAMIN C
- ☐ WZ WIZARD
- ☐ MCR MIDCENTURY ROSEWOOD
- ☐ CUST* ☒ CUSTOM COLOR

3 LED CRI/CCT

- ☐ 830CK 80 CRI / 3000K
- ☐ 835CK 80 CRI / 3500K
- ☐ 840CK 80 CRI / 4000K

4 SUSPENSION

- ☐ STD 12" – 96"
- ☐ EXT* 24" – 240"

6 CANOPY COLOR

- ☐ WP WHITE
- ☐ BP BLACK

7 POWER CORD

- ☐ WH WHITE
- ☐ BK BLACK