



Specifications

LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available.	DRIVERS	120–277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0–10v dimming input with a range of 1%–100%. Dim-to-Off standard. Driver can only be accessed from Canopy. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.
LUMEN MAINTENANCE	Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC.
CONSTRUCTION	1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples.	CLEANING & CARE	Designed to withstand the demands of rigorous cleaning requirements. Effective cleaning and disinfection of environmental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission.
ELECTRICAL	Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 10.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power. For additional information see link: <a href="http://www.bodine.com/products/inverter.html">http://www.bodine.com/products/inverter.html</a>	WARRANTY	5 year warranty on all standard components.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'. Available with multiple drop height J-hooks for group frame. Available with Grid hook for T-Grid Frame.		


Build America Buy America Act Compliant

# Circle Hollow

Fixture Options

CLOUDFORM COLLECTION

## DIMENSIONS



## VARIA COLORS OPTIONS

 CAULDRON N41	 ALMOND N20	 GYPSUM N06	 JARDIN G59	 CITYSCAPE N45	 MOONSTONE N31
 POME- GRANATE R37	 REDWOOD N31	 GINGER R14	 SQUASH Y14	 VAPOR W05	




 EARL GREY TEAK	 TOFFEE CHESTNUT	 VANILLA ASH	 HONEY OAT
 DARK MOCHA WALNUT	 BROWN SUGAR WALNUT	 BOURBON CHERRY	

# Circle Hollow


CLOUDFORM COLLECTION

## CEILING CONNECTIONS

### CABLES TO CEILING



### 4" OCTAGONAL JUNCTION BOX (BY OTHERS)




Required for powered units;  
optional for unlit units

### CANOPY/DRESS PLATE FINISH OPTIONS




## DECK MOUNT




## GRID MOUNT

Contact LightArt for Grid Mount hook options




## GRIP HOOK



LIGHT DISTRIBUTION OPTIONS

Consult factory or lightart.com for IES files, tested in accordance with IESNA LM79



PERFORMANCE – CIRCL HOLLOW

Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W/FT)	EFFICACY (LM/W)
1000	11	93
2000	22	91
3000	33	90
4001	45	89
5000	57	88
6001	70	86
7001	84	84
8000	96	83
9000	110	825
10000	125	80

LIGHT DISTRIBUTION

Based on measurement data

COLOR TEMPERATURE/CRI	MULTIPLIER
2700K / 80	0.98
2700K / 90	0.93
3000K / 80	1.02
3000K / 90	0.97
3500K / 80	1.00
3500K / 90	1.00
4000K / 80	1.08
4000K / 90	1.03

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value =  $L_1 \times C_m$  where:

$L_1$  = (Lumen output at 3500K / 90 CRI) ×

$C_m$  = (Color Temp. / CRI Multiplier) ×

Example:

850LM / 3000K / 80CRI

$(850) \times (1.02) = 789\text{LM}$

# Circle Hollow

## Part Number Specification

CLOUDFORM COLLECTION

**SPECIFICATION CODE** Example: 2 QTY CLF-LIGHT-HCIR-4H-GIN-DM-STD-830CK-5000LM-IP-INO-P01-WPC-WH

QTY. CLF-LIGHT-HCIR-  -  -  -  -  -  -  -  -  -  -  -

1 2 3 4 6 7 8 9 10 11 12

Complete form to order Cloudform Circle Hollow fixture(s). For each number, make one selection and enter in the corresponding box above.  
\*Indicates modified choices; additional lead times and/or costs may apply.

**1 HEIGHT**

☐ 4H 4" HEIGHT  
☐ 8H 8" HEIGHT

**2 MATERIAL**

**VARIA COLOR OPTIONS**

☐ CAU ☐ CHALDRON  
☐ MOO ☐ MOONSTONE  
☐ JAR ☐ JARDIN  
☐ CIT ☐ CITYSCAPE  
☐ GYP ☐ GYPSUM

☐ POM ☐ POMEGRANATE  
☐ RED ☐ REDWOOD  
☐ GIN ☐ GINGER  
☐ SQU ☐ SQUASH  
☐ ALM ☐ ALMOND  
☐ VAP ☐ VAPOR

**WOOD PRINT OPTIONS**

☐ ESW ☐ BROWN SUGAR WALNUT  
☐ TCH ☐ TOFFEE CHESTNUT  
☐ VAN ☐ VANILLA ASH  
☐ OAT ☐ HONEY OAT  
☐ DMW ☐ DARK MOCHA WALNUT  
☐ EGT ☐ EARL GREY TEAK  
☐ BRC ☐ BOURBON CHERRY

**3 MOUNTING**

☐ DM DECK MOUNT  
☐ GFM GROUP FRAME MOUNT  
☐ TGRD T-GRID MOUNT

**4 SUSPENSION**

☐ STD 12" - 96"  
☐ EXT 12" - 240"

**5 LED CRI / CCT**

☐ 827CK 80 CRI / 2700K  
☐ 830CK 80 CRI / 3000K  
☐ 835CK 80 CRI / 3500K  
☐ 840CK 80 CRI / 4000K

☐ 927CK 90 CRI / 2700K  
☐ 930CK 90 CRI / 3000K  
☐ 935CK 90 CRI / 3500K  
☐ 940CK 90 CRI / 4000K  
☐ TW TUNABLE WHITE

**6 OUTPUT**

☐ 1000LM 1000 LM  
☐ 2000LM 2000 LM  
☐ 3000LM 3000 LM  
☐ 4000LM 4000 LM  
☐ 5000LM 5000 LM  
☐ 6000LM 6000 LM

☐ 7000LM 7000 LM Max Tunable White and EM Battery Option  
☐ 8000LM 8000 LM  
☐ 9000LM 9000 LM  
☐ 10000LM 10000 LM  
☐ CU\* CUSTOM OUTPUT

lm

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION



CONTINUE SPECIFICATION

7 INSET PANEL

- ☐ IP
- WITH INSET PANEL
- ☐ NIP
- WITHOUT INSET PANEL

8 PANEL MATERIAL

PAINT COLOR OPTIONS

- ☐ TRB

☐ BLF

☐ STC

☐ TOT

☐ SHW

☐ IVL

☐ SOC

☐ TIE

☐ CAY
- TRICORN BLACK

BLACK FOX

STUDIO CLAY

TONY TAUPE

SHOJI WHITE

IVORY LACE

SOCKEYE

TIGEREYE

CAYENNE

☐ INO

☐ SOA

☐ AVA

☐ ALR

☐ BEI

☐ MAC

☐ TRN

☐ ICL

☐ CHE

INVENTIVE ORANGE

SOFT APRICOT

AVID APRICOT

ALMOND ROCA

BEIGE INTENSO

MACADMAIA

TRES NATURALE

ICY LEMONADE

CHEERFUL

☐ BRO

☐ SUG

☐ DUB

☐ POB

☐ LBB

☐ OLW

☐ NPC

BROCCOFLOWER

SUPREME GREEN

DUSTBLU

POWDER BLUE

LITTLE BOY BLU

OLYMPUS WHITE

NO PANEL COLOR

9 DIMMING AND CONTROLS

- ☐ P01
- 0-10V 1% DIMMING
- ☐ LEC\*
- HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
- ☐ EBM
- 0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION  
*Max Lumen output limited—consult LightArt.  
Not available with Tunable White.*
- ☐ DALI
- DALI CONTROL

10 CANOPY OPTIONS

- ☐ WPC
- WHITE
- ☐ BPC
- BLACK

11 POWER CORD

- ☐ WH
- WHITE
- ☐ BK
- BLACK

\*Indicates modified choices; additional lead times and/or costs may apply.